



# FXL400TQT



JOB NAME: \_\_\_\_\_  
 DATE: \_\_\_\_\_  
 TYPE: \_\_\_\_\_

## DESCRIPTION

HPS or MH specification grade flood with Integra Hood glare shield and trunnion mounting bracket. Lamp supplied.

## SPECIFICATIONS

**Finish:**

Chip and fade resistant polyester powder coating.

**Housing:**

Precision die cast aluminum with Wall Bracket, Trunnion or Slipfitter.

**Lens Frame & Glare Shield:**

Precision die cast aluminum. Hinged for easy access. Phillips head screws for added security.

**Lens Gasket:**

High temperature one piece molded silicone set in die cast retaining groove. Remains in place during relamping

**Lens:**

Thermal tempered shock resistant glass, 3/16" thick.

**Reflector:**

Anodized aluminum. Field adjustable beam spread.

**Socket:**

HID: Porcelain 4kv Pulse Rated socket with nickel plated screw shell CFL: Plug in type, GX24q-4 base

**UL Listing:**

Suitable for wet locations. Suitable for mounting within 4' of the ground

**EPA:**

Maximum EPA: 2.0

**Patents:**

Pat. D550,387

**Color:**

Bronze

**Weight:**

36.3

## ORDERING INFORMATION

**High Pressure Sodium**  
Lamp supplied with fixture

Total Watts	Lamp Type	Lamp Base	Ballast	Starting Amps/ Operating Amps				Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
				120V	208V	240V	277V				
400	ED18	Mogul	CWA-HPF QT	3.3/3.8	1.8/2.2	1.5/1.9	1.4/1.7	464	S51	50000	24000

**Factory Installed Options**  
Add suffix to Catalog Number

Swivel Photocontrol wired for 120V (/PCS)  
Single fusing for 120 and 277 volt (/F)

Double fusing for 208 and 240 volt (/FF)  
Button Photocontrol wired for 120V (/PC)

Note: Specifications may change without notice