WHAT YOU NEED TO KNOW ABOUT CO

WHAT IS CO? CO is an invisible, odorless, tasteless gas produced when fossil fuels do not burn completely, or are exposed to heat (usually fire). Electrical appliances typically do not produce CO.

These fuels include: Wood, coal, charcoal, oil, natural gas, gasoline, kerosene, and propane. Common appliances are often sources of CO. If they are not properly main-

tained, are improperly ventilated, or malfunction, CO levels can rise quickly. CO is a real danger now that homes are more energy efficient. "Air-tight mes with added insulation, sealed windows, and other weatherproofing can "trap" CO inside.

SYMPTOMS OF CO POISONING

These symptoms are related to CO POISONING and should be discussed with ALL household members. Mild Exposure: Slight headache, nausea, vomiting, fatigue ("flu-like" symptoms). Medium Exposure: Throbbing headache, drowsiness, confusion, fast heart rate. **Extreme Exposure:** Convulsions, unconsciousness, heart and lung failure. Exposure to Carbon Monoxide can cause brain damage, death.

IMPORTANT!

This CO Alarm measures exposure to CO over time. It alarms if CO levels are extremely high in a short period of time, or if CO levels reach a certain minimum over a long period of time. The CO Alarm generally sounds an alarm before the onset of symptoms in average, healthy adults. Why is this important? Because you need to be warned of a potential CO problem while you can still react in time. In many reported cases of CO exposure, victims may be aware that they are not feeling well, but become disoriented and can no longer react well enough to exit the building or get help. Also, young children and pets may be the first affected. The average healthy adult might not feel any symptoms when the CO Alarm sounds. However, people with cardiac or respiratory problems, infants, unborn babies, pregnant mothers, or elderly people can be more quickly and severely affected by CO. If you experience even mild symptoms of CO poisoning, consult your doctor immediately!

FINDING THE SOURCE OF CO AFTER AN ALARM

Carbon monoxide is an odorless, invisible gas, which often makes it difficult to locate the source of CO after an alarm. These are a few of the factors that can make it difficult to locate sources of CO:

- · House well ventilated before the investigator arrives.
- Problem caused by "backdrafting."

• Transient CO problem caused by special circumstances. Because CO may dissipate by the time an investigator arrives, it may be diffi-cult to locate the source of CO. **BRK Brands, Inc. shall not be obligated to** pay for any carbon monoxide investigation or service call.

POTENTIAL SOURCES OF CO IN THE HOME

Fuel-burning appliances like: portable heater, gas or wood burning fireplace, gas kitchen range or cooktop, gas clothes dryer. Damaged or insufficient venting: corroded or disconnected water heater vent pipe, leaking chimney pipe or flue,

Improper use of appliance/device:

operating a barbecue grill or vehicle

in an enclosed area (like a garage or

clogged chimney opening.

screened porch).

or cracked heat exchanger, blocked or

Transient CO Problems: "transient" or on-again-off-again CO problems can be caused by outdoor conditions and other special circumstances. The following conditions can result in transient CO situations: 1. Excessive spillage or reverse venting of fuel appliances caused by outdoor

conditions such as: • Wind direction and/or velocity, including high, gusty winds. Heavy air in

- the vent pipes (cold/humid air with extended periods between cycles).
- Negative pressure differential resulting from the use of exhaust fans. Several appliances running at the same time competing for limited
- fresh air
- Vent pipe connections vibrating loose from clothes dryers, furnaces, or water heaters.
- Obstructions in or unconventional vent pipe designs which can amplify the above situations. 2. Extended operation of unvented fuel burning devices (range, oven, fireplace).
- Temperature inversions, which can trap exhaust close to the ground. 4. Car idling in an open or closed attached garage, or near a home.

These conditions are dangerous because they can trap exhaust in your home. Since these conditions can come and go, they are also hard to recreate during a CO investigation.

HOW CAN I PROTECT MY FAMILY FROM CO POISONING?

A CO Alarm is an excellent means of protection. It monitors the air and sounds a loud alarm before Carbon Monoxide levels become threatening for average ealthy adults

- A CO Alarm is not a substitute for proper maintenance of home appliances. To help prevent CO problems and reduce the risk of CO poisoning: Clean chimneys and flues yearly. Keep them free of debris, leaves, and nests for proper air flow. Also, have a professional check for rust and corrosion, cracks, or separations. These conditions can prevent proper
- air movement and cause backdrafting. Never "cap" or cover a chimney in any way that would block air flow. Test and maintain all fuel-burning equipment annually. Many local gas or oil companies and HVAC companies offer appliance inspections for
- a nominal fee. Make regular visual inspections of all fuel-burning appliances. Check appliances for excessive rust and scaling. Also check the flame on the burner and pilot lights. The flame should be blue. A yellow flame means fuel is not being burned completely and CO may be present. Keep the blower door on the furnace closed. Use vents or fans when they are available on all fuel-burning appliances. Make sure appliances are vented to the outside. Do not grill or barbecue indoors, or in garages or on screen porches.
- Check for exhaust backflow from CO sources. Check the draft hood on an operating furnace for a backdraft. Look for cracks on furnace heat exchangers.
- · Check the house or garage on the other side of shared wall. • Keep windows and doors open slightly. If you suspect that CO is

escaping into your home, open a window or a door. Opening windows and doors can significantly decrease CO levels. In addition, familiarize yourself with all enclosed materials. Read this manual in its entirety, and make sure you understand what to do if your CO Alarm sounds.

REGULATORY INFORMATION FOR

SMOKE/CO ALARMS

REGULATORY INFORMATION FOR CO ALARMS WHAT LEVELS OF CO CAUSE AN ALARM?

Underwriters Laboratories Inc. Standard UL2034 requires residential CO Alarms to sound when exposed to levels of CO and exposure times as described below. They are measured in parts per million (ppm) of CO over time (in minutes).

- UL2034 Required Alarm Points*:
 If the alarm is exposed to 400 ppm of CO, IT MUST ALARM BETWEEN 4 and 15 MINUTES. If the alarm is exposed to 150 ppm of CO, IT MUST ALARM BETWEEN 10 and 50 MINUTES.
- If the alarm is exposed to 70 ppm if CO, IT MUST ALARM BETWEEN 60 and 240 MINUTES.
- * Approximately 10% COHb exposure at levels of 10% to 95% Relative Humidity (RH).

The unit is designed not to alarm when exposed to a constant level of 30 ppm for 30 days.

IMPORTANT!

CO Alarms are designed to alarm before there is an immediate life threat. Since you cannot see or smell CO, never assume it's not present. An exposure to 100 ppm of CO for 20 minutes may not affect average ealthy adults, but after 4 hours the same level may cause headac • An exposure to 400 ppm of CO may cause headaches in average, healthy

adults after 35 minutes, but can cause death after 2 hours. Standards: Underwriters Laboratories Inc. Single and Multiple Station carbon monoxide alarms UL2034.

According to Underwriters Laboratories Inc. UL2034, Section 1-1.2: "Carbon monoxide alarms covered by these requirements are intended to respond to the resence of carbon monoxide from sources such as, but not limited to, exhaust rom internal-combustion engines, abnormal operation of fuel-fired appliances, and fireplaces. CO Alarms are intended to alarm at carbon monoxide levels below those that could cause a loss of ability to react to the dangers of Carbon Monoxide exposure." This CO Alarm monitors the air at the Alarm, and is designed to alarm before CO levels become life threatening. This allows you precious time to leave the house and correct the problem. This is only possible if Alarms are located, installed, and maintained as described in this manual. Gas Detection at Typical Temperature and Humidity Ranges: The CO Alarm is not formulated to detect CO levels below 30 ppm typically. UL tested for false alarm resistance to Methane (500 ppm), Butane (300 ppm), Heptane (500 ppm), Ethyl Acetate (200 ppm), Isopropyl Alcohol (200 ppm) and Carbon Dioxide (5000 ppm). Values measure gas and vapor concentrations in parts per million.

REGULATORY INFORMATION FOR SMOKE ALARMS RECOMMENDED LOCATIONS FOR SMOKE ALARMS

Audible Alarm: 85 dB minimum at 10 feet (3 meters).


Installing Smoke Alarms in Single-Family Residences The National Fire Protection Association (NFPA), recommends one Smoke Alarm on every floor, in every sleeping area, and in every bedroom. In new construction, the Smoke Alarms must be AC powered and interconnected. See "Agency Placement Recommendations" for details. Continued.

For additional coverage, it is recommended that you install a Smoke Alarm in all rooms, halls, storage areas, finished attics, and basements, where temperatures normally remain between 40° F (4° C) and 100° F (38° C). Make sure no door or other obstruction could keep smoke from reaching the Smoke Alarms. More specifically, install Smoke Alarms:

- On every level of your home including finished attics and basements Inside every bedroom, especially if people sleep with the door partly or completely closed.
- In the hall near every sleeping area. If your home has multiple sleeping areas, install a unit in each. If a hall is more than 40 feet long (12 meters), install a unit at each end. • At the top of the first-to-second floor stairway, and at the bottom
- IMPORTANT!

Specific requirements for Smoke Alarm installation vary from state to state and from region to region. Check with your local Fire Department for current requirements in your area. It is recommended AC or AC/DC units be erconnected for added protection.

EXISTING HOMES NEW CONSTRUCTION



For minimum security install one Smoke Alarm as close to each sleeping area as possible. For more security, put one unit in each room. Many older mobile homes (especially those built before 1978) have little or no insulation. If your mobile home is not well insulated, or if you are unsure of the amount of insulation, it is important to install units on inside walls only. Smoke Alarms should be installed where temperatures normally remain between 40° F (4° C) and 100° F (38° C).

AGENCY PLACEMENT RECOMMENDATIONS IMPORTANT!

Standards: Underwriters Laboratories Inc. Single and Multiple Station Smoke

rooms, basements, and attached garages.

Alarms 217

NFPA 72 (National Fire Code) Chapter 11 "For your information, the National Fire Protection Association's Standard 72, "For your in reads as follows:" 11.5.1 One- and Two-Family Dwelling Units."

"11.5.1.1 Smoke Detection. Where required by applicable laws, codes, or standards for the specified occupancy, approved single- and multiple-station Smoke Alarms shall be installed as follows: (1) In all sleeping rooms. Exception: Smoke Alarms shall not be required in sleeping rooms in existing one- and two-family dwelling units. (2) Outside of each separate sleeping

area, in immediate vicinity of the sleeping rooms. (3) On each level of the dwelling unit, including basements. Exception: In existing one- and two family dwelling units, approved Smoke Alarms powered by batteries are permitted." "A.11.8.3 Are More Smoke Alarms Desirable? The required number of Smoke Alarms might not provide reliable early warning protection for those areas separated by a door from the areas protected by the required Smoke Alarms. For this reason, it is recommended that the householder consider the use of additional Smoke Alarms for those areas for increased protection. The additional areas include the basement, bedrooms, dining room, furnace room, utility room, and hallways not protected by the required Smoke Alarms. The installation of Smoke Alarms in kitchens, attics (finished or unfinished) or garages is not normally recommended, as these locations occasionally experience conditions that can result in improper operation."

California State Fire Marshal (CSFM) Early warning detection is best achieved by the installation of fire detection equipment in all rooms and areas of the household as follows: A Smoke Alarm installed in each separate sleeping area (in the vicinity, but outside bedrooms) and Heat or Smoke Alarms in the living rooms, dining rooms, bedrooms, kitchens, hallways, finished attics, furnace rooms, closets, utility and storage

GENERAL LIMITATIONS OF SMOKE/CO ALARMS

This Smoke/CO Alarm is intended for residential use. It is not intended for use in industrial applications where Occupational Safety and Health Administration (OSHA equirements for Carbon Monoxide Alarms must be met. The Smoke Alarm portion of this device is not intended to alert hearing impaired residents. Special purpose Smoke Alarms should be installed for hearing impaired residents. (CO Alarms are not yet available for the hearing impaired).

Smoke/CO Alarms may not waken all individuals. Practice the escape plan at least twice a year, making sure that everyone is involved – from kids to grand-parents. Allow children to master fire escape planning and practice before holding a fire drill at night when they are sleeping. If children or others do not readily waken to the sound of the Smoke/CO Alarm, or if there are infants or family members with nobility limitations, make sure that someone is assigned to assist them in fire drill and in the event of an emergency. It is recommended that you hold a fire drill while family members are sleeping in order to determine their response to the sound of the Smoke/CO Alarm while sleeping and to determine whether they may need assistance in the event of an emergency.

Smoke/CO Alarms cannot work without power. Battery operated units cannot work if the batteries are missing, disconnected or dead, if the wrong type of batteries are used, or if the batteries are not installed correctly. AC units cannot work if the AC power is cut off for any reason (open fuse or circuit breaker, failure along a power line or at a power station, electrical fire that burns the electrical wires, etc.). If you are concerned about the limitations of battery or AC power, install both types of units

This Smoke/CO Alarm will not sense smoke or CO that does not reach the sensors. It will only sense smoke or CO at the sensor. Smoke or CO may be present in other areas. Doors or other obstructions may affect the rate at which CO or smoke reaches the sensors. If bedroom doors are usually closed at night, we recommend you install an alarm device (Combination CO and Smoke Alarm o separate CO Alarms and Smoke Alarms) in each bedroom and in the hallway This Smoke/CO Alarm may not sense smoke or CO on another level of the

home. Example: This alarm device, installed on the second floor, may not sens smoke or CO in the basement. For this reason, one alarm device may not give

ABOUT SMOKE ALARMS

n different areas of the home.

Battery (DC) operated Smoke Alarms: Provide protection even when electricity fails, provided the batteries are fresh and correctly installed. Units are easy to install, and do not require professional installation. AC powered Smoke Alarms: Can be interconnected so if one unit senses AC with battery (DC) back-up: will operate if electricity fails. AC with battery (DC) back-up: will operate if electricity fails, provided the batteries are fresh and correctly installed. AC and AC/DC units must be

installed by a qualified electrician. Smoke/CO Alarms for Solar or Wind Energy users and battery backup power systems: AC powered Smoke/CO Alarms should only be operated with true or pure sine wave inverters. Operating this Alarm with most battery-

powered UPS (uninterruptible power supply) products or square wave or uasi sine wave" inverters will damage the Alarm. If you are not sure about your inverter or UPS type, please consult with the manufacturer to verify. Smoke Alarms for the hearing impaired: Special purpose Smoke Alarms should be installed for the hearing impaired. They include a visual alarm and an audible alarm horn, and meet the requirements of the Americans With Disabilities Act. Can be interconnected so if one unit senses smoke, all units alarm. Smoke alarms are not to be used with detector guards unless the combination has been evaluated and found suitable for that purpose All these Smoke Alarms are designed to provide early warning of fires if In these should relating and cared for as described in the user's manual, and if smoke reaches the Alarm. If you are unsure which type of Smoke Alarm to nstall refer the National Fire Protection Association (NEPA) Standard 72 National Fire Alarm Code) and NFPA 101 (Life Safety Code). National Fir Protection Association, One Batterymarch Park, Quincy, MA 02269-9101 Local building codes may also require specific units in new construction or

SPECIAL COMPLIANCE CONSIDERATIONS

AWARNING! This unit alone is not a suitable substitute for complete fire detection systems in places housing many people—like apartment buildings, condominiums, hotels, motels, dormitories, hospitals, long-term health care facilities, nursing homes, day care facilities, or group homes of any substitute for complete fire detection systems in warehouses, indust facilities, commercial buildings, and special-purpose non-residential buildings which require special fire detection and alarm systems. ding on the building codes in your area, this unit may be used to provide additional protection in these facilities.

The following information applies to all five types of buildings listed below In new construction, most building codes require the use of AC or AC/DC owered Smoke Alarms only. AC, AC/DC, or DC powered Smoke Alarms can be used in existing construction as specified by local building codes. Refer to NFPA 72 (National Fire Alarm Code) and NFPA 101 (Life Safety Code), local building codes. or consult vour Fire Department for detailed fire protection ements in buildings not defined as "households."

1. Single-Family Residence: Single family home, townhouse. It is recommended this unit be installed on every level of the home, in every bedroom, and in each bedroom hallway.

2. Multi-Family or Mixed Occupant Residence: Apartment building, condominium. This unit is suitable for use in individual apartments or condos provided a primary fire detection system already exists to meet fire detection requirements in common areas like lobbies, hallways, or porches. Using this unit in common areas may not provide sufficient warning to all residents or meet local fire protection ordinances/regulations.

3. Institutions: Hospitals, day care facilities, long-term health care facilities This unit is suitable for use in individual patient sleeping/resident rooms, provided a primary fire detection system already exists to meet fire detection requirements in common areas like lobbies, hallways, or porches. Using this unit in common areas may not provide sufficient warning to all residents or meet local fire protection ordinances/regulations.

4. Hotels and Motels: Also boarding houses and dormitories. This unit is suitable for use inside individual sleeping/resident rooms, provided a primary fire detection system already exists to meet fire detection requirements in common areas like lobbies ballways or porches. Using this unit in common areas may not provide sufficient warning to all residents or meet local fire protection ordinances/regulations.

5. Warehouses/Commercial Buildings: DO NOT use this Smoke/CO Alarm in warehouses, industrial or commercial buildings, special-purpose non-residen-tial buildings, RVs, boats, or airplanes. This Smoke/CO Alarm is specifically designed for residential use, and may not provide adequate protection in sidential application

adequate early warning. Recommended minimum protection is one alarm device in every sleeping area, every bedroom, and on every level of your home. Some experts recommend battery powered Smoke and CO Alarms be used in conjunction with rconnected AC powered Smoke Alarms. For details, see "About Smoke Alarms" or detail

Smoke/CO Alarms may not be heard. The alarm horn loudness meets or exceeds current UL standards of 85 dB at 10 feet (3 meters). However, if the Smoke/CO Alarm is installed outside the bedroom, it may not wake up a sound sleeper or one who has recently used drugs or has been drinking alcoholic beverages. This is especially true if the door is closed or only partly open. Even persons who are awake may not hear the alarm horn if the sound is blocked by distance or closed doors. Noise from traffic, stereo, radio, television, air conditioner, or other appliances may also prevent alert persons from hearing the alarm horn. This Smoke/CO Alarm is not intended for people who are hearing impaired.

The Alarm may not have time to alarm before the fire itself causes damage, injury, or death, since smoke from some fires may not reach the unit immedi-ately. Examples of this include persons smoking in bed, children playing with matches, or fires caused by violent explosions resulting from escaping gas. This Smoke/CO Alarm is not a substitute for life insurance. Though this ke/CO Alarm warns against increasing CO levels or the presence of smoke,

BRK Brands, Inc. does not warrant or imply in any way that they will protect lives. Homeowners and renters must still insure their lives. This Smoke/CO Alarm has a limited life. Although this Smoke/CO Alarm and all of its parts have passed many stringent tests and are designed to be as reliable as possible, any of these parts could fail at any time. Therefore, you must test this device weekly. The unit should be replaced immediately if it is not operating properly. This Smoke/CO Alarm is not foolproof. Like all other electronic devices, this Smoke/CO Alarm has limitations. It can only detect smoke or CO that reaches the sensors. It may not give early warning of the source of smoke or CO is in a remote part of the home, away from the alarm device.

TROUBLESHOOTING GUIDE

If the Alarm	Problem	You should
Horn "chirps" about once per minute.	Low battery warning.	Install two new AA batteries*.
Horn does three "chirps" every minute; LED has 3 rapid flashes with "chirps".	MALFUNCTION SIGNAL. Device is not working properly, and needs to be replaced.	Units under warranty should be returned to manufacturer for replacement. See "Limited Warranty" for details.
The light flashes GREEN and the horn sounds 5 "chirps" every minute.	END OF LIFE SIGNAL. Alarm needs to be replaced.	Immediately replace the Alarm.
Carbon Monoxide Alarm ONLY:		
CO Alarm goes back into alarm 4 minutes after you Silence it.	CO levels indicate a potentially dangerous situation.	IF YOU ARE FEELING SYMPTOMS OF CO POISONING, EVACUATE your home and call 911 or the Fire Department. Refer to "If The CO Alarm Sounds" for details.
CO Alarm sounds frequently even though no high levels of CO are revealed in an investigation.	The CO Alarm may be improperly located. Refer to "Where to Install This Alarm" for details.	Relocate your Alarm. If frequent alarms continue, have home rechecked for potential CO problems. You may be experiencing an intermittent CO problem.
Smoke Alarm ONLY:		
Smoke Alarm sounds when no smoke is visible.	Unwanted alarm may be caused by non-emergency source like cooking smoke.	Silence Alarm using Test/Silence button; clean the Alarm's cover with a soft, clean cloth. If frequent unwanted alarms continue, relocate your Alarm. Alarm may be too close to a kitchen, cooking appliance, or stearny bathroom.

If you have questions that cannot be answered by reading this manual, call Consumer Affairs at 1-800-323-9005, M-F 7:30 a.m. to 5:00 p.m. (CST)

LIMITED WARRANTY

BRK Brands, Inc., ("BRK") the maker of First Alert[®] brand products warrants that for a period of seven years from the date of purchase, this product will be free from defects in material and workmanship. BRK, at its option, will repair or replace this product or any component of the product found to be defective during the warranty period. Replacement will be made with a new or remanufactured product or component. If the product is no longer available, replacement may be made with a similar product of equal or greater value. This is your exclusive warranty. This warranty is valid for the original retail purchaser from the date of initial retail purchase and is not transferable. Keep the original sease receipt. Proof of purchase is required to obtain warranty performance. BRK dealers, service centers, or retail stores selling BRK products do not have the right to alter, modify or any way hange the terms and conditions of this warranty.

This warranty does not cover normal wear of participation of almage resulting from any of the following: negligent use or misuse of the product, use on improper voltage or current, use contrary to the operating instructions, disassembly, repair or alteration by anyone other than BRK or an authorized service center. Further, the warranty does not cover Acts of God, uch as fire, flood, hurricanes and tornadoes or any batteries that are included with this unit. BRK shall not be liable for any incidental or consequential damages caused by the breach of any express or implied warranty. Except to the extent prohibited by applicable law

any implied warranty of merchantability or fitness for a particular purpose is limited in duration to the duration of the above warranty. Some states, provinces or jurisdictions do not allow the exclusion or limitation of incidental or consequential damages or limitations on how long an implied warranty lasts, so the above limitations or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights that vary from state to state or province to province. How to Obtain Warranty Service

Service: If service is required, do not return the product to your retailer. In order to obtain warranty service. contact the Consumer Affairs Division at 1-800-323-9005. 7:30 AM - 5:00 PM Central Standard Time, Monday through Friday. To assist us in serving you, please have the model number and date of purchase available when calling. For Warranty Service return to: BRK Brands, Inc., 25 Spur Drive, El Paso, TX 79906 Battery: BRK Brands, Inc. make no warranty, express or implied, written or oral, including that of merchantability or fitness for any particular purpose with respect to battery.

For your records, please record:	Replace alarm 7 years after installation. Please write the date in the space
	provided:/Month/Year
Date Purchased:Where Purchased:	The alarm will also provide an audible End-of-Life Signal approximately 7 years after installation to remind you to replace the unit.
Date Installed:/Month/Year	The End-of-Life Signal can be silenced for up to 2 days. Do not unplug the alarm or remove the batteries until you get replacement.

First Alert® is a registered trademark of the First Alert Trust.

6

Printed in Mexico M08-0117-007 **Q** 09/10

First Alert **USER'S MANUAL**

COMBINATION CARBON MONOXIDE & SMOKE ALARM




TABLE OF CONTENTS

Introduction	
Fire Safety Tips	
Basic Safety Information	
Installation	
Where to Install This Alarm	1-
Where This Alarm Should NOT Be Installed	• •
How to Install This Alarm	
Optional Locking Features	
Weekly Testing	
Regular Maintenance	
If Your Smoke/CO Alarm Sounds	
What To Do First-Identify The Type Of Alarm	
If the CO Alarm Sounds	
If the Smoke Alarm Sounds	
Using the Silence Features	
What You Need To Know About CO	
What is CO?	
Symptoms of CO Poisoning	•
Potential Sources of CO in the Home	
How Can I Protect My Family From CO Poisoning?	
Regulatory Information For Smoke/CO Alarms	
Regulatory Information for CO Alarms	
Regulatory Information for Smoke Alarms	
About Smoke Alarms	
Special Compliance Considerations	
General Limitations Of Smoke/CO Alarms	
Troubleshooting Guide	
Limited Warranty	
© 2010 BRK Brands, Inc. All rights reserved. Distributed by BRK Brands, Ir 3901 Liberty Street Boad, Aurora II, 60504-8122	

3901 Liberty Street Road, Aurora, IL 60504-8122 Consumer Affairs: (800) 323-9005 • www.firstalert.com

All First Alert[®] Smoke Alarms conform to regulatory requirements, including UL217 and are designed to detect particles of combustion. Smoke particles of varying number and size are produced in all fires. Ionization technology is generally more sensitive than protococom-technology at detecting small particles, which tend to be produced in greater amounts by flaming fires, which consume combustible materials rapidly and spread quickly. Sources of these fires may include paper burning in a wastebasket, or a grease fire in the kitchen. Photoelectric technology is generally more sensitive than ionization technology at detecting large particles, which tend to be produced in greater amounts by smoldering fires, which may smolder for hours before bursting into flame. Sources of these fires may include cigarettes burning in couches or bedding.

For maximum protection, use both types of Smoke Alarms on each level and in every bedroom of your home.

INTRODUCTION

FIRE SAFETY TIPS

- Follow safety rules and prevent hazardous situations: 1) Use smoking materials properly. Never smoke in bed. 2) Keep matches or lighters away from children; 3) Store flammable materials in proper containers; 4) Keep electrical appliances in good condition and don't overload electrical circuits; 5) Keep stoves, barbecue grills, fireplaces and chimneys grease- and debris-free; 6) Never leave anything cooking on the stove unattended; 7) Keep portable heaters and open flames, like candles, away from flammable materials: 8) Don't let rubbish accumulate.
- Keep alarms clean, and test them weekly. Replace alarms immediately if hey are not working properly. Smoke Alarms that do not work cannot aler you to a fire. Keep at least one working fire extinguisher on every floor, and an additional one in the kitchen. Have fire escape ladders or other reliable neans of escape from an upper floor in case stairs are blocked.

BASIC SAFETY INFORMATION IMPORTANT!

- Dangers, Warnings, and Cautions alert you to important operating instructions or to potentially hazardous situations. Pay special attention to these items.
- This Smoke/CO Alarm is approved for use in single-family sidences. It is NOT designed for marine or RV us

ACAUTION! This combination Smoke/Carbon Monoxide Alarm has two separate In its combination Smoke/Carbon Monoxide Alarm has two separal alarms. The CO Alarm is not designed to detect fire or any other gas. It will only indicate the presence of carbon monoxide gas at the sensor. Carbon monoxide gas may be present in other areas. The Smoke Alarm will only indicate the presence of smoke that reaches the sensor. The Smoke Alarm is not designed to sense gas, heat or flames.

AWARNING!

- This Smoke/CO Alarm cannot operate without working batteries Removing the batteries for any reason, or failing to replace the batteries at the end of their service life, removes your pro • NEVER ignore any alarm. See "If Your Smoke/CO Alarm Sounds" for more information on how to respond to an alarm. Failure to respond can result in injury or death.
- The Silence Features are for your convenience only and will not orrect a problem. See "Using the Silence Features" for details. Iways check your home for a potential problem after any alarm. Failure to do so can result in injury or death
- Test this Smoke/CO Alarm once a week. If the Alarm ever fails to test correctly, have it replaced immediately! If the Alarm is not working properly, it cannot alert you to a problem.
- This product is intended for use in ordinary indoor locations of family living units. It is not designed to measure CO levels in compliance with Occupational Safety and Health Administration (OSHA) commercial or industrial standards. Individuals with mediate and different their meru make them mean considing to each or mediate them the standards. medical conditions that may make them more sensitive to carbon monoxide may consider using warning devices which provide audible and visual signals for carbon monoxide concentrations under 30 ppm. For additional information on carbon monoxide

INSTALLATION

and your medical condition contact your physician

WHERE TO INSTALL THIS ALARM

- Minimum coverage for Smoke Alarms, as recommended by the National Fire Protection Association (NFPA), is one Smoke Alarm on every floor, in Swery sleeping area, and in every bedroom (See "Regulatory Information For Smoke Alarms" for details on the NFPA recommendations). For CO Alarms, the National Fire Protection Association (NFPA) recommends that a CO Alarm should be centrally located outside of each separate sleeping area in the immediate vicinity of the bedrooms. For added protection, install additional CO Alarms in each separate bedroom, and on every level of your
- NOTE: For added protection, install an additional Smoke/CO Alarm at leas 15 feet (4.6 meters) away from the furnace or fuel burning heat source where possible. In smaller homes or in manufactured homes where this distance cannot be maintained, install the Alarm as far away as possible from the furnace other fuel burning source. Installing the Alarm closer than 15 feet (4.6 meters will not harm the Alarm, but may increase the frequency of unwanted alarms. In general, install combination Smoke and Carbon Monoxide Alarms: On every level of your home, including finished attics and basements. Inside every bedroom, especially if people sleep with the door partly or
- In the hall near every sleeping area. If your home has multiple sleeping areas, install a unit in each. If a hall is more than 40 feet (12 meters) long, install a unit at each end.
- · At the top of first-to-second floor stairs. • At the bottom of the basement stairs.
- For additional coverage, install Alarms in all rooms, halls, and storage areas, where temperatures normally remain between 40° F and 100° F (4° C and 38° C).

RECOMMENDED PLACEMENT

SUGGESTED AREAS FOR INSTALLING SMOKE ALARMS, CO ALARMS, AND COMBO UNITS KEY: SMOKE ALARMS •• CO ALARMS Ҷ●♦ 🛆 кітсне BOTH, OR COMBINAT SMOKE/CO ALARMS ънаш 🔤 r 🚍 uggested locations are based of r Smoke Alarms and NFPA 720 BASEMENT n Monoxide Alarms). Alw o national and local code

- When installing on the wall, the top edge of Smoke Alarms should be placed between 4 inches (102 mm) and 12 inches (305 mm) from the wall/ceiling line.
- When installing on the ceiling, place the alarm as close to the center as possible.
- In either case, install at least 4 inches (102 mm) from where the wall and eiling meet. See "Avoiding Dead Air Spaces" for more information NOTE: For any location, make sure no door or other obstruction could keep
- carbon monoxide or smoke from reaching the Alarm. Installing Smoke/CO Alarms in Mobile Homes For minimum security install one Smoke/CO Alarm as close to each sleeping

area as possible. For more security, put one unit in each room. Many older mobile homes (especially those built before 1978) have little or no insulation If your mobile home is not well insulated, or if you are unsure of the amount of insulation, it is important to install units on inside walls only.

WHERE THIS ALARM SHOULD NOT BE INSTALLED

- Do NOT locate this Smoke/CO Alarm: • In garages, furnace rooms, crawl spaces and unfinished attics. Avoid
- extremely dusty, dirty or greasy areas. • Where combustion particles are produced. Combustion particles form when something burns. Areas to avoid include poorly ventilated kitchens, garages, and furnace rooms. Keep units at least 20 feet (6 meters) from the sources of combustion particles (stove, furnace, water heater, space heater) if possible. In areas where a 20-foot (6 meter) distance is not possible – in modular, mobile, or smaller homes, for example – it is recommended the Smoke Alarm be placed as far from these fuel-burning sources as possible. The placement recommendations are intended to keep these Alarms at a reasonable distance from a fuel-burning source and thus reduce "unwanted" alarms. Unwanted alarms can occur if a Smoke Alarm is placed directly next to a fuel-burning source. Ventilate nese areas as much as possible.
- Within 5 feet (1.5 meters) of any cooking appliance. In air streams near kitchens. Air currents can draw cooking smoke into the smoke sensor and cause unwanted alarms.
- In extremely humid areas. This Alarm should be at least 10 feet (3 meters) from a shower, sauna, humidifier, vaporizer, dishwasher, laundry room utility room, or other source of high humidity.
- In direct sunlight.
- In turbulent air, like near ceiling fans or open windows. Blowing air may prevent CO or smoke from reaching the sensors. In areas where temperature is colder than 40° F (4° C) or hotter than 100°F
- (38° C). These areas include to conditioned crawl spaces, unfinished attics, uninsulated or poorly insulated ceilings, porches, and garages. • In insect infested areas. Insects can clog the openings to the sensing
- chamber. • Less than 12 inches (305 mm) away from fluorescent lights. Electrical
- " can interfere with the senso • In "dead air" spaces. See "Avoiding Dead Air Spaces".

AVOIDING DEAD AIR SPACES

IMPORTANT!

the pin out of the lock.

nit cannot receive bat

not alarm, replace it immediately.

alarm sounds.

IMPORTANT!

bracket.

bracket.

AWARNING!

ACAUTION!

the terminals on the end of the battery with the

terminals on the unit. Match "+" to "+" and "-" to "-." If the batteries are not fully inserted, the

Push and hold Test/Silence button until the

If the unit does not alarm during testing, DO NOT lock the battery compartment! Install new

tteries and test again. If the unit still does

. Using needle-nose pliers or a utility knife.

detach one locking pin from the mounting

Push the locking pin through the hole near the battery door latch on the back of the Smoke/CO Alarm.

Using needle-nose pliers or a utility knife,

Insert the locking pin through the hole on the back of the Smoke/CO Alarm as

When you attach the Smoke/CO Alarm to

· NEVER use an open flame of any kind to test this unit. You might

 DO NOT stand close to the Alarm when the horn is sounding Exposure at close range may be harmful to your hearing. When testing, step away when horn starts sounding.

It is important to test this unit every week to make sure it is working

properly. Using the test button is the recommended way to test this Smoke/CO Alarm.

2

accidentally damage or set fire to the unit or to your home. The built-in test switch accurately tests the unit's operation as required

ov Underwriters Laboratories, Inc. (UL), NEVER use vehicle exhaust

Exhaust may cause permanent damage and voids your warranty.

the mounting bracket, the locking pin's head will fit into a notch on the bracket.

shown in the diagram.

detach one locking pin from the mounting

TO LOCK THE MOUNTING BRACKET


"Dead air" spaces may prevent smoke from reaching the Smoke/CO Alarm. To avoid dead air spaces, follow installation recommendations below. On ceilings, install Smoke/CO Alarms as close to the center of the ceiling as possible. If this is not possible, install the Smoke/CO Alarm at least 4 inches (102 mm) from the wall or corner.

For wall mounting (if allowed by building codes), the top edge of Smoke/CO Alarms should be placed between 4 inches (102 mm) and 12 inches (305 mm) from the wall/ceiling line, below typical "dead air" spaces. On a peaked, gabled, or cathedral ceiling, install first Smoke/CO Alarm within 3 feet (0.9 meters) of the peak of the ceiling, measured horizontally.

Additional Smoke/CO Alarms may be required depending on the length, angle etc. of the ceiling's slope. Refer to NFPA 72 for details on requirement sloped or peaked ceilings.

HOW TO INSTALL THIS ALARM **IMPORTANT!**

Smoke/CO Alarm was designed to be mounted on the ceiling or wall. It is not a tabletop device. You must install this device on the ceiling or wall as outlined below. Read "Where To Install This Alarm" before




Tools you will need: pencil, drill with 3/16" or 5mm drill bit, flathead screwdriver, hamme

ACAUTION!

- Do not connect this unit to any other alarm or auxiliary device. It is a single-station unit that cannot be linked to other devices. Connecting anything else to this unit may prevent it from working properly. • Do not install this unit over an electrical junction box. Air currents
- around junction boxes can prevent smoke from reaching the sens-ing chamber and prevent the unit from alarming. Only AC powered units are intended for installation over junction boxes

IMPORTANT If you want to lock the battery compartment, or lock the Smoke/CO larm to the mounting bracket, please read the "Optional Locking Features" section.


- 1. Hold base firmly and twist the mounting bracket counterclockwise (left) to separate it from the unit.
- 2. Hold the mounting bracket against the ceiling (or wall) so the vertical mounting slot is aligned in the 12 o'clock position and trace around the inside of the mounting slots (vertical and horizontal mounting)
- 3. Put the unit where it won't get covered with dust when you drill the mounting holes.
- 4. Using a 3/16" (5 mm) drill bit, drill a hole through the center of the oval
- outlines you traced. 5. Insert the plastic screw anchors (in the plastic bag with screws) into the holes. Tap the screw anchors gently with a hammer, if necessary, until they are flush with the ceiling or wall.
- 6. Line the mounting bracket up over the plastic screw anchors. 7. Screw the mounting bracket to the ceiling or wall through the mounting
- slots using the two screws provided. 8. Before attaching the Alarm to




NOTE: The unit may beep briefly when you install the batteries. This is normal. The GREEN Light flashes about every 60 seconds when the unit is

The battery door will resist closing unless batteries are installed. This warns you the unit will not operate without batteries

mounting bracket. Line up the guides on the alarm's base with the guides on the mounting bracket. When guides are lined up, turn the base clockwise (right) until it





TO UNLOCK THE BATTERY COMPARTMENT 1. Remove the Smoke/CO Alarm from the mounting bracket. If the unit is locked to the bracket, see the section "To Unlock the Mounting Bracket." 学の文 2. Insert a flathead screwdriver under the nead of the locking pin, and gently pry it out

- of the battery compartment lock. (If you plan to relock the battery compartment, save the locking pin.)
- 3. To relock the battery compartment, close the battery door and reinsert locking pin in

IMPORTANT! When replacing the batteries, always test the Smoke/CO Alarm before relocking the pattery compartment

TO UNLOCK THE MOUNTING BRACKET

- 1. Insert a flathead screwdriver into the rectangular cut-out on the mounting bracket nearest to the locking pin.
- 2. Pry the Smoke/CO Alarm away from the bracket by pushing up on the screwdriver and turning the Smoke/CO Alarm counterclockwise (left) at the same time.

WEEKLY TESTING

You can test this Smoke/CO Alarm: Press and hold the Test/Silence button 3-5 seconds until unit starts to alarm.

- During testing, you will see and hear the following sequence: • The Horn will sound 3 beeps, pause, 3 beeps. The Power/Smoke LED flashes Red and the CO LED will be Off.
- Next the Horn will sound 4 beeps, pause, 4 beeps. The Power/Smoke LED will be Off and the CO LED flashes Red.
- If the unit does not alarm, make sure the batteries are correctly installed, and test again. If the unit still does not alarm, replace it immediately.

3

silence feature has been activated.

- the terminals on the end of the battery with the terminals on the unit. Match "+" to "+" and -" to "-." If the batteries are not fully inserted, the unit cannot receive battery power. receiving battery power. **AWARNING!** 9. Attach the Smoke/CO Alarm to the
 - snaps into place.
 - NOTE: Once the Smoke/CO Alarm is snapped onto the mounting bracket, you can rotate the Smoke/CO Alarm to adjust the alignment


10. Test the Smoke/CO Alarm. See "Weekly Testing" for details.


The optional locking features are designed to discourage unauthorized removal of the batteries or Alarm. It is not necessary to activate the locks in single-family households where unauthorized battery or Alarm removal is not a concern. This Smoke/CO Alarm has two separate locking features: one to lock the battery compartment, and the other to lock the Smoke/CO Alarm to the mounting bracket fou can choose to use either feature independently, or use them both Tools you will need: • Needle-nose pliers or utility knife • Standard flathead screwdrive Both locking features use locking pins, which are molded into the mounting bracket. Depending on which locking features you use, remove one or both pins from the mounting bracket using needle-nose pliers or a utility knife. To permanently remove either locking pin, insert a flathead screwdriver between the locking pin and the lock, and pry TO LOCK THE BATTERY COMPARTMENT Do not lock the battery compartment until you ctivate the battery and test the Smoke/CO Install the batteries before attaching the Alarm to the bracket. Insert the two (2) AA batteries (included) into the battery compartment. Match

OPTIONAL LOCKING FEATURES

- 4. Reattach the Smoke/CO Alarm to the mounting bracket.







AWARNING!

the unit immediately

IMPORTANT!

Type of Alarm

AWARNING!

vou must not ignore it!

echnician here:

AWARNING!

injury or death.

AWARNING!

Alarms[#] for details.

AWARNING!

Smoke

Carbon Monoxide (CO)

This unit has been designed to be as maintenance-free as possible, but there are a few simple things you must do to keep it working properly.

Use only the replacement batteries listed below. The unit may not operate properly with other batteries. Never use rechargeable batteries since they may not provide a constant charge. Test it at least once a week.

 Clean the Smoke/CO Alarm at least once a month; gently vacuum the outside of the Smoke/CO Alarm using your household vacuum's soft brush attachment. A can of clean compressed air (sold at computer or a structure). office supply stores) may also be used. Follow manufacturer instructions for use. Test the Smoke/CO Alarm. Never use water, cleaners or solvents since they may damage the unit.

• If the Smoke/CO Alarm becomes contaminated by excessive dirt, dust and/or grime, and cannot be cleaned to avoid unwanted alarms, replace Relocate the unit if it sounds frequent unwanted alarms. See "Where This Alarm Should Not Be Installed" for details.

Choosing a replacement battery:

Your Smoke/CO Alarm requires two standard AA batteries. The following batteries are acceptable as replacements: Eveready Energizer E91. These batteries are available at many local retail stores.

Actual battery service life depends on the Smoke/CO Alarm and the environment in which it is installed. All the batteries specified above are acceptable replacement batteries for this unit. Regardless of the manufacturer's suggested battery life, you MUST replace the battery immediately once the unit starts "chirping" (the "low battery warning").

To replace the batteries (without removing Alarm from the ceiling or wall):

Open the battery compartment. 2. Press tabs A and B as shown in the diagram and remove each battery.

3. Insert the new batteries, making sure they snap completely into the battery compartment. Match the terminals on the ends of the batteries with the terminals on the unit.

4. Close the battery compartment, and then test the unit by pressing the Test/Silence button.



IF YOUR SMOKE/CO ALARM SOUNDS

WHAT TO DO FIRST-IDENTIFY THE TYPE OF ALARM What You See and Hear

What fou See and Hear	
CO LED: Flashes Red Horn: 4 beeps, pause, 4 beeps, pause Power/Smoke LED: Off	
Power/Smoke LED: Flashes Red Horn: 3 beeps, pause, 3 beeps, pause CO LED: Off	

IF THE CO ALARM SOUNDS

ALARM-MOVE TO FRESH AIF If you hear the CO alarm horn and the CO red light is flashing, move everyone to a source of fresh air. DO NOT remove the batteries!

Actuation of your CO Alarm indicates the presence of carbon monoxide (CO) which can kill you. In other words, when your CO Alarm sounds,

IF THE CO ALARM SIGNAL SOUNDS: 1. Operate the Test/Silence button.

2. Call your emergency services, fire department or 911. Write down the number of your local emergency service here:

3. Immediately move to fresh air—outdoors or by an open door or window. Do a head count to check that all persons are accounted for. Do not re-enter the premises, or move away from the open door or window until the emergency services responder has arrived, the premises have been aired out, and your CO Alarm remains in its normal condition.

 After following steps 1-3, if your CO Alarm reactivates within a 24-hour period, repeat steps 1-3 and call a qualified appliance technician to inves-tigate for sources of CO from fuel-burning equipment and appliances, and inspect for proper operation of this equipment. If problems are identified during this inspection have the equipment serviced immediately. Note any combustion equipment not inspected by the technician, and consult the manufacturers' instructions, or contact the manufacturers directly, for more information about CO safety and this equipment. Make sure that motor vehicles are not, and have not, been operating in an attached garage or adjacent to the residence. Write down the number of a qualified appliance

NOTE: A qualified appliance technician is defined as "a person, firm, corporation, or company that either in person or through a representative, is engaged in and responsible for the installation, testing, servicing, or replacement of heating, ventilation, air conditioning (HVAC) equipment, combustion appliances and equipment, and/or gas fireplaces or other decorative combustion

IF THE SMOKE ALARM SOUNDS

RESPONDING TO AN ALARM

If the unit alarms and you are not testing the unit, it is warning you of a potentially dangerous situation that requires your immediate attention. NEVER ignore any alarm. Ignoring the alarm may result in

 Never remove the batteries from a battery operated Smoke/CO Alarm to stop an unwanted alarm (caused by cooking smoke, etc.). Removing batteries disables the alarm so it cannot sense smoke, and removes your protection. Instead open a window or fan the smoke away from the unit. The alarm will reset automatically. If the unit alarms get everyone out of the house immediately

WHAT TO DO IN CASE OF FIRE

 Don't panic; stay calm. Follow your family escape plan. Get out of the house as quickly as possible. Don't stop to get

sed or collect anything. Feel doors with the back of your hand before opening them. If a door is cool, open it slowly. Don't open a hot door. Keep doors and windows closed, unless you must escape through them. Cover your nose and mouth with a cloth (preferably damp).

Take short. shallow breaths. Meet at your planned meeting place outside your home.

and do a head count to make sure everybody got out safely.

 Call the Fire Department as soon as possible from outside. Give your address, then your name

• Never go back inside a burning building for any reason.

• Contact your Fire Department for ideas on making your home safer.

Alarms have various limitations. See "General Limitations of Smoke/CO

USING THE SILENCE FEATURES

Never remove the batteries to quiet an unwanted alarm. Removing the batteries disables the alarm and removes your protection

The Silence Feature is intended to temporarily silence the horn while you identify and correct the problem. Do not use the Silence Feature in emergency situations. It will not correct a CO problem or extinguish a fire.

The Silence Feature can temporarily quiet an unwanted alarm for several minutes. Press the Test/Silence button on the alarm cover for at least 3-5 seconds. After the Test/Silence button is released, the Red LED blinks during the silence

When the Smoke Alarm is Silenced	When the CO Alarm is Silenced
The Smoke Alarm will remain silent for up to 15 minutes, then return to normal	The CO alarm will remain silent for up to 4 minutes.
operation. If the smoke has not cleared-or continues to increase-the device will go back into alarm.	After 4 minutes, if CO levels remain potentially dangerous the horn will start sounding again.

SILENCING THE LOW BATTERY WARNING

This silence feature can temporarily quiet the low battery warning "chirp" for up to 8 hours. Press the Test/Silence button on the alarm cover. Once the low battery warning "chirp" silence feature is activated, the unit continues to flash the Green light once a minute for 8 hours. After 8 hours, the low batterv "chirp" will resume. Replace the batteries as soon as possible; this unit will not operate without battery power! To deactivate this feature: Press the Test/Silence button again. The unit will go into Test Mode and the low battery warning will resume (LED flashes and unit sounds "chirp" once a minute).

SILENCING THE END OF LIFE SIGNAL

This silence feature can temporarily quiet the End of Life warning "chirp" for up to 2 days. You can silence the End of Life warning "chirp" by pressing the Test/Silence button. The horn will chirp, acknowledging that the End of Life

After approximately 2 days, the End of Life "chirp" will resume. After approximately 2-3 weeks the End of Life warning cannot be silenced. 4