

BARBECUE LIGHTS BQ-08-FC,-FD-SERIES

SPECIFICATIONS

CONSTRUCTION: Cast aluminum bullet (BQ-08-FC) mounted to 24" or 36" (designated -36) stainless steel flex arm, chrome plated with black polyolefin shrink cover

CLAMP: 5" heavy duty stainless steel C-clamp with 6" black plastic T-handle

SWITCH: On/off push button control with rubber boot cover

WIRING: 12v. models: 18/2 black zip cord, 7 foot length from base of fixture, 120 v. models: 9" black SJT-WA grounded power cord supplied

CONNECTION: Optional FA-05 Quick Connector required to attach fixture lead to main cable of landscape lighting system.

SOCKET: MR16 (12v.); GU5.3 ceramic bi-pin with 250° C silicone lead wires, MR11; GZ4 ceramic bi-pin with 250°C silicone lead wires, MR16 (120v.) medium base ceramic with 200°C silicone lead wires

LAMP LIFE: MR16 (12v.); 5000 hours average rating, MR11 (12v.); 2000 hours average rating, MR16 (120v.); 2500 hours

STANDARD FINISH: Black texture polyester powder coat. With powder coat options, fixture heads will have black shrink tubing over flex arms, clamp will have black finish-optional finishes available

CONSTRUCTION: Stainless steel or cast aluminum bullet (BQ-08-FD-SS) mounted to 24" or 36" (designated -36) stainless steel flex arm, chrome plated with black polyolefin shrink cover

BASE AND SWITCH: New style cast stainless steel base with on/off push button control with rubber boot cover

WIRING: 12v. models: 18/2 black zip cord, 7 foot length from base of fixture, 120 v. models:

SOCKET: MR16; GU5.3 ceramic bi-pin with 250°C silicone lead wires, MR11; G24 ceramic bi-pin with 250°C silicone lead wires, MR16 (120v.) medium base ceramic with 200°C silicone lead wires

LAMP LIFE: MR16 (12v.); 5000 hours average rating, MR11 (12v.); 2000 hours average rating, MR16 (120v.); 2500 hours average rating

CONNECTION: Optional FA-05 Quick Connector required to attach fixture lead to main cable of landscape lighting system. (12 volt only)

STANDARD FINISH: Black texture polyester powder coat-optional finishes available

ODERING INFORMATION

| CATALOG NO. | DESCRIPTION | ARM LENGTH | LAMP SUPPLIED | STANDARD FINISH |
|---|--|--------------|--|----------------------------------|
| 12 VOLT | | | | |
| Transformer required for all | low-voltage BBQ lights. | | | |
| BQ-08-FC BQ-08-FC-SS | Cast aluminum bullet Stainless steel bullet | t 24" 24" | 20w MR16 FL (BAB) 20w MR16 FL (BAB) | Black texture Stainless steel |
| BQ-08-FC-36 BQ-08-FC-36-SS | Cast aluminum bullet Stainless steel bullet | 36" 36" | 20w MR16 FL (BAB) 20w MR16 FL (BAB) | Black texture Stainless steel |
| BQ-08-FD BQ-08-FD-SS | Cast aluminum bullet Stainless steel bullet | t 24" 24" | 20w MR16 FL (BAB) 20w MR16 FL (BAB) | Black texture Stainless steel |
| BQ-08-FD-36 BQ-08-FD-36-SS 120 VOLT | Cast aluminum bullet Stainless steel bullet | 36" 36" | 20w MR16 FL (BAB) 20w MR16 FL (BAB) | Black texture Stainless steel |

9" black SIT-WA grounded power cord supplied with all 120v Flex Clamp fixtures

| 9 black 331-WA grounded pow | ei coid supplied with all 1200 | . Flex Claffip | lixtules. | |
|-----------------------------|--------------------------------|----------------|--------------------|-----------------|
| BQ-08-FC-MR16-120V | Cast aluminum bullet | 24" | 35w med. base MR16 | Black texture |
| BQ-08-FC-36-MR16-120V | Cast aluminum bullet | 36" | 35w med. base MR16 | Black texture |
| BQ-08-FC-MR16-120V-SS | Stainless steel bullet | 24" | 35w med. base MR16 | Stainless steel |
| BQ-08-FC-36-MR16-120V-SS | Stainless steel bullet | 36" | 35w med. base MR16 | Stainless steel |
| BQ-08-FD-MR16-120V | Cast aluminum bullet | 24" | 35w med. base MR16 | Black texture |
| BQ-08-FD-MR16-120V-SS | Stainless steel bullet | 24" | 35w med. base MR16 | Stainless steel |
| BQ-08-FD-36-MR16-120V | Cast aluminum bullet | 36" | 35w med. base MR16 | Black texture |
| BQ-08-FD-36-MR16-120V-SS | Stainless steel bullet | 36" | 35w med. base MR16 | Stainless steel |
| | | | | |



FOCUS INDUSTRIES INC. 25301 COMMERCENTRE DRIVE LAKE FOREST. CA 92630

BQ-08-FD

Type: Job Name:

JOB INFORMATION

www.focusindustries.com sales@focusindustries.com (949) 830-1350 • FAX (949) 830-3390

12v. fixtures: 25 foot 16/2 fixture lead wire available; add -25F to catalog number. For use with Focus CPC or hub supplied by others.

| ı | FSA-00 | | | | | | | | <u> </u> | ARE FUREST, CA | 1 92030 | (343) 63 | 0-1330 • FAX (3 | 49) 630-3390 |
|---|-------------------------|-----------------------------|------------------|-------------------|-------|------------------|-------------------|------|-------------------|--------------------|---------|-----------------|------------------|----------------|
| | Powder Coat Finishes | Black Texture (Standard) | Antique Verde | Bronze Texture | Camel | White Texture | Hunter Texture | Rust | Weathered Iron | Weathered Brown | Stucco | Rubbed Verde | Chrome Powder | Terra Cotta |
| | Ordering Code | -BLT | -ATV | -BRT | -CAM | -WTX | -HTX | -RST | -WIR | -WBR | -STU | -RBV | -CPR | -TRC |



| BQ-08-FC 5" | BQ-08-FC-36 |
|---------------|---|
| 2.6° 5° 127mm | 2.6" 66mm |
| | Note: Drawing of fixtures shown with arm extended upward to illustrate length only. Hat must be pointed downwards for proper operation. |

BQ-08-FD-36

| C CUSTED US |
|-------------|
|-------------|