

WELL LIGHTS SL-20-SM





SPECIFICATIONS (for 12v)

CONSTRUCTION: Sealed bronze fiberglass reinforced composite

O-RING: Red high temperature silicone LENS: Clear convex tempered glass

LAMP SUPPLIED: 20 watt MR16 FL (BAB) with front glass (50 watt max.); 5000 hours average rating

LAMP SUPPLIED

20 watt MR16 FL(BAB)

20 watt MR16 FL(BAB)

LAMP OPTIONS: 20 watt MR16 ULTRA; 10,000 hours average rating,

20 watt MR16 TITAN 18,000 hours average rating or 4w ARROW LED 50,000 average rating

SOCKET: High temperature ceramic GU5.3 Bi-pin with 250° silicone lead wires

LAMP LIFE: 5000 hours average rating for MR16 **REFLECTOR:** Spun aluminum painted gloss white

DESCRIPTION

50 watt maximum Sealed composite grated

Sealed composite lensed

well light,

well light

WIRING: Black 4ft. 18/2 SPT-1W

CATALOG NO.

SL-20SMG-MR16

SL-20SML-MR16

12 VOLT INPUT.

CONNECTOR: FA-05 Quick Connector for 12v. model only (not supplied)

FINISH: Optional finishes available ORDERING INFORMATION



STANDARD FINISH

Bronze composite

Bronze composite







SL-20SML-MR16 with FA-135SM

SL-20SML-MR16



SL-20SMG-MR16 SL-20SML-MR16

SL-20SML-MR16 with FA-135SM





2x .50 Female NPS threaded ports BOTTOM available upon request

SPECIFICATIONS (for 120v)

CONSTRUCTION: Sealed bronze composite O-RING: Red high temperature silicone LENS: Clear convex tempered glass

SOCKET: High temperature ceramic medium base with 150°C silicone lead wires, and brass nickel plated screw shell LAMP LIFE: 2000 hours average rating for medium base

REFLECTOR: Spun aluminum painted high reflectance gloss white


WIRING: Standard wiring for 120 volt black, White & ground, 12" leads, 18 gauge.

FINISH: Optional finishes available

CATALOG NO.	DESCRIPTION	LAMP SUPPLIED	STANDARD FINISH		
120 VOLT INPUT	50 watt maximum				
SL-20SMG-PAR20	50w Par20 Sealed Bronze Grated Well Light	None	Bronze composite		
SL-20SML-PAR20	50w Par20 Sealed Bronze Lensed Well Light	None	Bronze composite		

LIGHT DISTRIBUTIONS

AND PHOTOMETRICS



20w MR16 FL (BAB)

LAKE FOREST, CA 92630

50w PAR20 (H/NFL)

(949) 830-1350 · FAX (949) 830-3390

ACCESSORIES

CATALOG NO. DESCRIPTION

FA-133SM/BRS Cast Aluminum/Brass Lens Holder FA-134SM/BRS Cast Aluminum/Brass Grate FA-135SM/BRS Stamped Aluminum/Brass Eyebrow Round 1/4" Mini Cell Louver FA-08-06 FA-10-SL20SMAMBER



Flat Amber Tempered Glass Lens SL-20-SM MR16/PAR20 FA-10-SL20SMBLUE Flat Blue Tempered Glass Lens SL-20-SM MR16/PAR20 FA-10-SL20SMGREEN Flat Green Tempered Glass Lens SL-20-SM MR16/PAR20 FA-10-SL20SMRED Flat Red Tempered Glass Lens SL-20-SM MR16/PAR20

FA-98-SL20SM Flat Linear Tempered Glass Lens SL-20-SM (SKYTEX) MR16/PAR20 Convex Glass Lens FOR SL-20-SM MR16/PAR20 FA-99-SL20SM FA-104-SL20SM Flat Softner Tempered Glass Lens SL-20-SM (SOLITE) MR16/PAR20

FA-104SB-20 Flat Softner Tempered Glass Lens SL-20-SM (Sand blasted) MR16/PAR20 FA-FORM-SL20SM Concrete form for SL-20SM Series

Please specify at time of order, MR16 or PAR20



Hex Cell Louve

FSA-00





FA-134SM/-BRS Stamped Aluminum/ Brass Grate



FA-135SM/-BRS Stamped Aluminum/ **Brass Evebrow**



2.90'

FA-98-20

2.90

74mm FA-104-20

FA-FORM-SL20SM Concrete Mold

2.90"

ı	FOCUS INDUSTRIES INC. 25301 COMMERCENTRE DRIVE	www.focusindustries.com sales@focusindustries.com						
	Notes:							
	Contractor:							
	Specifier:							
ı	Lamp(s):							
/	Cat. No.:	_						
)	Job Name:							
	Туре:	Date:						
	JOB INFORMATION							

Powder Coat Finishes	Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Terra Cotta
Ordering Code	-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-TRC