

**New Integra Hood for Friendly Lighting.** Awesome performance with quality and value from this compact 400 & 250 watt HID flood.

2" Integra Hood to reduce light trespass and glare

Better heat sinking of components

Reflector designed for precise heam control

Precision die cast aluminum housing with durable bronze powder coat finish

4" and 9" Hoods, Wire Guard and Polycarbonate Shield optional

Stainless Steel External Hardware

Sharp Light Cutoff Long Life Lamp supplied Floodzilla



with no hood

/ Line

Integra Hood

Supplied with 3' of STW cord (trunnion only)

Rugged Trunnion or Slip Fitter Mounting

## Floodzilla Trunnion

New clean design, compact, tough and good looking cast aluminum housing with 2" Integra Hood, steel trunnion mount for easy surface mounting and aiming flexibility. Factory wired for 277V. Lamp supplied.

Finish: Bronze



## Floodzilla Slipfitter Floodzilla with integral slip fitter for O.D 2 3/8" tenon size. Slipfitter joint adjusts over 180° arc. Factory wired

for 277V. Lamp supplied.

Finish: Bronze





Floodzilla & Guard

Glare Hoods field install in minutes

to further reduce glare and light

tresspass. Available in 4 1/2" or 9"

lengths. Guard is chrome plated

heavy gauge wire to provide

Glare Hood Finish: Bronze


protection.

Hood. Shield

## Polycarbonate Shield

1/4" thick clear polycarbonate shield protects lens and lamp. Standoffs securely attach the shield to the cover in minutes.





## Lamps LHPS250 BHPSH250QT BHPSH400QT LMH200PS BMHH200PSQ LMH250PS BMHH250PSQ LMH320PS BMHH320PSQ LMH350PS BMHH350PSQ LMH400PS BMHH400PSQ

Can be used with 4" & 9" glare hood

# **Product Information**

**High Pressure Sodium** Lamp supplied with fixture

Lamp supplied with fixture E = Pulse Start

**Metal Halide** 

PSQ & QT=Quad Tap=120 / 208 / 240 / 277 volts

**Factory Installed Options** Add suffix to catalog number

Accessories for Field Installation

# Specifications (4) us

# **UL Listing:**Suitable for wet locations. Suitable for

mounting within 4' of the ground.

## **Housing:** Precision die cast aluminum

Reflector:

## High quality anodized aluminum Lens:

Tempered thermal shock resistant glass


## Lens Gasket:

Molded one-piece silicone in die cast retaining groove to remain in place during relamping.

## Socket:

Glazed porcelain 4kv pulse rated with nickel plated screw shell and spring contacts.

Chip and fade resistant Bronze polyester powder coat finish.



Pulse Start

Complies with EISA 2007

250

400

**200** 

**250** 

**320** 

**350** 

**=**400

**Button Photocontrol** 

Glare hood 4" length Glare hood 9" length Polycarbonate shield Wire Guard

480 volt only ballast (consult factory)

Swivel Photocell

Twistlock PC

Weight:

Fixture

HPS250

HPS400

Patents:

lbs

33

intellectual property laws.

MH200

MH250

MH320 MH350

MH400

D115,510 & D115,521 and Taiwan patents D121,170 & D121,172 and international

vw.rabweb.com

Spec sheets • EZ Lighting Layouts

Photometrics · Wiring Diagrams IES Files • Installation Instructions



7V	Watts	ANSI	Lumens	Hours	Catalog Numbers
/1.1	295	S50	28,500	24,000	FZS250QT
1.7	464	S51	50,000	24,000	FZS400QT
.9	232	M136	19,000	15,000	FZH200PSQ
1.1	288	M138	22,000	12,000	FZH250PSQ
1.4	368	M132	30,000	20,000	FZH320PSQ
1.6	400	M131	33,300	20,000	FZH350PSQ
1.8	450	M135	40,000	20,000	FZH400PSQ
_	Specify Photocell voltage				/PC
					/PCS
					/PCT
					/480

outured Marrisons
FZS250QT FZS400QT
FZH200PSQ FZH250PSQ FZH320PSQ FZH350PSQ
FZH400PSQ

H400PSQ	FZI
C CS CT	/PC /PC /PC
80	/48

# FZS250SFQT FZS400SFQT FZH200SFPSQ FZH250SFPSQ EZH320SEPSO FZH350SFPSQ H400SFPSQ



Wire Guard


FZH4	(4" length Glare hood)
FZH9	(9" length Glare hood)
GDFZP	(Polycarbonate shield)
GDFZW	(Wire Guard)

Poles, Bullhorns and Mounting Brackets available See pages 64-69




# **Photometrics**

Floodlighting 400w HPS @ 30' Mounting Height **Effective Projected Area:** Maximum EPA = 1.3 Aimed 45° below horizon Fixture




1 0 1 Multiples of Mounting Ht Values shown in Footcandles				
	Mounting Height Multiplier		Multi HPS	plier MH
15	4.0	<b>E</b> 200	-	.4
20	2.3	250	.6	.4
30	1.0	<b>E</b> 250	-	.5
35	.7	<b>320</b>	-	.6
40	.6	<b>E</b> 350	-	.7
		400	-	.7
		<b>E</b> 400	1.0	.8


# Sign & Wall Lighting 400w HPS @ 10' Mounting Distance Aimed 45° above horizon




Mountii Height	ng Multiplier	Watts	Multiplier HPS MH	
5	4.0	<b>200</b>	-	.4
10	1.0	250	.6	.4
12	.7	<b>E</b> 250	-	.5
15	.4	<b>320</b>	-	.6
		<b>350</b>	-	.7
		400	1.0	.7
		<b>a</b> 400	-	.8

# **Dimensions**







√ 10.2cm



