

**Classic Landscape Lawn Lights** packed with rugged features. Now with Energy Saving CFL and Self-Ballasted Fluorescent





Rugged die cast aluminumhousing with durable powder coating.

Socket with all copper electrical parts and 20" leads

Quick and secure installation with one corrosionproof screw

Threaded, gasketed globes for durable weatherproofing and easy relamping

12" color matched mounting stemwith 1/2" threads available



Includes easy mounting 1/2" threaded nipple



Rugged path lights with louvers to direct light downward blendwith any landscaping.



# **Product Information**

Incandescent (120 volt)

NPF 120 volt ballast

Lamp supplied with fixture. Minimum operating temperature 32ºF

#### **Self Ballasted Compact** Fluorescent Lamps

Lamp supplied with fixtures Minimum operating temperature -20°F

.amp Natts			Initial Lumens		
75	A-19	Med	1220	750	
100	A-19	Med	1650	750	
13	Quad	GX23-2	860	10,000	
13 23	Spiral Spiral	Med Med	870 1450	10,000 10,000	

# Specifications 💵

#### **UL Listing:**

Suitable for wet locations. Suitable for mounting within 4 feet of the ground.

Medium base porcelain with all copper electrical parts and 20" leads, including a ground lead.

Incandescent- (not supplied) Medium base A-19 lamps, 120V. 4-tier - 100 watt max. 3-tier - 75 watt max. Fluorescent- (supplied) 13 watt quad tube NPF 120v ballast, GX23-2 base

13w self ballasted spiral lamp, Med. base 23w self ballasted spiral lamp, Med. base

#### Globes:

Threaded, gasketed globe protects against weather, garden sprinklers and insects. Clear glass GL100 globes standard for 4 Tier. Clear glass GL60 globes standard for 3 Tier.

#### **Housing:**

Die cast aluminum housing with powder coat finish.

#### Voltage:

120 volts AC

#### Patents:

The designs of RAB fixtures are protected under U.S. and international intellectual property laws.

#### **Replacement Parts:**

<u>Part</u> Catalog # Socket SLL GL100 Globe for 4 tier -clear Globe for 4 tier -white GL100W Globe for 3 tier - clear GL60

#### **Mounting Stem:**

Accessory 12" mounting stem with 1/2" threads on both ends available Catalog # 12" Stem Verde Green ST12VG 12" Stem Black

#### **Mighty Post Mounting:**

See page 116.

### Info Online 24/7



For sturdy Lawn Light mounting,

use RAB Mighty Posts (see pages 116-117)

> Wiring Diagrams Installation Instructions Product Specifications



### Four Tier 6"

Rugged die cast aluminum 6" diameter housings. Threaded, gasketed clear glass globe for durable weatherproofing and easy relamping. 1" long, 1/2" threaded nipple included for easy mounting. 100 watt max. Incandescent lamp not supplied.

Black

Verde Green

Finish:



#### **Four Tier Flare**

10" diameter top tier, 6" diameter lower tier. Rugged die cast aluminum housings. Threaded, gasketed clear glass globe for durable weatherproofing and easy relamping. 1" long, 1/2" threaded nipple included for easy mounting. 100 watt max. Incandescent lamp not supplied. Fluorescent lamp supplied.

### Finish: Black



### **Three Tier 6"**

Rugged die cast aluminum 6" diameter housings. Threaded, gasketed clear glass globe for durable weather-proofing and easy relamping.
1" long, 1/2" threaded nipple included for easy mounting. 75 watt max. Incandescent lamp not supplied.
Fluorescent lamp supplied.

Finish:





#### **Three Tier Flare**

10" diameter top tier. 6" diameter lower tiers. Rugged die cast aluminum housings. Threaded, gasketed clear glass globe for durable weatherproofing and easy relamping. 1" long, 1/2" threaded nipple included for easy mounting. 75 watt max.Incandescent lamp not supplied. Fluorescent lamp supplied.

Finish:





# **Catalog Numbers**

LL22VG	LL22B
LL22VG/F13	LL22B/F13

LL23VG/FS23 LL23B/FS23

Verde Green	Black	
LL23VG	LL23B	
LL23VG/F13	LL23B/F13	

LL23VG/FS23 LL23B/FS23

verde Green	Black	
LL322VG	LL322B	
LL322VG/F13	LL322B/F13	
LL322VG/FS13	LL322B/FS13	

Verde Green	Black
LL323VG	LL323B
LL323VG/F13	LL323B/F13
LL323VG/FS13	LL323B/FS13

### **Dimensions**







