



JOB	NAME

DATE:

TYPE:

DESCRIPTION

SPECIFICATIONS

Compatibility with old H100:

H101 floods and accessories replace the discontinued RAB H100 and accessories. Parts are not interchangeable. Contact factory for price and availability of the old H100 Series. **Gaskets:**

High temperature silicone rubber extends around both socket and lamp.

Housings:

Die cast aluminum with powder coat finish Lamps:

Lamps:

Medium base Par-38 lamps up to 150 watts. Halogen lamps give brighter light and choice of beam spreads

Sockets:

Porcelain with all copper current carrying components

Swivels:

Fully adjustable with sure-grip locks. 1/2" NPS threaded arm with serrated locking swivel fits all standard mounting covers. Color matched EZ Grip lock nuts.

UL Listing:

Suitable for wet locations. Suitable for mounting within 4' of the ground. Can be aimed above horizontal with accessory hood

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws

Color: White

Weight: 5.35

ORDERING INFORMATION

Total	I Lamp Lamp Starting Amps/ Operating Amp						mps	Input	LAMP	Initial	Lamp
Watts	Туре	Base	Ballast	120V	208V	240V	277V	Watts	ANSI	Lumens	Hours
300	PAR38	Medium	0	0	0	0	0	0	0	0	0

Factory Installed Options Add suffix to Catalog Number

Note: Specifications may change without notice

RAB Lighting, Inc. • 170 Ludlow Ave• Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com