



JOB	NAME:	

DATE:

TYPE:

DESCRIPTION

New! 4 Tier Dome Top offers wide light spread for wider walkways and parking lots where maximum light is required. Rugged die cast aluminum housings. Threaded, gasketed clear glass globe for durable weatherproofing and easy relamping. 1" long, 1/2" threaded nipple included for easy mounting. 75 watt max. incandescent, 13 watt fluorescent.

SPECIFICATIONS

Globes:

Threaded, gasketed globe protects against weather, garden sprinklers and insects. Clear glass GL 100 globes standard for 4 Tier. Clear glass GL60 globes standard for 3 Tire. GL100 white globes also available for attractive appearance and glare reduction.

Housing:

Die cast aluminum housing with powder coat F13: finish

Mounting Stem:

Accessory 12" mounting stem with 1/2" threads on both ends available

Socket:

Medium base porcelain with all copper electrical parts and 20" leads, including a ground lead.

UL Listina:

Suitable for wet locations. Suitable for mounting within 4 feet of the ground

Voltage:

120 volts AC

Ballast Minimum Starting Temperature: 32

Dome Top:

Wide light spread for wider walkways & parking lots where maximum light is required. Full Cutoff for narrow walkways & glare free lighting in garden areas

Compact Fluorescent 13W

Lamp:

Fluorescent lamp supplied. 13 watt quad tube. NPF 120V ballast.GX23-2 base Quad lamps, 120V

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws

Color:

Black

Weight: 6.9

ORDERING INFORMATION

Total Watts	Lamp Type	Lamp Base	Ballast	Starting 120V	g Amps/ O 208V	perating A 240V	Amps 277V	Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours	
13	Quad	GX23-2	NPF 120V	0.3				17		860	10000	

Factory Installed Options Add suffix to Catalog Number

Note: Specifications may change without notice

RAB Lighting, Inc. • 170 Ludlow Ave• Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com © 2009