



# VAN5F64MSW

JOB NAME: \_\_\_\_\_

DATE: \_\_\_\_\_

TYPE: \_\_\_\_\_

## DESCRIPTION

Sensor controlled Vandalproof fixtures. VAN 3 up to 42 watts CFL. VAN5 up to 96 watts CFL, VAN6 up to 26 watts CFL @ 120v. Sensor color matched to fixture. Sensor is not vandalproof. Lamps supplied.

## SPECIFICATIONS

### "No Hands" Auto Testing:

Auto mode starts after 4 minutes of testing. No adjustment needed.

### Built for Severe Conditions:

Double weatherproofing for long life

### LED Detection Indicator:

Glows red day and night for "on-guard" deterrence.

### Manual Override:

Double flip wall switch logic prevents activation by short power outages. Resets after 8 hours. No extra wiring needed.

### Photocontrol:

Deactivates lights during daylight. Fully adjustable for 24 hour operation or custom applications. Please specify voltage.

### Quick Test Time:

5 seconds test time for fast installation. Works day or night.

### Sensor Case Construction:

Precision molded Lexan®

### Surge Protection:

Withstands up to 3000 volts

### Time Adjustment:

5 seconds to 15 minutes CFL lamps have longer life if Time Adjustment is set to < 7 minutes.

### UL Listing:

Suitable for wet locations.

### Vandal Resistant Lens:

Hard lens resists vandalism

### Voltage:

120 volts AC 60 Hz.

### Ballast Minimum Starting Temperature:

0

### Min Start Temp:

0°

### Patents:

Pat. D547,484

### Color:

White

### Weight:

10.5

## ORDERING INFORMATION

Compact Fluorescent Lamp supplied with fixture	Total Watts	Lamp Type	Lamp Base	Ballast	Starting Amps/ Operating Amps				Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
					120V	208V	240V	277V				
	64	2-32W Triple	GX24q-3	Electronic QT	0.57			0.25	36		4800	12000

**Factory Installed Options**  
Add suffix to Catalog Number

Note: Specifications may change without notice

**RAB Lighting, Inc.** • 170 Ludlow Ave • Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com  
© 2009