

OB NAME: _	
DATE:	
TYPE:	

DESCRIPTION

Medium size ceiling mount fixture: 35, 50 and 70 watt HPS, 50 and 70 watt Metal Halide. Housing is die cast aluminum with clear vandalproof polycarbonate refractor. Quartz Restrike models available. Lamps supplied.

SPECIFICATIONS

Conduit Entry:

1/2"

HID Quartz restrike:

Add suffix "/QR" to Van3 (50w restrike) or Van5 (100w restrike) for HOT restrike. Provides immediate illumination in case of momentary power failure

Housings:

Die cast aluminum with powder coat bronze or white finish

Reflectors / Backplate:

Heavy gauge cold rolled steel with high reflectance baked white enamel

Refractor

Injection molded polycarbonate, designed for maximum structural strength

Sockets:

Medium base 4kv Pulse Rated Glazed porcelain

Screws:

Tamperproof center pin Torx-head and slotted Phillips head stainless steel screws provided. Be sure to order your Torx screwdriver (Catalog # VANDRIVER)

UL Listing:

Suitable for wet locations. Fixtures can be wired with 90° C supply wiring if supply wires are routed 3" away from ballast.

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

Quartz Restrike:

50W Quartz lamp provides immediate illumination in case of momentary power


CONSP:

White

Weight:


7.98

DIMENSIONS



PHOTOMETRIC

70w HPS @ 8' Mounting Height



Mounting Height Multiplier		Watts	Multiplier HPS MH CFL		
8'	1.0	26			.3
9'	.8	32			.4
10'	.7	42			.5
12'	.4	35	.4		
14'	.3	50	.6	.5	
		70	1.0	.9	

ORDERING INFORMATION

High Pressure Sodium Total Lamp Lamp Starting Amps/ Operating Amps Input LAMP Initial Lamp 120V 208V 240V Lamp supplied with fixture Watts Type **Ballast** Hours 50 ED17 Medium R-NPF 120V 1.8/1.2 62 S68 4000 24000

 Factory Installed Options
 Swivel Photocontrol (/PCS)
 Mini Motion Sensor (/MS)

 Add suffix to Catalog Number
 Quartz Restrike (HPS & MH only) (/QR)
 Button Photocontrol (/PC)

Note: Specifications may change without notice