



LED RECESSED ADJUSTABLE

3-1/4" SQUARE LENSED ANGLE CUT



IC Rated, 700 LUMEN

IC43LSQ-431SQ, IC943LSQ-431SQ

PRODUCT DESCRIPTION

Recessed adjustable 13W LED luminaire with 3-1/4" square lensed angle cut reflector produces up to 650 fixture lumens and approximates the performance of a 50W MR16 lamp. Fixture has 50° visual cutoff and features precision geared hot-aiming. Sealed Air-Loc® housing ensures maximum energy savings and controls plenum sound transmission. Low profile IC rated housing for use in insulated or non-insulated areas.

PRODUCT SPECIFICATIONS

LED Light Engine Consistent fixture to fixture color consistency within 3-step MacAdam ellipse • 2700K, 3000K, 3500K, or 4000K color temperatures are available with 85 CRI typical standard • 3000K also available with 93 CRI typical and R9 >80.

Modular Optics Available with 12° Spot, 24° Narrow Flood, or 35° Flood field interchangeable optics • 50° distribution is available when AF3-50DEG accessory lens is used with 12° Spot optic • Patent pending auto-adjusting optic holder maximizes luminaire efficiency by maintaining optimal LED optic position • Accommodates up to three (3) additional beam control lenses and/or filters.

Adjustability Acu-Aim™ precision geared hot-aiming achieves 370° rotation, 45° tilt • Optimized center beam optics translates light engine forward as it is aimed off nadir, ensuring maximum light and low brightness • Black aiming mechanism preserves dark aperture.

Reflector Die cast, angle-cut, parabolic reflector maintains low glare, tight corners, and 50° cut-off • Available in haze, black haze, wheat haze, or white finishes.

Trims Style Self Flanged and Flush Mount trims utilize precision wound double torsion springs for tight, secure fit to ceiling
 • Flange is same finish as reflector unless optional painted white flange is specified • For flush mount installations in drywall ceilings use the FMSQ4 flush mount adapter • For flush mount installations in wood, stone, or tile ceilings the FMSQ4-SC*** must be used (specify ceiling thickness and adapter finish).

LED Driver Choice of four drivers to accommodate voltages from 120-277 volts AC • Dedicated 120V (-I) driver is dimmable with most incandescent, magnetic low voltage, and electronic low voltage dimmers • Universal Voltage (-U) driver is dimmable with most 0-10V protocol dimmers • Lutron Hi-Lume® A Series 3-wire (-L) driver is dimmable with 3-wire fluorescent controls and compatible with EcoSystem® • Lutron Hi-Lume® A Series 2-wire (-D) driver is dimmable with 2-wire forward phase dimmers containing a neutral wire • For a list of compatible dimmers, refer to [ACLXLED-DIM](#)
 • Power Factor > 0.9 • Field replaceable from below or above ceiling.

Life Rated for 50,000 hrs at 70% lumen maintenance.

Warranty 5 years from date of purchase on LED components
 • Standard Juno Lighting Group product guarantee terms and conditions apply.

Codes/Labels UL and cUL listed for through branch wiring, wet locations • Meets energy code Air Leakage requirements per ASTM E283 • Union made.

Mounting IC43LSQ features Patented (US Patent 8,038,113) Pro-VI™ Bar Hanger System with locking set screws, permitting quick placement of housing within 24" O.C. joists or suspended ceilings • Robust bar eliminates flexing regardless of fixture position • Integral T-bar notch with locking tabs secures housing to suspended ceiling grid • Captive bugle-headed ring shank nail for quick one-step installation • Bar Hanger foot aligns to bottom of construction joist and breaks away for use in suspended ceilings.

IC943LSQ is equipped with vertically adjustable mounting brackets that accept 1/2" conduit, "C" channels (HB-26 or HB-50), linear flat bars (LB-27) or 26" telescoping Real Nail bar hangers (HB-1).

Junction Box Rated for 4 No. 12 AWG 90° C through branch circuit conductors and includes (6) 1/2", (1) 3/4", and (4) Non-metallic sheathed cable knock-outs • Push-in electrical connectors for field connections.

Housing/Mounting Frame Black steel plaster frame and housing painted for visually dark interior • V-Notch in plaster frame and Patented (US Patent 8,277,090) Tru-Line™ Platform featuring +/- 1/2" translation and +/- 45° aperture rotation aids fixture alignment during installation.

Ceiling Thickness 1/2" - 7/8" ceiling standard • For thicker ceilings, order CTA4SQ-125 (7/8"-1 1/4"), CTA4SQ-163 (1 1/4"-1 5/8") or CTA4SQ-200 (1 5/8" - 2") • CTA4SQ not required for wood, stone, or tile flush mount applications.

REV-11/14

Project: _____

Fixture Type: _____


Location: _____

Contact/Phone: _____



IC43LSQ



IC943LSQ



DIMENSIONS



4 1/8" CEILING CUTOUT
 (REFER TO INSTRUCTION SHEET FOR
 FLUSH MOUNT CEILING CUTOUT)

	A
Self Flanged	4 1/2"
Flush Mount	3 5/8"

ELECTRICAL DATA

Driver Option	Dedicated 120V (-I)	Universal Voltage (-U)		Lutron 3-wire (-L)	Lutron 2-wire (-D)
Voltage	120	120	277	120 277	120
Input Power	12.8	13.7	14.1	12.6 13.6	13.5
Input Current	0.10	0.11	0.05	0.10 0.05	0.11
Frequency	50/60Hz	50/60Hz		50/60Hz	50/60Hz
Power Factor	0.99	0.99	0.90	0.99 0.94	0.98



LED RECESSED ADJUSTABLE

3-1/4" SQUARE LENSED ANGLE CUT

IC Rated, 700 LUMEN



IC43LSQ-431SQ, IC943LSQ-431SQ

Ordering Information Housing, trim and accessories each ordered separately

Example: **IC43LSQ-835-F-1**

Housings	CRI/Color Temperature	Beam Optics	Drivers	Options
IC43LSQ	827 2700K, 85CRI	S 12° Spot	I 120V, Forward & Reverse Phase Dimming	CP Chicago Plenum
IC943LSQ	830 3000K, 85CRI	N 24° Narrow Flood		
	835 3500K, 85CRI	F 35° Flood	U 120-277V, 0-10V Dimming	
	840 4000K, 85CRI		L 120-277V, Lutron Hi-Lume 3-wire Dimming, Ecosystem Compatible	
	930 3000K, 93CRI		D 120V, Lutron Hi-Lume 2-wire Dimming	

Example: **431SQW-SF**

Trim/Description		
		
Self Flanged ¹	Flush Mount ²	Description
431SQBHZ-SF	431SQBHZ-FM	Black Haze Reflector
431SQHZ-SF	431SQHZ-FM	Haze Reflector
431SQW-SF	431SQW-FM	White Reflector
431SQWHZ-SF	431SQWHZ-FM	Wheat Haze Reflector

¹For self flanged reflector with optional white painted flange, replace "-SF" suffix with "-SFWH".

²Flush Mount trims must be used with Flush Mount Adapter, ordered separately.

Product specifications subject to change without notice.

Flush Mount Adapters

Cat. #	Description
FMASQ4	Drywall Ceiling Adapter
FMASQ4-SC100-WH	Wood, Stone, Tile, 1/2"-1" Thick Ceiling, Adapter, White
FMASQ4-SC100-BL	Wood, Stone, Tile, 1/2"-1" Thick Ceiling, Adapter, Black
FMASQ4-SC138-WH	Wood, Stone, Tile, 1"-1 3/8" Thick Ceiling, Adapter, White
FMASQ4-SC138-BL	Wood, Stone, Tile, 1"-1 3/8" Thick Ceiling, Adapter, Black
FMASQ4-SC175-WH	Wood, Stone, Tile, 1 3/8"-1 3/4" Thick Ceiling, Adapter, White
FMASQ4-SC175-BL	Wood, Stone, Tile, 1 3/8"-1 3/4" Thick Ceiling, Adapter, Black

Optical Accessories

Cat. #	Description	Cat. #	Description
TIR-1-SP	12° Spot Optic	T7403	Med. Green Dichroic Lens
TIR-1-NFL	24° Narrow Flood Optic	T7404	Med. Blue Dichroic Lens
TIR-1-FL	35° Flood Optic	T7405	Yellow Dichroic Lens
AF3-50DEG	50° Optic Film (Use with 12° Optic)	T7406	Magenta Dichroic Lens
T741	Med. Pink Color Filter	T7411	Blue Green Dichroic Lens
T742	Warm Red Color Filter	T7416	Daylight Blue Correction Lens
T743	Daylight Blue Color Filter	T7420	Diffuse Spread Lens
T744	Med. Blue Color Filter	T7422	UV Filter Lens
T745	Med. Amber Color Filter	T7477	Prismatic Lens
T746	Med. Green Color Filter	T7478	Linear Spread Lens
T7401	Red Dichroic Lens	T7459BL	Hexcell Louver

Misc. Accessories

Cat. #	Description
CTA45Q-125	1 1/4" Thick Ceiling Adapter
CTA45Q-163	1 5/8" Thick Ceiling Adapter
CTA45Q-200	2" Thick Ceiling Adapter
HB-1	(2) Real Nail 3 Bar Hangers
HB-26	(2) 26" C-Channel Bar Hangers
HB-50	(2) 50" C-Channel Bar Hangers
LB-27	(2) 27" Linear Bar Hangers
EMI-20	20W Emergency Lighting Inverter

To order, specify catalog number.



LED RECESSED ADJUSTABLE

3-1/4" SQUARE LENSED ANGLE CUT

IC Rated, 700 LUMEN

IC43LSQ-431SQ, IC943LSQ-431SQ


PHOTOMETRIC REPORT

Test Report: PT05122501
 Catalog No: IC43LSQ-830-S-1
 (Aim at 30°)
 with 431SQHZ-SF trim

Watts: 12.8
 Lumens: 667
 Luminaire LPW: 52.1

Candlepower Distribution

Degrees	Vertical	Candela
0°	28	
5°	41	
10°	87	
15°	278	
20°	1506	
25°	4939	
30°	8016	
35°	6822	
40°	2985	
45°	728	
50°	136	
55°	28	
60°	4	
65°	0	
70°	0	
75°	0	
80°	0	
85°	0	
90°	0	




PHOTOMETRIC REPORT

Test Report: PT05122502
 Catalog No: IC43LSQ-830-N-1
 (Aim at 30°)
 with 431SQHZ-SF trim

Watts: 12.9
 Lumens: 663
 Luminaire LPW: 51.4

Candlepower Distribution

Degrees	Vertical	Candela
0°	66	
5°	118	
10°	324	
15°	1142	
20°	2228	
25°	2879	
30°	3166	
35°	3059	
40°	2461	
45°	1326	
50°	284	
55°	27	
60°	7	
65°	0	
70°	0	
75°	0	
80°	0	
85°	0	
90°	0	




PHOTOMETRIC REPORT

Test Report: PT05122505
 Catalog No: TC43LSQ-830-F-1
 (Aim at 30°)
 with 431SQHZ-SF trim

Watts: 12.8
 Lumens: 663
 Luminaire LPW: 51.0




Candlepower Distribution

Degrees	Vertical	Candela
0°	341	
5°	628	
10°	867	
15°	1074	
20°	1244	
25°	1353	
30°	1390	
35°	1357	
40°	1238	
45°	983	
50°	530	
55°	279	
60°	40	
65°	0	
70°	0	
75°	0	
80°	0	
85°	0	
90°	0	



CBPC • Centerbeam candlepower
FC • Footcandles at beam center (aim point)

In vertical aiming applications, aim point (X) is determined by dividing distance from the wall (D) by the tangent of the desired aim angle (A) (0.5774 for 30°, 1.0 for 45°).



LED	Beam Type	Beam Spread°	Rated Life	CBCP	0°			30°			30°			40°		
					MH	FC	L W	FC	L W	D	FC	X	L W	FC	X	L W
3000K, 85 CRI SP	NFL	12°	50,000	9586	6	266	1.3 1.3	173	1.7 1.5	3	133	5.2 2.6 1.3	283	3.6 1.6 1.0		
					8	150	1.7 1.7	97	2.3 1.9	4	75	6.9 3.5 1.7	159	4.8 2.1 1.3		
					10	96	2.1 2.1	62	2.8 2.4	5	48	8.7 4.3 2.1	102	6.0 2.6 1.6		
					12	67	2.5 2.5	43	3.4 2.9	6	33	10.4 5.2 2.5	71	7.2 3.1 2.0		
	NFL	24°	50,000	4338	4	271	1.7 1.7	176	2.3 2.0	2	136	3.5 3.9 1.7	288	2.4 2.2 1.3		
					6	121	2.6 2.6	78	3.5 2.9	3	60	5.2 5.9 2.6	128	3.6 3.3 2.0		
					8	68	3.4 3.4	44	4.6 3.9	4	34	6.9 7.9 3.4	72	4.8 4.4 2.6		
					10	43	4.3 4.3	28	5.8 4.9	5	22	8.7 9.8 4.3	46	6.0 5.5 3.3		
	FL	35°	50,000	1678	4	105	2.5 2.5	68	3.5 2.9	2	52	3.5 7.2 2.5	111	2.4 3.6 2.0		
					6	47	3.8 3.8	30	5.2 4.4	3	23	5.2 10.8 3.8	50	3.6 5.3 2.9		
					8	26	5.0 5.0	17	7.0 5.8	4	13	6.9 14.4 5.0	28	4.8 7.1 3.9		
					10	17	6.3 6.3	11	8.7 7.3	5	8	8.7 18.0 5.0	18	6.0 8.9 4.9		
					12	12	7.6 7.6	8	10.4 8.7	6	6	10.4 21.6 7.6	12	7.2 10.7 5.9		

Multipliers: 827 - 0.92
 930 - 0.92
 835 - 1.01
 840 - 1.02

