



UNDERWATER LIGHTS SL-33-SERIES

SPECIFICATIONS

- CONSTRUCTION:** Solid cast brass body and cap
- AIMING BRACKET (SL-33-AB, SL-33-AB-AC only):** Solid cast brass with black knobs
- LENS:** High impact clear tempered flat glass
- LAMP:** 20 watt MR16 flood (BAB) with front glass (50 watt max.)
- SOCKET:** GU5.3 high-temperature ceramic bi-pin with 250°C lead wire
- LAMP LIFE:** 5000 hours average rating; also available 10,000 hour MR16, add **-10K** to catalog no.
- WIRING:** 15 feet of 18/2 SJT-WA cord, side mount wiring on -SM designated models
- CORD CONNECTOR:** Brass nickel-plated liquid-tight straight bushing from base of fixture
- MOUNTING:** Flush to bottom surface with aiming bracket (-AB). Wall mount with stainless steel screws 3.5" (not supplied)
- STANDARD FINISH:** Unfinished brass, available with Black Acid Treatment. Add **-BAT** to catalog number



SL-33-BAT

SL-33-SM-AC




SL-33-AB




SL-33-AB-AC

ORDERING INFORMATION

CATALOG NO.	DESCRIPTION
SL-33	Brass Underwater light
SL-33-AC	Brass Underwater light with angle collar
SL-33-AB	Brass Underwater light, adjustable aiming bracket and black thumbscrews
SL-33-AB-AC	Brass Underwater light with angle collar and adjustable aiming bracket
SL-33-SM	Brass Underwater light with side mount cord
SL-33-SM-AC	Brass Underwater light with side mount cord and angle collar



LIGHT DISTRIBUTIONS AND PHOTOMETRICS



FL-13-BAB-FG
FOR SL-33 SERIES

ACCESSORIES



- FA-11-SL-33-BLUE** Blue Tempered Glass Lens
- FA-11-SL-33-GREEN** Green Tempered Glass Lens
- FA-11-SL-33-RED** Red Tempered Glass Lens
- FA-11-SL-33-AMBER** Amber Tempered Glass Lens
- FA-11-SL-33-WL** White Flashed Opal Tempered Glass Lens
- FA-137** For additional cord length, add length in feet to catalog number (50' maxi.)
- FA-154** Brass Adjustable Aiming Bracket
- FA-155-CST** Cast Brass Angle Collar (-AC)

12v. fixtures: 25 foot 16/2 fixture lead wire available; add **-25F** to catalog number. For use with Focus CPC or hub supplied by others.

FSA-00

Powder Coat Finishes	Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Terra Cotta
Ordering Code	-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-TRC

JOB INFORMATION

Type: _____ Date: _____

Job Name: _____

Cat. No.: _____

Lamp(s): _____

Specifier: _____

Contractor: _____

Notes: _____

FOCUS INDUSTRIES INC.
25301 COMMERCENTRE DRIVE
LAKE FOREST, CA 92630

www.focusindustries.com
sales@focusindustries.com
(949) 830-1350 • FAX (949) 830-3390



FOCUS™
INDUSTRIES

INSTALLATION INSTRUCTIONS (12v) FOR SL-33 UNDERWATER LIGHT FIXTURES

Inspected by

Without Aiming Bracket

- 1) Install fixture into pond/fountain using rocks to keep fixture in place.
- 2) Route wire out of water and connect to 12v power supply per local code. Check for proper operation.

With Aiming Bracket (-AB)

- 1) Install fixture into pond/fountain, adjust aiming bracket to desired angle. Note: (3) holes in Aiming bracket can be used to attach/screw to surface.
- 2) Route wire out of water and connect to 12v power supply per local code. Check for proper operation.

LAMP INSTALLATION/REPLACEMENT

CAUTION: Do not exceed maximum wattage marked on fixture label.

- 1) Turn off power to fixture.
- 2) Remove fixture from water.
- 3) Remove 4 screws on top cap. Remove cap. Replace lamp with same type/wattage. Check and clean both gasket and glass lens. Reinstall lamp gasket and glass lens. Tighten 4 screws in small even increments to ensure even seal.
- 4) Reinstall in water.

For Questions Call 1-888-882-1350

