

## DESCRIPTION

The Lumark LVL20UG vaportight area light provides an indoor / outdoor solution in applications where lighting fixture protection is required. The fixture provides equivalent light output up to 100-watt incandescent and 23-watt CFL fixtures with high-quality and long lasting illumination. The fixture is vaportight to protect against dust and moisture. Ideal for garages, storage, and industrial areas.

<b>Catalog #</b>		<b>Type</b>
<b>Project</b>		
<b>Comments</b>		<b>Date</b>
<b>Prepared by</b>		

## SPECIFICATION FEATURES

### Construction

- Durable die-cast aluminum housing and cage provides protection against vandalism
- Vaportight IP65 rating protects against dust and moisture
- Versatile mounting options - wall, ceiling and post
- Frosted glass lens
- (5) 1/2" NPT conduit openings

### Electrical

- Frosted glass lens
- Maintenance-free LEDs with L70 50,000 hours of life
- Universal 120-277V power supply
- Fixture operating temperature range from -20°C to 40°C
- cULus listed for wet locations

### Optics

- 3500K color temperature
- Fixture produces up to 1450 Lumens

### Warranty

- Five-year warranty




## LVL20UG VAPORTIGHT LED

Solid State LED


AREA LUMINAIRE

## DIMENSIONS

### Top View




### Side View




## MOUNTING OPTIONS


### Wall Mount



### Post Mount



### Ceiling Mount



## POWER LUMENS

<b>Delivered Lumens</b>	1,450
<b>CCT (Kelvin)</b>	3,500
<b>CRI (Color Rendering Index)</b>	80
<b>Power Consumption (W)</b>	17.7

## ORDERING INFORMATION

Model	Description
LVL20UG	Die-cast Aluminum Vaportight LED