HL3 3" Square Trim Series

Recessed 3-inch aperture LED downlight / directional with field interchangeable optics provide various distribution patterns. Ideal for accent, task and general area lighting. Housing is airtight, suitable for 2x6 residential or shallow plenum commercial constructions and can be used in direct contact with insulation. Trims are available in a range of finishes and can be installed rimless with an optional rimless adapter. Use where high efficiency, excellent light control and low aperture brightness are required.

Catalog #	Туре
Project	
Comments	Date
Prepared by	

DIRECTIONAL OPEN




TLS3R Square Reflector, Open, Self Flanged






ORDERING INFORMATION

Trim	Shielding	Finish	Flange
TLS3R = 3.25" aperture square reflector, open, self-flanged	[blank] = open	Anodized Finishes H = semi-specular clear reflector and flange HWF = semi-specular clear reflector and matte white flange	[blank] = full overlap self-flanged
		Electroplated Finishes BN = brushed nickel reflector and flange ORB = oil rubbed bronze reflector and flange	
		Painted Finishes MW = matte white reflector and flange MB = matte black reflector and flange	









TLS3RMWRL Square Reflector, Open, Rimless





Trim	Shielding	Finish	Flange
TLS3R = 3.25" aperture square reflector, open, rimless	[blank] = open	Painted Finishes MW = matte white reflector and flange	RL = rimless, must be used with rimless adapter ordered separately





DIRECTIONAL OPEN



TLS3BBWF TLS3WBWF


Square Baffle, Open, Self Flanged






ORDERING INFORMATION

Trim	Shielding	Finish	Flange
TLS3R = 3.25" aperture square baffle, open, self-flanged	[blank] = open	Painted Finishes BBMF = matte black baffle, matte white flange WBWF = matte white baffle, matte white flange	[blank] = full overlap self-flanged








TLS3PINSquare Pinhole w/Oculus,
Open, Self Flanged






ORDERING INFORMATION

Trim	Shielding	Finish	Flange
TLS3PIN = 2.00" aperture square pinhole w/ oculus, open, self- flanged	[blank] = open	Electroplated Finishes BNBB = brushed nickel flange, black oculus ORBBB = oil rubbed bronze flange, black oculus Painted Finishes MWWB = matte white flange, white oculus MWBB = matte white flange, black oculus MBBB = matte black flange, black oculus	[blank] = full overlap self-flanged









TLS3PINMWWBRL Square Pinhole w/Oculus, Open, Rimless





Trim	Shielding	Finish	Flange
TLS3PIN = 2.00" aperture square pinhole w/ oculus, open, rimless	[blank] = open	Painted Finishes MWWB = matte white flange, white oculus	RL = rimless, must be used with rimless adapter ordered separately







DIRECTIONAL LENS




TLS3R2GConical Reflector,
Diffuse Lens, Self Flanged






ORDERING INFORMATION

Trim	Shielding	Finish	Flange
TLS3R = 3.25" aperture square reflector, lens, self-flanged	2G = micro- prismatic lens	Anodized Finishes H = semi-specular clear reflector and flange HWF = semi-specular clear reflector and matte white flange Electroplated Finishes BN = brushed nickel reflector and flange ORB = oil rubbed bronze reflector and flange	[blank] = full overlap self-flanged
		Painted Finishes MW = matte white reflector and flange MB = matte black reflector and flange	








TLS3R2GMWRL Square Reflector, Diffuse Lens, Rimless






ORDERING INFORMATION

Trim	Shielding	Finish	Flange
TLS3R = 3.25" aperture conical reflector, open, rimless	2G = micro- prismatic lens	Painted Finishes MW = matte white reflector and flange	RL = rimless, must be used with rimless adapter ordered separately









TLS3PR2GMWSquare Polymer Reflector,
Diffuse Lens, Self Flanged





Trim	Shielding	Finish	Flange
TLS3R = 3.25" aperture square polymer reflector, lens, self- flanged	2G = micro- prismatic lens	Painted Finishes MW = matte white reflector and flange	[blank] = full overlap self-flanged







DIRECTIONAL LENS



TLS3R2GBBWF TLS3R2GWBWF


Square Baffle, Diffuse Lens, Self Flanged







ORDERING INFORMATION

Trim	Shielding	Finish	Flange
TLS3R = 3.25" aperture square baffle, lens, self-flanged	2G = micro- prismatic lens	Painted Finishes BBMF = matte black baffle, matte white flange WBWF = matte white baffle, matte white flange	[blank] = full overlap self-flanged








TLS3PIN2GSquare Pinhole w/Oculus,
Diffuse Lens, Self Flanged






ORDERING INFORMATION

Trim	Shielding	Finish	Flange
TLS3PIN = 2.00" aperture square pinhole w/ oculus, open, self- flanged	2G = micro- prismatic lens	Electroplated Finishes BNBB = brushed nickel flange, black oculus ORBBB = oil rubbed bronze flange, black oculus Painted Finishes MWWB = matte white flange, white oculus MWBB = matte white flange, black oculus MBBB = matte black flange, black oculus	[blank] = full overlap self-flanged









TLS3PIN2G*RL Square Pinhole w/Oculus, Diffuse Lens, Rimless





Trim	Shielding	Finish	Flange
TLS3PIN = 2.00" aperture square pinhole w/ oculus, open, rimless	2G = micro- prismatic lens	Painted Finishes MWWB = matte white flange, white oculus	RL = rimless, must be used with rimless adapter ordered separately







LENS WALL WASH





TLS3LWW6G Square Angle Cut Lens Wall Wash, Self Flanged



ORDERING INFORMATION

Trim	Shielding	Finish	Flange
TLS3LWW = 3.25" aperture square lens wall wash, self-flanged	6G = linear spread lens	Anodized Finishes H = semi-specular clear reflector and flange HWF = semi-specular clear reflector and matte white flange Painted Finishes MW = matte white reflector and flange	[blank] = full overlap self-flanged







TLS3LWW6GMWRL Square Angle Cut Lens Wall Wash, Rimless



Trim	Shielding	Finish	Flange
TLS3LWW = 3.25" aperture square lens wall wash, rimless	6G = linear spread lens	Painted Finishes MW = matte white reflector and flange	RL = rimless, must be used with rimless adapter ordered separately

