

The H1499T is a small aperture low voltage housing for providing accent and task lighting. The H1499T is designed for use in non-insulated ceiling or for insulated ceilings but insulation MUST be kept 3" from all sides of the housing.

Housing

Formed of 20 gauge CRS with white powder coat finish.

Plaster Frame

Galvanized steel construction. The housing can be removed from plaster frame to provide access to the junction box. Plaster frame features include:

- Regressed locking screw for securing hanger bars from below the ceiling
- Six cutouts for easily crimping hanger bars in position
- Halo name embossed on plaster frame.

Junction Box

- Listed for through branch circuit wiring
- Positioned to accommodate straight conduit runs
- 1/2" trade size conduit

knockouts with true pry-out slots positioned to accommodate straight conduit runs.

- Three Slide-N-Side[™] wire traps allow non-metallic sheathed cable to be installed without tools and without removing knockouts.
- Allows wiring connections to be made outside the junction box
- Insert the cable directly into the trap after connections are made.
- Accommodates the following standard non-metallic sheathed cable types:

(US) #14/2, #14/3, #12/2, #12/3 (Canada) #14/2, #14/3, #12/2

GOT NAIL!™ Pass-N-Thru™ Bar Hangers

- Pre-installed nail easily installs in regular lumber, engineered lumber and laminated beams.
- Score lines allow "tooless" shortening for 12" joists.
- Bar hangers can be repositioned 90° on plaster frame

Bar Hanger Features include:

 Safety and guidance system prevents snagging, ensures smooth straight nail penetration and allows bar hangers to be easily removed if necessary.

- Automatic levelling flange aligns the housing and lets you hold the housing in place with one hand while driving nails
- Housing can be positioned at any point within 24" joist span
- Bar hangers do not need to be removed from frame for shortening
- Integral T-bar clips snaps onto Tbars - no additional clips required

Transformer

120V Integral magnetic transformer steps line voltage down to lamp operating voltage. For lamps up to 50W.

Thermal Protector

Self resetting thermal protector deactivates fixture if overheating occurs due to improper lamping or misapplied insulation.

Labels

- UL/cUL Listed for Damp Location
- UL/cUL listed for Feed Through
- IP Rated (Improper Lamp)



H1499T

4" Aperture Shallow Ceiling 12V Low Voltage, MR16

RECESSED DOWNLIGHTING

- Thermally Protected Non-IC Shallow Ceiling Low Voltage Housing
- Integral magnetic Transformer
- Insulation must be kept 3" away from all sides of housing
- For use with 12V MR16 halogen lamps

HALO®

H1499IC

H1499T

H1499RT


H1499T75

1421

Reflector Trim

- Die cast trim ring with reflector cone
- Provides General Illumination
- · Lamps:

H1499T H1499RT H1499IC	50W 12V MR16
H1499T75	75W 12V MR16







1421RGWhite Trim, Residential Gold Reflector

1421CGWhite Trim, Champagne Gold Reflector

White Trim, Clear Specular Reflector



1421SL Silver Trim, Clear Specular Reflector



1421MBWhite Trim, Black Specular Reflector



1421H White Trim, Haze Reflector



1421BZTuscan Bronze, Tuscan
Bronze Reflector



1421ACAntique Copper Trim, Antique Copper Reflector




1421SN Satin Nickel Trim, Satin Nickel Reflector

1493

Coilex® Baffle

- Die cast trim ring
- Coilex® Baffle
- For general lighting
- Lamps:

H1499T H1499RT H1499IC	50W 12V MR16
H1499T75	75W 12V MR16





1493PBPolished Brass Trim with Black Baffle



1493W White with White Baffle



1493P White with Black Baffle



1493SNSatin Nickel Trim with Black Baffle



1493BCBlack Chrome Trim with Black Baffle



1493SL Silver Trim with Black Baffle



1493TBZ
Tuscan Bronze Trim with Black
Raffle



1493ACAntique Copper Trim with Black Baffle

H1499T

H1499RT


H1499T75

1453

Metal Baffle

- Die cast trim ring with matching finish metal baffle
- For general lighting
- · Lamps:

H1499T	50W 12V MR16
H1499RT	0011 121 111110
H1499IC	
H1499T75	75W 12V MR16





1453TBZ Tuscan Bronze trim with Tuscan Bronze Baffle



1453AC Antique Copper Trim with Antique Copper Baffle




1453SN Satin Nickel Trim with Satin Nickel Baffle

1419

1-7/8" Pinhole Baffle

- Die cast trim ring with metal baffle
- · For concentrated accent lighting
- · Lamps:

H1499T H1499RT H1499IC	50W 12V MR16
H1499T75	75W 12V MR16





1419SL Silver with Black Baffle

1419W White with White Baffle

1419P White Trim with Black Baffle



1419TBZ Tuscan Bronze with Black Baffle



1419AC Antique Copper with Black Baffle



1419SN Satin Nickel with Black Baffle

1420

Adjustable Slot Aperture - 35° Tilt

- Die cast trim ring with slot aperture
- For directional accent lighting
- 35° tilt, 360° rotation
- · Lamps:

H1499T H1499RT H1499IC	50W 12V MR16
H1499T75	75W 12V MR16











1420TBZ Tuscan Bronze Trim



1420AC Antique Copper Trim

HALO®

H1499IC

H1499T

H1499RT

H1499T75

1495

Adjustable Gimbal - 30° Tilt

Features:

- Die cast trim ring and gimbal
- For directional accent lighting
- 30° Tilt, 360° rotation
- · Lamps:

H1499T H1499RT H1499IC	50W 12V MR16
H1499T75	75W 12V MR16







1495SN Satin Nickel Trim with Satin Nickel Gimbal



1495SL Silver Trim with Silver Gimbal



1495 White Trim with White Gimbal



1495TBZ Tuscan Bronze Trim with Tuscan Bronze Gimbal



1495AC Antique Copper Trim with Antique Copper Gimbal

1496 Retractable Elbow - 60° Tilt

Features:

- Die cast trim ring with matching finish retractable elbow
- · For directional accent lighting
- 60° tilt, 360° rotation
- Lamps:

H1499T H1499RT H1499IC	50W 12V MR16
H1499T75	75W 12V MR16

Aperture: 1-3/4" [44mm] OD: 5-1/16" [129mm]





Satin Nickel Trim with Satin Nickel Elbow



Silver Trim with Silver Elbow



White Trim with White Elbow



Tuscan Bronze Trim with Tuscan Bronze Elbow




Antique Copper Trim with Antique Copper Elbow

1497

Adjustable Mirror Trim - 90° Tilt

- Die cast trim ring with 90° adjustable scoop
- For directional accent lighting ideal for wall wash applications
- 90° tilt, 360° rotation
- · Lamps:

Lampo.	
H1499T H1499RT H1499IC	50W 12V MR16
H1499T75	75W 12V MR16





H1499IC

H1499T

H1499RT

H1499T75

1498

Adjustable Eyeball with Baffle - 30° Tilt

- · Die cast trim ring with matching finish eyeball
- · For directional accent lighting
- · 30° tilt, 360° rotation
- · Lamps:

H1499T H1499RT H1499IC	50W 12V MR16
H1499T75	75W 12V MR16









1498PB

Brass Eyeball, Black Baffle



Polished Brass Trim with Polished Silver Trim with Silver Eyeball, Black Baffle



White Trim with White Eyeball,

Black Baffle



Satin Nickel Trim with Satin Nickel Eyeball, Black Baffle



Black Chrome Trim with Black Chrome Eyeball, Black Baffle



White Trim and eyeball with White Baffle



Tuscan Bronze Trim with Tuscan Bronze Eyeball, Black Baffle



1498AC Antique Copper Trim, Antique Copper Eyeball, Black Baffle


1945

Metropolitan Ice Lite

- Frosted glass trim in clear or blue
- For general illumination
- · Lamps:

H1499T	
H1499RT	
H1499IC	

50W 12V MR16



1945BLUE Frosted Blue Glass




1945 Clear Frosted Glass

1946 Metropolitan Deco

- · Polished metallic accents with Translucent Rings
- For general illumination
- · Lamps:

H1499T	
H1499RT	50W 1
H1499ICT	

2V MR16



1946BC Black Chrome Accent with Translucent Rings




1946PB Polished Brass Accent with translucent Rings

1951

Adjustable Lensed Shower Light - 54 15° Tilt

- · Wet location listed for use in showers
- · Non conductive, corrosion free polymer trim
- · Clear specular splay reflector
- 15° tilt, 360° rotation
- · Lamps:







1951SNS Satin Nickel Trim, Clear Specular Splay Reflector



1951SLS Silver Trim, Clear Specular Splay Reflector



1951PS White Trim, Clear Specular Splay Reflector



1951TBZS Tuscan Bronze Trim, Clear Specular Splay Reflector

1951ACS Antique Copper Trim, Clear Specular Splay Reflector