

## E26 5" Trim Series


### DESCRIPTION

Perftex™ baffle trim with self-flange in the 5" trim family for use in recessed downlighting. Compatible for use in Halo and other housings.

Catalog #		Type
Project		
Comments		Date
Prepared by		

### SPECIFICATION FEATURES

- Perforated pattern baffle contoured for BR30 and PAR30L lamps
- Coil spring retention
- Self-flanged trim ring sized to hide gaps caused by construction tolerances.



### Dimensions:

A: 5-1/2" [141mm]

H: 2-1/8" [55mm]

OD: 6-5/8" [168mm]

Housings	Max Lamp Compatibility
H5ICAT H5RICAT	50W PAR30S, 60W PAR30L, 50W BR30
E5ICAT E5RICAT	
H25ICAT	5110WB: 39W PAR30S, 60W PAR30L, 50W BR30 5110BB, 5110BKBB: 39W PAR30S, 60W PAR30L, 40W BR30
H5T H5RT	75W PAR30L, 65W BR30
E5TAT E5RTAT	


Compatible with Halogen, Incandescent, LED\* or CFL\* lamps.



**5110WB**  
White Perftex™ Baffle,  
White Trim



**5110BB**  
Black Perftex™ Baffle,  
White Trim



**5110BKBB**  
Black Perftex™ Baffle,  
Black Trim

**5110**

5-Inch Perftex™ Baffle,  
Self-flange

### ORDERING INFORMATION

SAMPLE NUMBER: 5110WB

Trim	Finish
5110= 5" Perftex™ Baffle, Self-flange	WB=Matte White baffle, Matte White trim BB=Black baffle, White trim BKBB=Black baffle, Black trim

### HALO HOUSING COMPATIBILITY

Trim #	Style	H5ICAT	H5RICAT	E5ICAT	E5RICAT	H25ICAT	H5ICATNB	E5ICATNB	H25ICATNB
5110	Baffle	•	•	•	•	•	—	—	—
		H5T	H5RT	E5TAT	E5RTAT	H5TNB	E5TATNB		
		•	•	•	•	—	—		

For use in other's housings, refer to U.L. Classification list at [www.eaton.com/lighting/legal](http://www.eaton.com/lighting/legal).

\*UL1993 listed LED & CFL equivalent lamps permitted. Consult lamp manufacturer for conditions of use. Eaton does not warranty the lamp.



Select trims are classified for use in others housings.  
See [www.eaton.com/lighting/legal](http://www.eaton.com/lighting/legal).