DESCRIPTION

Universal Lampholders accept a wide range of lamps and accessories. For use with Halo and Lazer-by-Halo track systems.

Catalog #	Туре
Project	
Comments	Date
Prepared by	

SPECIFICATION FEATURES

Electrical Quick Lock Adapter

Polycarbonate casing. Attaches electrically and mechanically anywhere along the track. Visual polarity line assures proper grounding. Two position conductor allows use in single circuit and either circuit of two circuit track.

L700 6' [152mm] 2-5/8" [67mm]

Max. Extension: 10-5/8" [270mm] (less lamp)


L1700




Stem allows lampholder to rotate 332° and adjust vertically from 0° to 180° for L700 and L1700, and 0° to 90° for L702 and L703.

Accessories

L280 Light Shield clips onto lamp and can be used with L700, L703 and L1700. Allows use of L200 color filters or 272 and L275 louvers.



6" [152mm] (less lamp)



UL listed and CSA certified for use

with Halo and Lazer-by-Halo track



HALO®



L702








L1700


LINE VOLTAGE **UNIVERSAL** LAMPHOLDERS

Power-Trac®




Note: Specifications and Dimensions subject to change without notice.





Max. Extension: 7-1/4" [184mm] (less lamp)



Lampholder	Lamps
L700	30-300W R40 150-250 PAR28
L702	30-300W R40 75W PAR16 50W PAR20 75W PAR30 Long Neck 150W PAR38
L703	30-300W R40 75W PAR30 150/250W PAR38
L1700	50W PAR20 75W PAR30

ORDERING INFORMATION SAMPLE NUMBER: L700P

Finish L700=L700 Universal Lampholder MB=Black L702=L702 Universal Lampholder P=White L703=L703 Universal Lampholder L1700=L1700 Universal Lampholder

Accessories (Order Separately)	Finish
L280=PAR38 Light Shield, allows use of L200 color filters or 272 and 275 louvers	MB=Black P=White

Listings

and track systems.

Max. Extension: 5-1/2" [140mm] (less lamp)

L280 Light Shield

Visit our web site at www.cooperlighting.com Customer First Center 1121 Highway 74 South Peachtree City, GA 30269 770.486.4800 FAX 770 486.4801 Cooper Lighting 5925 McLaughlin Rd. Mississauga, Ontario, Canada L5R 1B8 905.507.4000 FAX 905.568.7049