


WALL OR CEILING MOUNT EUROLUXE® SERIES	Cat.#		 HUBBELL Outdoor Lighting
	Job	Type	
			Approvals

Intended Use

- Several colors and accessories, including guards and shields, are available for both interior and exterior applications, such as entry, perimeter, walls, stairwells, corridors, etc.

Construction

- Borosilicate glass lens sealed to housing by silicone gasket and stainless steel philips head screws; Ribbed lens uniformly spreads light for a symmetrical, soft distribution
- Die cast aluminum housing and face trims
- Two point lag or hickey mount to recessed junction box
- Dark bronze, Black and White finishes are offered

Electrical

- Available in 50w HPS, 28w fluorescent and 100w max. incandescent, 120V only
- BRLU LED has 6 LED in 15w, 120-277V, 830 lumens, 5000K, 700mA
- Lamp included on 50w HPS, 28w fluorescent and 15w LED


Listings

- Listed to UL1598 for use in wet locations



BR BO				
	A	C	A	C
				B
	A	B	C	
BRI ROUND	5 1/2"	9 1/2"	10 1/8"	
	150 mm	241 mm	257 mm	
BOI OVAL	5 1/2"	6 2/8"	11 1/4"	
	150 mm	162 mm	286 mm	

ORDERING INFORMATION ORDERING EXAMPLE: BOI-01



Catalog Number	Shape	Finish	Wattage	Weight	
				lbs.	kg
LED ¹					
BRLU-01	Round	Bronze	15 max.	6.0	2.7
BRLU-04	Round	White	15 max.	6.0	2.7
INCANDESCENT ²					
BRI-01	Round	Bronze	100 max.	4.0	1.8
BRI-02	Round	Black	100 max.	4.0	1.8
BRI-04	Round	White	100 max.	4.0	1.8
BO1-01	Oval	Bronze	100 max.	3.5	1.6
BO1-02	Oval	Black	100 max.	3.5	1.6
BO1-04	Oval	White	100 max.	3.5	1.6
HIGH PRESSURE SODIUM (lamp included) ²					
BRS-01	Round	Bronze	50	7.5	3.4
BRS-02	Round	Black	50	7.5	3.4
BRS-04	Round	White	50	7.5	3.4
BOS-01	Oval	Bronze	50	7.0	3.2
BOS-02	Oval	Black	50	7.0	3.2
BOS-04	Oval	White	50	7.0	3.2
FLUORESCENT (lamp included) ^{1,3}					
BRF-01	Round	Bronze	28	6.0	2.7
BRF-02	Round	Black	28	6.0	2.7
BRF-04	Round	White	28	6.0	2.7
BOF-01	Oval	Bronze	28	5.5	2.5
BOF-02	Oval	Black	28	5.5	2.5
BOF-04	Oval	White	28	5.5	2.5

¹ Fluorescent CSA certified for outdoor applications only, not available in 277V

² Pulse-rated medium base socket

³ Two-pin fluorescent socket - PLC 28, 2700K, -20°F starting

⁴ LED units feature 5 year limited warranty

ACCESSORIES

(order as separate part #)

Catalog Number	Description
BO-GX¹	Cast aluminum guard for oval fixture
BR-GX¹	Cast aluminum guard for round fixture
BO-SX¹	Cast aluminum shield for oval fixture
BR-SX¹	Cast aluminum shield for round fixture

¹ Finish must be specified, substitute **X** for: **1**-bronze, **2**-black, **4**-white



PHOTOMETRIC REPORTS

Catalog Number	Report #
BRI-0X	HP05330.IES
BRI-0X/BR-SX	HP05331.IES
BRI-XX	ITL60433.IES
BRLU-0X	BRLU01.IES