



# DIMMER COMPATIBILITY

Project: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Location: \_\_\_\_\_

Contact/Phone: \_\_\_\_\_

UNIVERSAL VOLTAGE		UNIVERSAL VOLTAGE	
Universal Voltage (120-277V) Housings (-U) 0-10V Dimming Control • Dimming range of 100% down to 10% or lower with a minimum load of one fixture. <sup>1</sup> Additional Lutron products required for switching functionality when using Lutron 0-10V dimmers (such as PP-120H or PP-277H)		Universal (120-277V) Fixtures with Lutron® Hi-Lume® A Series Driver (-L) 3-Wire Dimming and EcoSystem® Compatible • For a list of compatible dimmers, please reference Lutron's Report Card for EcoSystem and 3-Wire Control dimming systems located at - <a href="http://www.lutron.com/TechnicalDocumentLibrary/EcoSystem_3-wire_report_card.pdf">http://www.lutron.com/TechnicalDocumentLibrary/EcoSystem_3-wire_report_card.pdf</a> Consult technical services for additional information regarding other dimmer model qualification.	
Juno Qualified Dimmers			
Fixture Series	Lutron® Model Numbers:	Leviton® Model Numbers:	Whole House Integrated Control Systems:
900 & 1400 LUMEN LED DOWNLIGHT TC 5" and 6" Generation 4 Series	Nova® NFTV Series <sup>1</sup> Nova T*® NTFTV Series <sup>1</sup> Diva® DDTV Series <sup>1</sup> Grafik Eye QS GRX-TVI	ILLUMATECH™ IP710-DLX Series	Schneider Electric C-Bus SLCLE5504TAMP* Lutron® Homeworks® GRX-TVM2  Note: C-Bus is 25 fixtures per channel.
900 & 1400 LUMEN LED DOWNLIGHT TC 5" and 6" Generation 3 Series	Nova® NFTV Series <sup>1</sup> Nova T*® NTFTV Series <sup>1</sup> Diva® DDTV Series <sup>1</sup> Grafik Eye QS GRX-TVI	ILLUMATECH™ IP710-DLX Series	Schneider Electric C-Bus SLCLE5504TAMP* Lutron® Homeworks® GRX-TVM2  Note: C-Bus is 25 fixtures per channel.

\* Juno recommended dimmers

Consult technical services for additional information regarding other dimmer model qualification.

