

4" VERTICAL COMPACT FLUORESCENT REMODEL HOUSING

26W COMPACT FLUORESCENT LAMP

PL426RE

PRODUCT DESCRIPTION

Contact/Phone:

PL Remodel Housing for applications where back side of ceiling is not accessible • Installs through an opening in the ceiling from below • Secured in place by factory installed remodel springs plus additional field-installed lock-down mounting clip • Designed for use in non-insulated areas • If installed where insulation is present, the insulation must be pulled back 3" from all sides of the PL housing.

PRODUCT SPECIFICATIONS

Lamp One 26W Triple Tube (4-pin) CFL lamp (CFTR26W/GX24q).

Socket Fixed mounted socket attaches to top of housing.

Ballast 120V thru 277V HPF Rapid Start Electronic with end-of-life lamp protection • UL listed/CSA certified.

Trims Trim selection shown on reverse.

Labels UL listed for damp locations • Union made • UL and C-UL Listed • Trims 11, 12, 4101 and 4102 are wet location approved for covered ceiling applications.

Testing All reports are based on published industry procedures; field performance may differ from laboratory performance.

Product specifications subject to change without notice.

INSTALLATION


Junction Box Pre-wired junction box • Junction box provided with removable access plate, (5) ½" knockouts, (4) Non-metallic sheathed cable connectors and ground wire • Knockouts equipped with pryout slots.


Housing Aluminum housing • Remodel springs accommodate up to 11/4" ceiling thickness.

PRODUCT CODES

Catalog Number	Input Voltage	Lamp Rating (max.)	Ballast	
PL426RE	120-277V	26W Triple Tube (4-pin) CFL	HPF	

DIMENSIONS





4 3/8" CEILING CUTOUT



4" VERTICAL **COMPACT FLUORESCENT REMODEL HOUSING**

26W COMPACT FLUORESCENT LAMP

PL426RE

TRIMS/LAMPS

	Cat. No.	Description	Max. Lamp Rating
	11-WH ◆	Drop Opal	26W Triple Tube (4-pin) CFL lamp
	13-WH	2" Pinhole with Integral Shield	26W Triple Tube (4-pin) CFL lamp
	14B-WH 14B-SC 14B-ABZ 14B-BL 14W-WH	Black Baffle Black Baffle Black Baffle Black Baffle White Baffle	26W Triple Tube (4-pin) CFL lamp
	17CLI-WH 17G-WH 17B-WH 17PT-SC 17W-WH 17HZ-WH 17WHZ-WH 17WHZ-ABZ	Cone - Clear Low Iridescent Alzak® Cone - Gold Alzak® Cone - Black Alzak® Cone - Pewter Alzak® Cone - Closs White Cone - Haze Cone - Wheat Haze Cone - Wheat Haze	26W Triple Tube (4-pin) CFL lamp
Optimized for CFL	170CLI-WH 170HZ-WH 170WHZ-WH	Cone - Clear Low Iridescent Alzak® Cone - Haze Cone - Wheat Haze	26W Triple Tube (4-pin) CFL lamp
Optimized for CFL	140B-WH 140W-WH	Black Baffle White Baffle	26W Triple Tube (4-pin) CFL lamp
	12W-WH ♦ 12W-SC ♦ 12W-ABZ ♦	Shower Trim, frosted perimter lens Shower Trim, frosted perimter lens Shower Trim, frosted perimter lens	26W Triple Tube (4-pin) CFL lamp

Cat. No.	Description	Max. Lamp Rating
4101-WH ♦ 4101-SC ♦ 4101-ABZ ♦	Beveled Dome Shower Beveled Dome Shower Beveled Dome Shower	26W Triple Tube (4-pin) CFL lamp
4102-WH ◆ 4102-SC ◆ 4102-ABZ ◆	Beveled Shower Beveled Shower Beveled Shower	26W Triple Tube (4-pin) CFL lamp
4103FROST-WH 4103FROST-SC	Beveled Cylinder Beveled Cylinder	26W Triple Tube (4-pin) CFL lamp
4104HZ-SC 4104WHZ-ABZ	Beveled Cone Beveled Cone	26W Triple Tube (4-pin) CFL lamp
4150MESH-SC	Cylinder	26W Triple Tube (4-pin) CFL lamp

Trim Size: 5" O.D.

Trim Finish: ABZ - Classic Aged Bronze, BL -Black, SC - Satin Chrome, WH - White. Alzak is a registered trademark of Alcoa Corp.

Note: In Canada when insulation is present, Type IC fixtures must be used.

◆ UL Listed for use in wet location.