TC20S

5" UNIVERSAL

INCANDESCENT LAMPS

TC HOUSING

juno

Project:

Fixture Type:

Location:

Contact/Phone:

PRODUCT DESCRIPTION

TC Housing design for use in non-insulated areas \bullet If installed where insulation is present, the insulation must be pulled back 3" from all sides of the TC housing.

PRODUCT SPECIFICATIONS

Lamp Lamp ratings based on trim selected-see reverse.

Socket Medium base porcelain with nickel-plated copper screw shell • Drop socket with spring to accommodate certain trim installation.

Trims Trim selection shown on reverse.

Labels U.L. listed for through-branch wiring, damp locations and IP • Product thermally protected against improper use of lamps or insulation • Union made • UL Listed/CSA certified • Trims 210N, 211 and 212N are wet location approved for covered ceiling applications • Trims 215 and 216 are wet location approved for covered ceiling applications, when used with outdoor rated lamps.

Testing All reports are based on published industry procedures; field performance may differ from laboratory performance.

Product specifications subject to change without notice.

INSTALLATION

Real Nail Bar Hangers Telescoping Real Nail system permits quick placement of housing anywhere within 24" O.C. joists, or suspended ceilings • Bars scored in two locations for fast clean breaking allowing housing installation in tight applications

• Edge-mounted for extra strength and captive to mounting frame


 Features Real Nail captive nail system for quick one-step installation
 May be installed either perpendicular or parallel to junction box
 Quick-Loc slot (location identified on the mounting frame) and oversized locking set screw lock fixture in position.

Junction Box Pre-wired junction box provided with (5) ½" and (1) ¾" knockouts, (4) Non-metallic sheathed cable connectors and ground wire, U.L. listed/CSA certified for through-branch wiring, maximum 8 No. 12 AWG 90° C branch circuit conductors (4 in, 4 out) • Junction box provided with removable access plates • Knockouts equipped with pryout slots.

Mounting Frame 22-gauge die-formed galvanized steel mounting frame • Rough-in section (junction box, mounting frame, housing and bar hangers) fully assembled for ease of installation
Sight lines embossed on mounting frame to allow for easy viewing when aligning fixtures.

Housing .032" aluminum housing • Housing is vertically adjustable to accommodate up to a 1" ceiling thickness.

DIMENSIONS



5 5/8" CEILING CUTOUT

ACCESSORIES

Catalog No.	Description		
G2405	T-Bar Clips (Set of 4)		

To order, specify catalog number.



PRODUCT CODES

Catalog Number	Input Voltage	Lamp Rating (max.)
TC205	120V	A19/BR30/PAR20/PAR30/PAR30L/R20 (See reverse for max. trim rating)

TC20S

5" UNIVERSAL TC HOUSING INCANDESCENT LAMPS

TRIMS/LAMPS

1 1	(IMS/LA				
		Cat. No.	Description	Max. Lamp Ratir	ng
\langle	\bigcirc	201 N-WH	Open Frame	65W BR30	
** 🏈		203B-WH 203W-WH	Deep Black Baffle Deep White Baffle	75W PAR30, 65W BR30	
** 🤇		205B-WH 205W-WH 205B-SC 205B-ABZ	BR30/PAR30 Black Baffle BR30/PAR30 White Baffle BR30/PAR30 Black Baffle BR30/PAR30 Black Baffle	75W PAR30, 65W BR30	
** ((204C-WH 204G-WH 204B-WH 204PT-SC 204HZ-WH 204W-WH 204W-WH 204WHZ-WH	BR30/PAR30 Cone - Clear Alzak® BR30/PAR30 Cone - Gold Alzak® BR30/PAR30 Cone - Black Alzak® BR30/PAR30 Cone - Pewter Alzak® BR30/PAR30 Cone - White Gloss BR30/PAR30 Cone - Wheat Haze BR30/PAR30 Cone - Wheat Haze	75W PAR3OL, 75W PAR3O, 65W BR3O	
** ((206C-WH 206G-WH 206B-WH 206PT-SC 206HZ-WH 206WHZ-WH 206WHZ-ABZ	Deep Cone - Clear Alzak® Deep Cone - Gold Alzak® Deep Cone - Black Alzak® Deep Cone - Pewter Alzak® Deep Cone - Haze Deep Cone - Wheat Haze Deep Cone - Wheat Haze	75W PAR30, 65W BR30	
** 🤇		207C-WH 207G-WH 207B-WH 207W-WH 207HZ-WH 207HZ-WH	Cone - Clear Alzak® Cone - Gold Alzak® Cone - Black Alzak® Cone - Gloss White Cone - Haze Cone - Wheat Haze	50W PAR20/R20	
		215B-WH ♦♦ 215W-WH ♦♦	BR30/PAR30 Black Baffle BR30/PAR30 White Baffle	75W PAR30L, 75W PAR30 w/Socket Extender, 60W A 19, 85W BR30	
		216C-WH ♦♦ 216G-WH ♦♦ 216W-WH ♦♦ 216HZ-WH ♦♦ 216WHZ-WH ♦♦	Cone - Clear Alzak® Cone - Gold Alzak® Cone - Gloss White Cone - Haze Cone - Wheat Haze	75W PAR30L, 75W PAR30 w/Socket Extender, 85W BR30, 60W A19 (Clear, Gold, Haze and Wheat Haze Cones), 40W A19 (White Cone)	
<	\bigcirc	208NB-WH 208NW-WH	Eyeball with Black Baffle Eyeball with White Baffle	50W PAR20/R20	
	\bigcirc	529-WH 529-SC 529-ABZ	PAR30 Eyeball PAR30 Eyeball PAR30 Eyeball	75W PAR30	
\langle	O	209N-WH	Gimbal Ring with Flat Trim	75W PAR30	
		688B-WH 688W-WH	Gimbal Ring with Black Baffle Gimbal Ring with White Baffle	75W PAR30	
(689C-WH 689G-WH 689HZ-WH 689WHZ-WH 689WHZ-ABZ	Gimbal Ring in Clear Cone Gimbal Ring in Gold Cone Gimbal Ring in Haze Cone Gimbal Ring in Wheat Haze Cone Gimbal Ring in Wheat Haze Cone	75W PAR30	
		210N-WH ♦ 210N-SC ♦ 210N-ABZ ♦	Lensed Shower/Closet Light Lensed Shower/Closet Light Lensed Shower/Closet Light	40W A 19	Trim Size: 6¼" O.D. (except Cat No. 529 - 6½" O.D.) Trim Finish: ABZ - Classic Aged Bronze, BL - Black, GP - Graphite, PW - Plastic White (Polycarbonate material shower trim), SC - Satin Chrome, SL - Silver, WH - White. Alzak is a registered trademark of Alcoa Corp.
Ć	\bigcirc	211-PW ♦	Shower Trim	40W A 19	Alzak is a registerea trademark of Alcoa Corp. Note: In Canada when insulation is present, Type IC fixtures must be used.
\langle		212N-WH ♦ 212N-SC ♦ 212N-ABZ ♦	Shower Trim Shower Trim Shower Trim	75W PAR30, 60W A15	 ◆ UL Listed for use in wet location. ◆ UL Listed for use in wet location with outdoor rated lamp. ** NOTE: TR5 Trim Ring compatible with 203, 204, 205, 206, 207 trims.



1300 S. Wolf Road • Des Plaines, IL 60018 • Phone (847) 827-9880 • Fax (847) 827-2925
 JUNO LIGHTING GROUP
 220 Chrysler Drive • Brampton, Ontario • Canada L6S 6B6 • Phone (905) 792-7335 • Fax (905) 792-0064

 by Schneider Electric
 Visit us at www.junolightinggroup.com
 Printed in U.S.A. ©2012 Juno Light
 Printed in U.S.A. ©2012 Juno Lighting, LLC.