



Description

Non-IC rated vertical CFL remodel housing for remodel applications where back side of ceiling is not accessible • Designed to be installed in non-insulated areas, or where insulation is spaced at least 3" from housing

Listings

UL Listed, C-UL/CSA certified for through-branch wiring, damp and wet locations • Wet location listed when used with a 239, 240, 241, 243, 271, 2330, 6101 and 9900 trim


Features


- 6" Remodel housing
- 120V through 277V HPF rapid start electronic ballast with end-of-life lamp protection
- Ballast mounted on J-box cover
- Removable or fixed mounted socket accommodates a variety of trim installations
- Remodel clips accommodate up to a 2" ceiling
- Fully assembled white painted steel housing
- Pre-wired junction box with (5) 1/2" knockouts with pryout slots, (4) non-metallic sheathed cable connectors, and ground wire
- UL Listed, C-UL/CSA certified for through-branch wiring, maximum (4) #12 AWG conductors (2 in,
- Shadow-free, knife-edge trim design blends smoothly into the ceiling and allows architectural continuity with Aculux® trims
- One 13W quad or triple tube (4-pin) CFL lamp. See trim selection on pages 85-86

Ordering Information

Catalog Number: PL613RE

Dimensions





6 3/4" Ceiling Cutout





Trims for ICPL618E - PL613RE

Lensed (cont)



Drop Opal with Reflector

Catalog # 271-PW

Catalog #

DescriptionPlastic White

Max. Lamp Rating

ICPL/PL618: 18W ICPL/PL613: 13W





Wall Wash



261W-WH 261B-WH

Description

White Baffle, White Trim Black Baffle, White Trim Max. Lamp Rating

ICPL/PL618: 18W ICPL/PL613: 13W



Scoop

Note: Specify General Electric or Osram Sylvania lamps only.

Decorative



Decorative Swirled Etched Opal Glass

Catalog # De 243-WH Op

DescriptionOpal Glass

Max. Lamp Rating

ICPL/PL618: 18W ICPL/PL613: 13W







Beveled Frame, Frosted Dome Lens

Catalog # Description 6101-ABZ Classic Aged

Classic Aged Bronze Satin Chrome Trim White Trim

Max. Lamp Rating

ICPL/PL618: 18W ICPL/PL613: 13W







Baffle, Regressed Frosted Dome Lens

Description

White Baffle, White Trim Black Baffle, White Trim

Max. Lamp Rating

ICPL/PL618: 18W ICPL/PL613: 13W







Fluted Drop Opal

Catalog # 9900-WH

6101-SC

6101-WH

Catalog #

2330W-WH

2330B-WH

DescriptionWhite Trim

Note: Specify General Electric or Osram Sylvania lamps only. Compatible with TR6, 6" trim ring

Max. Lamp Rating

ICPL/PL618: 18W ICPL/PL613: 13W





