



Description

Non-IC rated housing • Designed to be installed in non-insulated areas, or where insulation is spaced at least 3" from housing

Listings

UL Listed, C-UL/CSA certified for through-branch wiring, damp and wet locations • Wet location listed with the 20, 21, 22, 239, 240, 241, 242, 243, and 9900 trims • The listing also includes the 28 and 29 trims, only when used with PAR30/PAR38 outdoor rated lamps • Conforms with City of Chicago IP requirements

Features

- 6" Housing
- Medium base porcelain socket with nickel-plated copper screw shell
- Drop socket with spring to accommodate certain trim installation
- Housing is vertically adjustable to accommodate up to a 2" ceiling thickness
- Housing is fully assembled for ease of installation
- Real Nail® 3 bar hangers: telescoping system with pre-installed removable nail for easy repositioning of housing in joist construction • Integral T-bar mounting feature for secure installation in suspended ceilings • Patented breakaway bars for tight joist spacing • Bar hangers may be re-positioned 90° • Curved foot facilitates alignment with joist bottom • Quick-Loc slot and oversized set screw lock fixture in position
- Pre-wired junction box with (5) 1/2" and (1) 3/4" knockouts with pryout slots, (4) non-metallic sheathed cable connectors, and ground wire
- Shadow-free, knife-edge trim design blends smoothly into the ceiling and allows architectural continuity with Aculux® trims
- UL Listed, C-UL/CSA certified for through-branch wiring, maximum (8) #12 AWG minimum 90° C branch circuit conductors (4 in, 4 out)
- Thermally protected against improper use of lamps or insulation
- Lamp wattage ratings and apertures based on trim selection on pages 90-95

Ordering Information

Catalog Number: **TC2**

Catalog Number: **TC2S** - TC2 with smaller footprint bar hanger (Real Nail® 2)

Catalog Number: **TC2W** - TC2 with push-in electrical connectors for fast, secure installation

Dimensions

