

new



### Description

ICPL Energy Star, Air-Loc® sealed double-wall construction housing for use in 7/12 to 12/12 pitch slopes (30° to 45°) • Can be completely covered with insulation • Fully sealed Air-Loc housing stops infiltration and exfiltration of air, reducing heating and cooling costs • Juno's patented Slope Ceiling Down-Lites direct light straight down, providing proper lighting from a sloped surface

### Listings

Energy Star qualified • UL Listed for contact with insulation, through-branch wiring, and damp locations • Meets Washington State Air Tight Requirements, IECC • Complies with FCC Part 18 consumer use limits • Complies with California's Title 24 energy code

### Features

- 6" super slope housing
- 120V HPF rapid start electronic FCC Class B ballast with end of life lamp protection
- One 26W, 32W, or 42W triple tube (4-pin) CFL lamp
- Energy Star, Air-Loc® CFL double wall housing does not require separate gasket
- Oblique angle housing design holds trims flush with the ceiling
- Socket mounts to an adjustable plate to accommodate various pitch ceilings
- Supplied with threaded barrel CFL socket
- Inner housing is vertically adjustable to accommodate up to a 1" ceiling thickness
- Real Nail® 3 bar hangers: telescoping, patent-pending system permits quick placement of housing anywhere within 24" OC joists or suspended ceiling
  - Integral T-bar mounting feature and clip secures housing in suspended ceiling grid
  - Patented break-away bars for tight joist spacing
  - Bar hanger foot contoured to align to bottom of construction joist
  - Quick-Loc slot and oversized locking set screw lock fixture in position
- Pre-wired junction box with (6) 1/2" and (1) 3/4" knockouts, (4) non-metallic sheathed cable connectors, and ground wire
- Shadow-free, knife-edge trim design blends smoothly into the ceiling allows architectural continuity with Aculux® trims
- Angle-cut baffles ensure grooves remain parallel to the floor to provide proper optics
- UL listed for through-branch wiring, maximum (8) #12 AWG 90° C branch circuit conductors (4 in, 4 out)
- 2 year warranty
- Lamp wattage ratings and apertures based on trim selection on page 112

### Ordering Information

Catalog Number: **ICPL928-42**

Catalog Number: **ICPL928-42-DB120** - ICPL928-42 with 120V HPF dimmable ballast – T24 compliant, Energy Star® qualified

### Dimensions

