

JUNO

6" SUPER SLOPE CEILING LED - 900 LUMENS IC NEW CONSTRUCTION HOUSING

Project: _____

Fixture Type: _____

Location: _____

Contact/Phone: _____

SUPER SLOPE:
7/12 to 12/12 PITCH (30° to 45°)

IC928LED9G3 LENSED TRIMS

PRODUCT DESCRIPTION

Dedicated LED, Air-Loc® sealed slope ceiling new construction housing with integral light engine • IC rated construction housing can be completely covered with insulation • Fully sealed housing stops infiltration and exfiltration of air, reducing heating and air cooling costs without the use of additional gaskets • LED housing is designed to provide 50,000 hours of life and is compatible with standard Juno trims • 5 year limited warranty on LED components.

ENVIRONMENTALLY FRIENDLY, ENERGY EFFICIENT

- No harmful ultraviolet or infrared wavelengths
- No lead or mercury
- Comparable light output to 26W compact fluorescent while consuming less than 16W*



PRODUCT SPECIFICATIONS

LED Light Engine Extruded heat sink and cast aluminum slider plate integrated directly with housing provides superior thermal management to ensure the long life of the LED • Replaceable light engine mounts directly to slider plate and incorporates the latest generation, high lumen output LED array • LEDs are binned to standards that exceed ENERGY STAR® requirements yielding superior fixture to fixture color uniformity • 2700K, 3000K, 3500K, or 4100K color temperatures available • 80 minimum CRI typical.

Optical System Computer-optimized internal reflector with specular finish coupled with a high transmission diffusing lens conceals the LEDs and produces uniform aperture luminance • Adjustable slider plate to position LEDs/reflector perpendicular to floor • Plate includes 1/4" adjustment indicators for consistent alignment.

Aesthetic Trim Selections Compatible with a selection of existing Juno trims • Trims are wet location approved for covered ceiling applications.

LED Driver Choice of dedicated 120 volt driver or universal voltage driver that accommodates input voltages from 120-277 volts AC at 50-60Hz • Power factor > 0.9 at 120V input • 120 volt only driver dimmable with the use of most incandescent, magnetic low voltage and electronic low voltage wall box dimmers • Universal voltage driver is dimmable with the use of most 0-10V wall dimmers • For a list of compatible dimmers, see **JUNOLEDG3-DIM** • Mounted inside housing on a removable J-box cover for ease of maintenance.

Life Rated for 50,000 hours at 70% lumen maintenance.

Labels UL listed for U.S. and Canada through-branch wiring, wet locations (covered ceilings) • Union made • UL and cUL listed.

Testing All reports are based on published industry procedures; field performance may differ from laboratory performance.


Product specifications subject to change without notice.

HOUSING FEATURES

Housing Designed for use in IC (insulated ceiling) or non-IC construction • .032" aluminum housing sealed for Air-Loc compliance • Access door for junction box accessibility • Insert skirt is vertically adjustable to accommodate up to a 1" ceiling thickness.

Junction Box Pre-wired junction box provided with (5) 1/2" and (1) 3/4" knockouts, (4) non-metallic sheathed cable connectors and ground wire, UL and cUL listed for through-branch wiring, maximum 8 No. 12 AWG 90° C branch circuit conductors (4 in, 4 out) • Junction box provided with removable access plates • Knockouts equipped with pryout slots • Push-in electrical connectors supplied as standard for fast, secure installation.

DIMENSIONS



Mounting Frame 22-gauge die-formed galvanized steel mounting frame • Rough-in section (junction box, mounting frame, housing and bar hangers) fully assembled for ease of installation.

Real Nail® 3 Bar Hangers Telescoping Real Nail® 3 system permits quick placement of housing anywhere within 24" O.C. joists or suspended ceilings • Includes removable nail for repositioning of fixture in wood joist construction • Integral T-bar mounting feature for suspended ceilings • Design covered under patents US5,505,419 and D552,969.

ELECTRICAL DATA DEDICATED 120 VOLT ONLY DRIVER OPTION

	120V
Input Power	15.4W (+/-5%)
Input Current - Max	0.15A
Frequency	50/60Hz
EMI/RFI	FCC Title 47 CFR, Part 15, Class B (residential)
Minimum starting temp	-20°C

ELECTRICAL DATA UNIVERSAL VOLTAGE

	120V	277V
Input Power	16.5W (+/-5%)	16.9W (+/-5%)
Input Current - Max	0.155A	0.072A
Frequency	50/60Hz	50/60Hz
EMI/RFI	FCC Title 47 CFR, Part 15, Class A (commercial)	FCC Title 47 CFR, Part 15, Class A (commercial)
Minimum starting temp	-40°C	-40°C

*Nominal input wattage @ 120 volt operation with dedicated 120 volt driver under stable operating conditions.

6" SUPER SLOPE CEILING LED - 900 LUMENS IC NEW CONSTRUCTION HOUSING

SUPER SLOPE: 7/12 to 12/12 PITCH (30° to 45°)

IC928LED9G3 LENSED TRIMS

ORDERING INFORMATION: Housing and trim each ordered separately.

Example: **IC928LED9G3-35K-1**

Housing	Color Temperature	Voltage
IC928LED9G3	27K 2700K 3K 3000K 35K 3500K 41K 4100K	1 Dedicated 120V only (forward phase and ELV dimming) U Universal Voltage 120-277V (0-10V dimming)

Example: **6033W-WH**

Trim/Description
 6033W-WH White Baffle, Regressed Frosted Dome Lens

UL Listed for use in wet location.

Trim Size: 9¹/₈" O.D.
Trim Finish: WH - White.

Note: In Canada when insulation is present, Type IC fixtures must be used.


PHOTOMETRIC REPORT

Test Report #: PT06120705R

Catalog No: IC928LED9G3-35K-1
with 6033W-WH Trim

Luminaire Spacing Criterion: 1.90

Luminaire LPW: 38



CANDLEPOWER DISTRIBUTION (Candelas)

Degrees Vertical	0°
0	249
5	305
10	351
15	393
20	421
25	432
30	424
35	399
40	356
45	305
50	248
55	191
60	144
65	106
70	74
75	49
80	30
85	14
90	0

AVERAGE INITIAL FOOTCANDLES

Multiple Units (Square Array, 60' x 60' room)

Ceiling 80% Wall 50% Floor 20%

Spacing	RCR1	RCR3	RCR5
4.0'	38	30	24
5.0'	24	19	15
6.0'	17	13	11
7.0'	14	11	9
8.0'	11	8	7
9.0'	8	6	5
10.0'	6	5	4

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixture
0-30°	191	N/A	32.8
0-40°	304	N/A	52.2
0-60°	489	N/A	84.0
0-90°	582	N/A	100.0

INITIAL FOOTCANDLES (One Unit, 15.5W, 59.5° Beam)

Distance to Footcandles Illuminated Plane (Ft.)	Beam Center	Beam Diameter
6	6.9	6.9'
8	3.9	9.1'
10	2.5	11.4'
12	1.7	13.7'
14	1.3	16.0'
16	1.0	18.3'
18	0.8	20.6'
20	0.6	22.9'

LUMINANCE (Average cd/m²)

Degrees	Average Luminance
45	28155
55	21736
65	16372
75	12358
85	10485



1300 S. Wolf Road • Des Plaines, IL 60018 • Phone (847) 827-9880 • Fax (847) 827-2925
220 Chrysler Drive • Brampton, Ontario • Canada L6S 6B6 • Phone (905) 792-7335 • Fax (905) 792-0064
Visit us at www.junolightinggroup.com

Printed in U.S.A. ©2012 Juno Lighting, LLC.