



FIRE RATED BARRIER - 1 HOUR

ACCESSORY

SP19311-FBA-1

Project: _____

Fixture Type: _____

Location: _____

Contact/Phone: _____

PRODUCT SPECIFICATIONS

For use with the following Juno Air-Loc IC housings: IC1 Series, IC1P Series, IC1LED Series, IC20 Series, IC21 Series, IC22 Series, IC23 Series, IC23-LED Series, IC25 Series, V4ICW Series, V5ICW Series, V6ICW Series, IC20LED Series, IC920LED Series, IC22LED Series, IC922LED Series, ICPL613 Series, ICPL618 Series, ICPL626 Series, ICPL632 Series, ICPL513 Series, ICPL518 Series, ICPL526 Series, IC2 Series, ICPL926 Series, IC926 Series, IC926LED Series, IC6 Series.

Consult factory for compatibility with other Juno housings.

PRODUCT FEATURES

- ETL/INTERTEK/OPL Listed for US Market: 1 hour fire rating for L500 floor-ceiling assemblies
- Flexible
- Lightweight
- Eliminates Drywall Boxes
- Use standard Juno trims with housings specified above
- Rated for use with IC housings

INSTALLATION SUITABILITY

- L500-Series floor-ceiling design with solid wood joist or open-web wood truss construction, 2" x 10" (min.), 16" (max.) centers, Min 1/2" thick gypsum board ceiling, wood flooring
- Spacing of luminaires not to exceed one per 25 square feet with minimum separation of 3 feet between luminaires

DIMENSIONS

