



# FIRE RATED BARRIER - 2 HOUR

ACCESSORY

**SP28112-FBA-1**

Project: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Location: \_\_\_\_\_

Contact/Phone: \_\_\_\_\_

## PRODUCT SPECIFICATIONS

UL/CUL Classified for use with the following Juno Air-Loc IC housings: IC21, IC23 Series, IC570, IC571, ICPL570, ICPL613 Series, ICPL618 Series, ICPL626 Series, ICPL632 Series, IC2 Series, ICPL513 Series, ICPL518 Series, ICPL526 Series, IC20 Series, V4ICLV. Consult factory for compatibility with other Juno housings.

## PRODUCT FEATURES

- UL/CUL/OPL/ETL Listed: 2 hour fire rating for L500, D500, G500, D200, G200, J200 and L200 floor-ceiling assemblies
- Flexible
- Lightweight
- Eliminates Drywall Boxes
- Use standard Juno trims with housings specified above
- Rated for use with IC housings

## INSTALLATION SUITABILITY

- L500, D500, G500, D200, G200, J200 and L200-Series floor-ceiling design with solid wood joist or open-web wood truss construction, 2" x 10" (min.), 24" (max.) centers, Min 1/2" thick gypsum board ceiling, wood flooring
- Spacing of luminaires not to exceed one per 25 square feet with minimum separation of 3 feet between luminaires

## DIMENSIONS

