G1.4.73

JUNO

Project:

Fixture Type:

Location:

Contact/Phone:

PRODUCT DESCRIPTION

IC Air-Loc® Remodel Housing for use with Juno retrofit LED trim modules • Energy efficient, sealed housing • IC Remodel Housing for remodel application where back side of ceiling is not accessible • Installs through an opening in the ceiling from below • Secured in place by factory installed remodel springs • Can be completely covered with insulation • Fully sealed housing stops exfiltration of air, reducing heating and air cooling costs without the use of additional gaskets.

PRODUCT SPECIFICATIONS

Electrical Connections Features non-screw base 120V plug-in connector • Compatible with Juno retrofit LED trim modules • Meets high efficacy requirements of California T24.

Labels U.L. listed for U.S. and Canada for through-branch wiring and damp locations.

Testing All reports are based on published industry procedures; field performance may differ from laboratory performance.

Product specifications subject to change without notice.

INSTALLATION

Junction Box Pre-wired junction box, UL listed/CSA certified for through-branch wiring maximum 4 No. 12 AWG 90° C branch circuit conductors (2 in, 2 out) • Junction box provided with removable access plate, (5) $\frac{1}{2}$ " knockouts, (4) Non-metallic sheathed cable connectors and ground wire • Knockouts equipped with pryout slots.

Housing IC housing, .032" aluminum sealed for Air-Loc Compliance • Remodel springs accommodate up to $1^{1}/8''$ ceiling thickness.




COMPATIBLE WITH 5RLD SERIES


IC20R-LEDT24



5" IC REMODEL HOUSING

DIMENSIONS





5 1/2" CEILING CUTOUT

PRODUCT CODES

Catalog Number	Input Voltage
IC20R-LEDT24	120V

COMPATIBLE LED MODULES

(To order, specify catalog number)

Catalog Number	Description
5RLD-927-6-WWH	Juno Basics LED Retrofit Trim, 600 lumen, 2700K, White Baffle
5RLD-930-6-WWH	Juno Basics LED Retrofit Trim, 600 lumen, 3000K, White Baffle

