













### Pendant Mounting Accessories (cont)

	<b>Catalog #</b> TLR92-12-WH TLR92-12-BL TLR92-12-SL  TLR92-18-WH TLR92-18-BL TLR92-18-SL  TLR92-24-WH TLR92-24-BL TLR92-24-SL  TLR92-36-WH TLR92-36-BL TLR92-36-SL  TLR92-48-WH TLR92-48-BL TLR92-48-SL	<b>Finish</b> White Black Silver  White Black Silver  White Black Silver  White Black Silver  White Black Silver	<b>Description</b> <ul style="list-style-type: none"><li>• For pendant mounting Trac 12/25 to T-Bar or rigid ceilings</li><li>• 12", 18", 24", 36" 48" stem lengths</li><li>• Use two for 2', 4', or 6' of trac or three for 8' of trac</li><li>• Provides mechanical support only</li><li>• Order TLR37 or TLR37-9-16 T-Bar Clip to mount on T-Bar ceilings</li></ul>	
	<b>Catalog #</b> T96WH T96BL T96SL	<b>Finish</b> White Black Silver	<b>Description</b> <ul style="list-style-type: none"><li>• Joins pendant stems for use in higher ceiling applications</li></ul>	
	<b>Catalog #</b> T94WH T94BL T94SL	<b>Finish</b> White Black Silver	<b>Description</b> <ul style="list-style-type: none"><li>• Permits TLR90, TLR91 and TLR92 Pendant Stems to hang straight from sloped ceilings</li><li>• Accomodations two 12 gauge solid THHN copper wires at up to a 60° angle</li><li>• 20-amp capacity (based on 12 gauge wire)</li></ul>	
	<b>Catalog #</b> TLR93WH TLR93BL TLR93SL	<b>Finish</b> White Black Silver	<b>Description</b> <ul style="list-style-type: none"><li>• Includes ceiling canopy and trac mounting hardware only - threaded rod by others</li><li>• Use two for 2', 4', or 6' of trac or three for 8' or trac</li></ul>	
	<b>Catalog #</b> TLR95-48-WH TLR95-48-BL TLR95-48-SL  TLR95-144-WH TLR95-144-BL TLR95-144-SL	<b>Finish</b> White Black Silver  White Black Silver	<b>Description</b> <ul style="list-style-type: none"><li>• 48" or 144" cable lengths</li><li>• Length is easily field adjustable</li><li>• Recommended for trac patterns only (not recommended for straight runs)</li><li>• Supports should be placed every 3' plus at feed points, bend peaks and corners</li></ul>	
	<b>Catalog #</b> TLR96-48-WH TLR96-48-BL TLR96-48-SL  TLR96-144-WH TLR96-144-BL TLR96-144-SL	<b>Finish</b> White Black Silver  White Black Silver	<b>Description</b> <ul style="list-style-type: none"><li>• 48" or 144" cable lengths</li><li>• Length is easily field adjustable</li><li>• Recommended for trac patterns only (not recommended for straight runs)</li><li>• Supports should be placed every 3' plus at feed points, bend peaks and corners</li><li>• Includes 10 gauge stranded tandem feed wire</li><li>• TLR50 End Feed Connector required (order separately, see page 850)</li></ul>	

Trac 12™



JUNO LIGHTING GROUP  
by Schneider Electric