

Type:
Job:
Fixture Catalog number:

Fixture and Finish

Fixture Options:

Ordered Separately from Fixture
See page 2

Mounting Options:

Ordered Separately from Fixture
See pages 3-4

Approvals:
Date:
Page: 1 of 4

Specifications

Lamp Housing: Die-cast brass, stainless steel fasteners and stainless steel set screw lock for aiming pivot.

Aiming: Aimable 358° vertically, horizontal aiming controlled by installation on mounting device.

Ravenna Yoke: Die-cast low copper aluminum, stainless steel fasteners and 1/2" NPSM brass nipple mount.

Lens: Tempered glass, 1/8" nominal thickness.

Gasketing: Silicone gaskets used throughout.


Transformer: 120 volt to 12 volt, 20 watt electronic stepdown transformer, enclosed and gasketed in yoke base.

Wiring: No. 18AWM rated 105°C.

Driver/Optical System: 3 LED emitters configured in a triangle array comprised together as a module. Each LED is encapsulated under a precision optical prism to produce a narrow flood pattern. The -40c driver is within the module and operates on 12V AC or DC current, 10 watt, 0.83 amp.

Finish: Natural Brass (NB) or Verde Green Patina (VG).

Certification: UL Listed to U.S. and Canadian safety standards for wet locations.




ORDERING INFORMATION

Fixture
Finish
☐ **BNL276NB**

Natural Brass

☐ **BNL276VG**

Verde Green Patina



Catalog Number: BNL276

Report Number: k103894

Voltage: 120 Watts: 10 Amps: 0.083

Lumens: 394 CBCP: 1874 Beam: 20°

CCT: 3000K Efficacy: 39.4 Lm/W

Type:

Job:

Page: 2 of 4



Fixture Options

Ordered Separately from Fixture

Lens Accessories

Cat. No. (See right)

☐ No Option

HL - Hex Cell Louver: Constructed of hex cell aluminum louvers providing 45° cutoff, mounted in a circular frame, finished in baked high-heat flat black. Can be used in combination with colored lenses. Inserts behind lens. Cannot be used in combination with **SL** spread or **PL** prismatic lenses.

Cat. No.

☐ **HL** Hex Cell Louver



PL - Prismatic Lens: Softens lamp distribution and flattens beam spread. Best with flood lamps. Inserts behind lens. Cannot be used in combination with **HL** louver.

Cat. No.

☐ **PL** Prismatic Lens



SL - Spread Lens: Creates an oval beam pattern, more narrow in one beam axis. Best with spot lamps. Inserts behind lens. Cannot be used in combination with **HL** louver.

Cat. No.

☐ **SL** Spread Lens



Type:

Job:

Page: 3 of 4



Mounting Options

Ordered Separately from Fixture

Landscape Light Post by Engineered Products Co.


Cat. No.

☐ EP17

☐ No Option

PVC fixture molded in black with 1/2" NPT mount is corrosion free and UV resistant. Replaces EMT, conduit connectors and weatherproof boxes. 100% shatter resistant against denting and cracking. Angled bottom to eliminate cable congestion.

17 1/2" post length



Brass In-grade Architectural Junction Box

Cat. No.

☐ JBR-2

☐ JBR-3

☐ JBR-21

☐ JBR-24

☐ No Option

Die-cast brass with 1/2" NPSM fixture mount and die-cast cover. Internal set screw provided for locking position. 18 cu in. internal volume.

JBR-2 (2) 1/2" NPT in bottom

JBR-3 (2) 3/4" NPT in bottom

JBR-21 (2) 1/2" NPT in sides, (2) 1/2" NPT in bottom

JBR-24 (4) 1/2" NPT in sides, (2) 1/2" NPT in bottom

All side taps provided with plugs.


25 Year Limited Warranty:

Solid brass junction boxes are warranted for 25 years, from date of sale, against manufacturing defects and failure due to corrosion.

Application Notes

- Creates a flush-mounted appearance.
- May be cast in concrete for increased stability.

CAUTION: Fixture stem and swivel must not contact soil or standing water. Provide drainage away from junction box.



Composite In-Grade Architectural Junction Box

Cat. No.

☐ JBR-4

☐ JBR-5

☐ No Option


Composite box with 1/2" NPSM fixture mount and composite cover. 19 cu in. internal volume.

JBR-4 (2) 3/4" NPT knockouts in bottom.

(4) 3/4" NPT knockouts on sides.

JBR-5 Same as above but with brass cover.

CAUTION: Fixture stem and swivel must not contact soil or standing water. Provide drainage away from J-Box.



Type:

Job:

Page: 4 of 4



Mounting Options

Ordered Separately from Fixture

Brass In-grade Staked Junction Box

Cat. No.

☐ **JBR30**


☐ **No Option**

JBR30

BRASS IN-GRADE STAKED JUNCTION BOX

Die-cast brass with 1/2" NPSM fixture mount and die-cast cover. Internal set screw provided for locking position. 18 cu in. internal volume.

(2) 1/2" NPT in bottom with (2) 19" long brass stakes



Stanchion Mount

Cat. No.

Finish

☐ **SM18/BL**

Black

☐ **SM18/DB**

Dark Bronze

☐ **SM18/GR**

Verde Green

☐ **No Option**

3" O.D. by .188" wall cast aluminum with 1/2" NPSM fixture mount and hand hole with flush cover. Internal set screw fixture lock accessible through hand hole. Internal ground lug supplied with installed lead. Super TGIC powder coat paint over clear anodizing and titanated zirconium conversion coating.

