





# Accent Light - KLV205 Installation Instructions

# INSTRUCTIONS PERTAINING TO A RISK OF FIRE OR INJURY TO PERSONS **IMPORTANT SAFETY INSTRUCTIONS!**

WARNING: To reduce the risk of FIRE, or INJURY TO PERSONS: Do not overdrive fixtures with greater than 12 volts or fixture over-heating and short lamp life will occur. Do not overload the transformer by installing (or relamping) higher wattage lamps than planned. Note: Total wattage of all lamps connected to one transformer must not exceed the capacity of that transformer. Do not install luminaire within 10 feet (3.04m) of a pool, spa, or fountain. DO NOT operate luminaire with missing or damaged lens.

SAFETY WARNING: When relamping, be sure electrical supply is OFF. Low voltage fixtures can become very HOT depending on the lamp wattage used. Glass lenses and metal areas above & around the lamp can become HOT enough to blister hands. Use discretion when touching fixture and be sure to allow fixture to cool before relamping. When relamping fixture avoid touching the lamp envelope with bare hands. If touching the lamp is necessary during installation, clean the envelope with alcohol and dry with a clean, soft cloth before turning ON. Contamination of the envelope may reduce lamp performance.

MAINTENANCE: To maintain light efficiency and prevent fixture-overheating, glass lenses and enclosure must be kept clean and free of dirt, dust, leaves, trash (combustible materials) and mineral deposits from water. Particular care should be taken not to locate fixtures where small children can reach them if higher wattage's are used.

Note: Keep the lamp free from impact while burning, as this may deform the filament and shorten the lamp life. NOT INTENDED FOR INDOOR USE. All electrical work should be done by a qualified electrician.

Unit intended for mounting with Diffuser/Glass Barrier and Lamp Holder greater than 2 in. (5.08 cm) from the ground plane.

## KEEP THIS SHEET FOR FUTURE REFERENCE.

**Tools Required:** 

- □ <sup>3</sup>/<sub>16</sub>" Allen Wrench
- ☐ 1/8" Allen Wrench
- ☐ Flat Blade Screwdriver
- ☐ Adjustable Wrench

□ Philips Screwdriver

#### Installation Instructions:





1. Remove coupling from fixture.



2. Tighten coupling onto mounting device.




**DO NOT** overload the transformer by installing (or relamping) higher wattage lamps than planned. Remember, the total wattage of all lamps connected to one trans-former must not exceed the capacity of that transformer.

3. Install fixture onto coupling. Attach fixture leads. Note: KIM KLV Mounting Options can be installed before fixture is attached.



4. To install lamp, remove four shield screws.



5. Remove shield and lens gasket assembly.



6. Install lamp of type and wattage shown on fixture label and chart on page 2.

Revision 10/14/11 EC 111014007 Status 18 Part No. 95489

# Accent Light KLV205 Installation Instructions



7. Replace lens (convex side out) fitting lens gasket assembly into the recess on fixture body. Replace light shield over lens after making sure the drain hole is down, so water will not stand on lens. Tighten opposing screws progressively and evenly.




8. Loosen set screw, adjust fixture rotation, and tighten set screw.

Additional wire and connectors may be purchased from Kim Lighting.


KLV427 #12-2 Cable KLV432 #8-2 Cable KLV410 Connector KLV411 Connector

**Note:** Low voltage cable is intended for shallow burial, maximum of 6" (152 mm).

LAMP INFORMATION		
Cat. No.	Lamp Type	Max. Watts
KLV205	MR-16 Bi-Pin	75



 To adjust angle, loosen swivel screw, do not disengage. Hold fixture at desired angle and tighten swivel screw. Fixture may be aimed up or down.



**Note:** Swivel stem must be installed with the mounting threads facing down-to-horizontal. Fixtures may not be installed with mounting threads facing upward unless shielded from rain or sprinklers.



 Connect fixture cable to main system cable with a sealed connector.

### KIM LIGHTING LIMITED WARRANTY

When installed in accordance with Kim Installation Instructions and accepted trade practices, the following shall apply:

# **General Product Limited Warranty Coverage**

All material and component parts used in the manufacture of Kim Products, are warranted to be free from defects of material and/or workmanship for a period of 1 year from date of sale, with the following exceptions:

## uxiliary Equipment

All auxiliary equipment (such as lamps, ballasts, and transformers) provided by and/or included in Kim Products shall carry the component manufacturer's warranty.

## **Copper and Bronze Landscape Components**

Copper and Bronze Landscape fixture components shall be warranted against defects of material and/or workmanship, and failure due to corrosion, for a period of 25 years from date of sale.

## **Composite In-Grade Components**

Composite In-Grade fixture components installed below grade, shall be warranted against defects of material and/or workmanship, and failure due to corrosion, for a period of 7 years from date of sale.

#### **Aluminum Landscape Components**

Aluminum Landscape fixture components not in direct contact with soil, shall be warranted against defects of material and/or workmanship for a period of 3 years from date of sale. Aluminum fixture components in direct contact with soil shall be warranted from defects of material and failure from corrosion for a period of 1 year from date of sale.

# **Limit of Liability and General Conditions**

Only products which are installed, used and maintained in accordance with applicable Kim instructions, specifications and accepted trade practices, are covered by the Kim Warranty. During the warranty period, with proof of purchase, Kim will repair or replace with the same or similar product, at Kim's option, without charge. Labor costs are the owner's responsibility and are excluded from this warranty. This warranty is void if the product is modified, tampered with, misapplied, poorly installed, improperly maintained, or subjected to abnormal conditions.

Repair or replacement as provided under this warranty is the exclusive remedy of the purchaser. This warranty is in lieu of all other warranties, expressed or implied, including any implied warranty of fitness for a particular application. Kim Lighting shall not be liable to the purchaser for indirect or consequential damages.





How may we serve you better? Please let us know.
Visit our website at: www.kimlighting.com
Your concerns are important to us.