

<b>Type:</b> <b>Job:</b> <b>Fixture Catalog number:</b>  <hr/> Fixture and Finish	<b>Fixture Options:</b> <hr/> Ordered Separately from Fixture See page 2	<b>Approvals:</b>   <b>Date:</b> <b>Page: 1 of 3</b>
	<b>Mounting Options:</b> <hr/> Ordered Separately from Fixture See page 3	

## Specifications

**Housing and Shield:** Die-cast low copper aluminum.

**Swivel:** Die-cast aluminum with locking teeth and 1/2" solid brass NPT mount. Provides horizontal rotation independent of the threaded mount. Swivel locked by 1/4-20 stainless set screw. Clear anodized prior to powder coating for added corrosion resistance.


**Lens:** Convex clear tempered glass with silicone gasket.

**Socket:** G4 to GY6.35 socket for bipin lamp.

**Wiring:** 6' No. 18-2 12 Volt cable with fork connectors.

**Finish:** Super TGIC thermoset polyester powder coat paint, 2.5 mil nominal thickness, applied over a titanated zirconium conversion coating; 2500 hour salt spray test endurance rating. Standard colors are Black (**BL**), Dark Bronze (**DB**), and Verde Green (**GR**).

**Certification:** UL Listed to U.S. and Canadian safety standards for wet locations.



## ORDERING INFORMATION

Fixture*	Finish
<input type="checkbox"/> KLV205BL	Black
<input type="checkbox"/> KLV205DB	Dark Bronze
<input type="checkbox"/> KLV205GR	Verde Green

### Wattage / Lamp

**20W - 75W**  
 MR16 Bipin  
 Halogen

\*Remote transformer required.



KIM LIGHTING RESERVES THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE.

Type:

Job:

Page: 2 of 3



## Fixture Options

Ordered Separately from Fixture


### Internal Louver

Cat. No.

**L12**

**No Option**

Clips onto rim of MR16 lamp and provides additional brightness control.



Type:

Job:

Page: 3 of 3



## Mounting Options

Ordered Separately from Fixture

<p><b>Landscape Light Post by Engineered Products Co.</b></p> <p>Cat. No.  <input type="checkbox"/> EP17  <input type="checkbox"/> No Option</p>	<p>PVC fixture molded in black with 1/2" NPT mount is corrosion free and UV resistant. Replaces EMT, conduit connectors and weatherproof boxes. 100% shatter resistant against denting and cracking. Angled bottom to eliminate cable congestion.</p> <p>17 1/2" post length</p>	
<p><b>Low Voltage Spear Mount</b></p> <p>Cat. No.      Finish  <input type="checkbox"/> KLV400BL    Black  <input type="checkbox"/> KLV400DB    Dark Bronze  <input type="checkbox"/> KLV400GR    Verde Green  <input type="checkbox"/> No Option</p>	<p>Die-cast low copper aluminum with 1/2" NPSM fixture mount. Stainless steel set screw locks fixture into mount. Cable slot allows easy fixture mounting before or after installation in ground. Super TGIC powder coat paint over clear anodizing and titanated zirconium conversion coating.</p> <p><b>Spear Mounting in Concrete</b></p> <p>In addition to soil mounting, the KLV400 can be installed in a concrete footing for added stability and permanence.</p>	
<p><b>Low Voltage Surface Mount</b></p> <p>Cat. No.      Finish  <input type="checkbox"/> KLV405BL    Black  <input type="checkbox"/> KLV405DB    Dark Bronze  <input type="checkbox"/> KLV405GR    Verde Green  <input type="checkbox"/> No Option</p>	<p>Die-cast low copper aluminum with 1/2" NPSM fixture mount. Stainless steel set screw locks fixture into mount. Two holes provided for flat head wood screws. Super TGIC powder coat paint over clear anodizing and titanated zirconium conversion coating.</p>	
<p><b>Extension Module</b></p> <p>Cat. No.      Finish  <input type="checkbox"/> KLV415BL    Black  <input type="checkbox"/> KLV415DB    Dark Bronze  <input type="checkbox"/> KLV415GR    Verde Green  <input type="checkbox"/> No Option</p>	<p>For raising fixtures to a height above foliage for efficient and unobstructed operation. Constructed of 1 5/8" diameter extruded aluminum with die-cast ends. 1/2" NPSM female thread on one end, and other end has a 1/2" NPSM solid brass nipple. Stainless steel allen head set screw locks fixture onto mount. Super TGIC powder coat paint over titanated zirconium conversion coating. Two modules may be stacked for additional height.</p>	