

Type:
Job:

Approvals:

Fixture Catalog number:

Fixture Options:

Fixture and Finish

Ordered Separately from Fixture
 See page 2

Date:
Page: 1 of 2

Specifications

Housing and Lens Frame: Die-cast low copper alloy aluminum. Frame with silicone gasket, attaches to housing with four captive ¼-20 stainless steel, slotted cap screws.

Arm: Cast aluminum. Head is independently rotatable 360° vertically from top dead center. Head may be positioned straight up. Set screw provided for locking position.

Wall Plate: Die-cast low copper alloy aluminum. Attaches to stainless steel plate for mounting to any standard electrical outlet box. Internal set screw provided for locking position.

Lens: Tempered clear soda lime glass with silicone gasket. Flush with lens frame to promote water runoff when positioned upward.

Socket: G4 to GY6.35 socket for bipin lamp.

Wiring: No. 18-2 12 Volt cord.


Finish: Each luminaire receives a fade and abrasion resistant, electrostatically applied, thermally cured, triglycidal isocyanurate (TGIC) polyester powdercoat finish. Standard colors are Black (**BL**), Dark Bronze (**DB**), and Verde Green (**GR**).

Certification: UL Listed to U.S. and Canadian safety standards for wet locations.

ORDERING INFORMATION

Fixture ¹	Lamp	Finish
<input type="checkbox"/> KLV50BL	50W MR16 Bipin Halogen	Black
<input type="checkbox"/> KLV50DB	50W MR16 Bipin Halogen	Dark Bronze
<input type="checkbox"/> KLV50GR	50W MR16 Bipin Halogen	Verde Green

¹Remote transformer required.



KIM LIGHTING RESERVES THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE.

Type:

Job:

Page: 2 of 2



Fixture Options

Ordered Separately from Fixture

Lens Accessories

Cat. No. (See right)

No Option

HL72 - Hex Cell Louver: Constructed of hex cell aluminum louvers providing 45° cutoff, mounted in a circular frame, finished in baked high-heat flat black. Can be used in combination with colored lenses. Inserts behind lens into lens gasket. Cannot be used in combination with **SL** spread or **PL** prismatic lenses.

Cat. No.

HL72 Hex Cell Louver



PL72 - Prismatic Lens: Softens lamp distribution and flattens beam spread. Best with flood lamps. Inserts behind lens into lens gasket. Cannot be used in combination with **HL72** louver.

Cat. No.

PL72 Prismatic Lens



SL72 - Spread Lens: Creates an oval beam pattern, more narrow in one beam axis. Best with spot lamps. Inserts behind lens into lens gasket. Cannot be used in combination with **HL72** louver.

Cat. No.

SL72 Spread Lens

