

**Type:**  
**Job:**  
**Fixture Catalog number:**

**Approvals:**

Fixture and Finish

**Date:**  
**Page: 1 of 1**

## Specifications

**Housing:** Die-cast low copper alloy aluminum with clear anodized finish. Two 1/2" NPT in sides. Housing mounts into concrete, brick, or masonry (non-combustible materials). Internal splice area provided behind lamp plate.

**Lens Frame:** Die-cast aluminum, with silicone gasket, attaches to housing with two captive 10-32 stainless steel, hex socket cap screws.

**Lens:** Tempered prismatic glass with silicone gasket, concealed above lens frame opening.

**Socket:** G4 to GY6.35 socket for bipin lamp.

**Transformer:** Requires remote transformer.

**Finish:** Each luminaire receives a fade and abrasion resistant, electrostatically applied, thermally cured, triglycidal isocyanurate (TGIC) polyester powdercoat finish. Standard colors are Black (**BL**), Dark Bronze (**DB**), and Verde Green (**GR**).

**Certification:** UL Listed to U.S. and Canadian safety standards for wet locations.

## ORDERING INFORMATION

Fixture <sup>1</sup>	Lamp	Finish
<input type="checkbox"/> <b>KLV810BL</b>	50W T-3 or T-4 Bipin Halogen	Black
<input type="checkbox"/> <b>KLV810DB</b>	50W T-3 or T-4 Bipin Halogen	Dark Bronze
<input type="checkbox"/> <b>KLV810GR</b>	50W T-3 or T-4 Bipin Halogen	Verde Green

<sup>1</sup>Remote transformer required.

