

FEATURES & SPECIFICATIONS

INTENDED USE — The MRSL retrofit kit is designed to convert existing strip-based fixtures to LED technology. Flexible kit allows easy retrofit which reduces energy consumption for existing strip fixtures that are 4"-5" in width and approximately 2" in depth. **Certain airborne contaminants can diminish the integrity of acrylic and/or polycarbonate.** [Click here for Acrylic-Polycarbonate Compatibility table for suitable use.](#)

CONSTRUCTION — Die-formed channel cover secured by self-tapping screws for quick, secure mounting.

Finish: Paint process ensures superior paint adhesion and rust resistance. White paint finish is standard.

OPTICS — LEDs provide 80 CRI at 3500 K, 4000 K and 5000 K.

ELECTRICAL — Utilizes LEDs integrated on a two-layer circuit board, ensuring cool-running operation. Electronic LED driver is multi-volt. 0-10V dimming standard.

INSTALLATION — Channel cover installs quickly and securely using provided self-tapping screws.

LISTINGS — UL listed to US and Canadian safety standards. Damp location listed. Listed for 95°F (35°C) ambient.

DesignLights Consortium® (DLC) qualified product. Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.

WARRANTY — 5-year limited warranty. For use in damp locations with ambient temperatures ranging from -4°F (-20°C) to 95°F (35°C). Complete warranty terms located at: www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

NOTE: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Catalog Number
Notes
Type

LED Striplight Retrofit Kit

MRSL



Specifications			
All dimensions are shown in inches (centimeters) unless otherwise noted. (weight and dimensions could vary based upon options)			
LENGTH	WIDTH	DEPTH	WEIGHT
48 (121.92)	5 (12.7)	2.25 (5.72)	5 lbs. (2.3kgs)

ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Example: MRSL L48 1750LM 835 SBR10

Series	Length	Nominal Lumens ¹	Voltage	CRI/Color Temp	Options
MRSL	L48	1750LM	(Blank) 120-277V	835 80CRI 35K	E7W Emergency battery pack, 7W, non-CEC compliant
		3500LM		840 80CRI 40K	PLR1LVG Plug in wiring, low voltage
		5000LM		850 80CRI 50K	SBR10 Integrated dimming occupancy sensor
	L96 ¹	3500LM			L/Lens Less Lens
		7000LM			
		10000LM			

Notes

1 L96 fixtures come as 2' sections, one master and one satellite

OPERATIONAL DATA

Product	Lumens			Wattage	LPW		
	35K	40K	50K		35K	40K	50K
MRSL L48 1750LM	1722	1794	1852	13.74	125	131	135
MRSL L48 3500LM	3540	3689	3514	27.01	131	137	130
MRSL L48 5000LM	4763	4963	5121	35.26	135	141	145
MRSL L96 3500LM	3697	3853	3975	26.48	140	146	150
MRSL L96 7000LM	6641	6921	7139	48.85	136	142	146
MRSL L96 10000LM	10068	10492	10826	72.82	138	144	149