

Receptacles for dimming use



- Duplex for dimming both connected loads
- Projecting nubs prevent standard plugs from being used
- Requires replacement plugs for dimming use
- 15A model shown
- Includes 1-gang wallplate

Duplex for dimming use

15 A	120/125V*	NTR-15-DFDU- AA ²
20 A	120/125V*	NTR-20-DFDU- AA ²

Receptacles for dimming use



- Top half for dimming
- Projecting nub prevents standard plug from being used
- Requires replacement plugs for dimming use
- Bottom half is a general use receptacle and will fit standard duplex plugs
- 15A model shown
- Includes 1-gang wallplate

Split duplex (half for dimming use)

15 A	120/125V*	NTR-15-HFDU- AA ²
20 A	120/125V*	NTR-20-HFDU- AA ²

Receptacles for dimming use



- Duplex for dimming both connected loads
- Projecting nubs prevent standard plugs from being used
- Requires replacement plugs for dimming use
- 15A model shown
- Includes 1-gang wallplate
- Tamper resistant shutter mechanism

Dual dimming tamper resistant

15 A	120/125V*	NTR-15-DDTR- AA ²
20 A	120/125V*	NTR-20-DDTR- AA ²

Receptacles for dimming use



- Top half for dimming
- Projecting nub prevents standard plug from being used
- Requires replacement plugs for dimming use
- Bottom half is a general use receptacle and will fit standard duplex plugs
- 15A model shown
- Includes 1-gang wallplate
- Tamper resistant shutter mechanism

Half dimming tamper resistant

15 A	120/125V*	NTR-15-HDTR- AA ²
20 A	120/125V*	NTR-20-HDTR- AA ²

AA²: Architectural matte color codes, see pg. 153 (1-gang wallplate included)

*Metal finishes are only available as separate wallplates. Match with separate Black (BL) controls and accessories.