



DIMMER COMPATIBILITY

Project: _____

Fixture Type: _____

Location: _____

Contact/Phone: _____

Fixture Series

900 & 1400 LUMEN
LED DOWNLIGHT
TC 5" and 6"
Generation 4 Series

UNIVERSAL VOLTAGE			UNIVERSAL VOLTAGE
Universal Voltage (120-277V) Housings (-U) 0-10V Dimming Control • Dimming range of 100% down to 10% or lower with a minimum load of one fixture. ¹ Additional Lutron products required for switching functionality when using Lutron 0-10V dimmers (such as PP-120H or PP-277H)			Universal (120-277V) Fixtures with Lutron® Hi-Lume® A Series Driver (-L) 3-Wire Dimming and EcoSystem® Compatible • For a list of compatible dimmers, please reference Lutron's Report Card for EcoSystem and 3-Wire Control dimming systems located at - http://www.lutron.com/TechnicalDocumentLibrary/EcoSystem_3-wire_report_card.pdf Consult technical services for additional information regarding other dimmer model qualification.
Juno Qualified Dimmers			
Lutron® Model Numbers:	Leviton® Model Numbers:	Whole House Integrated Control Systems:	
Nova® NFTV Series ¹ Nova T*® NTFTV Series ¹ Diva® DDTV Series ¹ Grafik Eye QS GRX-TVI	ILLUMATECH™ IP710-DLX Series	Schneider Electric C-Bus SLCLE5504TAMP* Lutron® Homeworks® GRX-TVM2 Note: C-Bus is 25 fixtures per channel.	

* Juno recommended dimmers

Consult technical services for additional information regarding other dimmer model qualification.