





# Juno SlimForm™ LED with Selectable CCT

5" and 7" Round Downlight for JBox Installation

## JSF Series



### Dimensions



Project:
Fixture Type:
Location:
Contact/Phone:

### Product Features

Sleek, ultra-low profile energy efficient LED surface mount downlights available in 5" and 7" sizes. Optional finish trims available for custom, designer look similar to standard recessed downlights. Provides general illumination in residential and commercial applications including multi-family and hospitality. Ideal for use in corridors, living spaces, closets, hallways, pantries, stairways, outdoor covered areas and much more.

With the newly added selectable CCT switch, the JSF gives the ultimate in flexibility for both the distributor as well as the end user.

### Applications

- Suitable for wet locations (indoor covered ceilings): perfect for closets, showers, bathrooms, outdoor soffits, and covered ceiling applications.
- Residential and Light Commercial applications including multi-family and hospitality
- Ideal for use in corridors, foyers, living spaces, closets, hallways, pantries, stairways and much more
- Installs directly into industry standard junction boxes
- Suitable for use within closet storage spaces when installed per NEC requirements. *Junction box sizes vary - Verify compatibility with fixture prior to installation*

### Performance

Delivered Lumens	JSF 5IN = 800L JSF 7IN = 1100L
Led Color Temperature	Switchable White (2700K, 3000K, 3500K, 4000K, 5000K) Default set at 3000K
CRI	90+
Voltage	Dedicated 120V and MVOLT (120V-277V)
Dimming	Phase Dimming down to 10%. 0-10V and phase dimming available.

### Specifications

	Width	Depth
JSF 5IN	5.25 (13.34)	0.75 (1.91)
JSF 7IN	7.77 (19.74)	0.75 (1.91)

All dimensions are in Inches (centimeters unless otherwise indicated).



# Juno SlimForm™ LED with Selectable CCT

5" and 7" Round Downlight for JBox Installation



JSF

## ORDERING INFORMATION

### SlimForm LED Downlight

Example: JSF 5IN 07LM SWW5 90CRI 120 FRPC WH

Series	Size/Lumens	Color Temperature	CRI	Voltage/Driver	Finish
JSF SlimForm Surface Mount Downlight - Round	<b>5IN 07LM</b> 5", 700 Lumens	<b>SWW5</b> Switchable White (2700K, 3000K, 3500K, 4000K, 5000K)	<b>90CRI</b> 90+ CRI	<b>120 FRPC</b> Dedicated 120V, Forward Reverse Phase Dimming	<b>WH</b> White
	<b>7IN 10LM</b> 7", 1000 Lumens				<b>BL LGL</b> Black Low Glare lens
				<b>MVOLT ZT</b> Universal Voltage 120V-277V, 0-10V Dimming	<b>BZ LGL</b> Bronze Low Glare lens
					<b>SN LGL</b> Satin Nickel Low Glare Lens

## ACCESSORIES

**TRIM** – Optional, field installable finish trim rings available to change the exterior finish of fixture.

Example: JSFTRIM 5IN BZ

Series	Size	Finish
JSFTRIM SlimForm Accessory-Trim	5IN 5 inches	WH White
		BL Black
	7IN 7 inches	BZ Bronze
		SN* Satin Nickel

**Note:**

\* SN not available for 5IN



BLACK



BRONZE



SATIN NICKEL



# Juno SlimForm™ LED with Selectable CCT

5" and 7" Round Downlight for JBox Installation



JSF

## Specifications

### Construction

Shallow, less than 1", solid ring with white finish • Non conductive construction allows for light shower applications • Optional, field installable finish trims available for 5" and 7" versions to change the exterior finish of fixture

### Optics

Light guide technology combined with diffusing lens conceals the LEDs from direct view and provides uniform lens luminance.

### LED Light Engine

LEDs mounted directly to heatsink designed to provide superior thermal management and ensure long life • Selectable CCT with steps at 27K, 30K, 35K, 40K, 50K • LEDs binned for 4-step MacAdam ellipse color consistency • 90 CRI minimum.

### LED Driver

Choice of dedicated 120 volt (120) driver or universal voltage (MVOLT) driver that accommodates input voltages from 120-277 volts AC at 50/60Hz • Power factor > 0.9 at 120V input • 120 volt driver is dimmable with the use of most incandescent, magnetic low voltage and electronic low voltage wall box dimmers • Universal voltage driver is dimmable with the use of most 0-10V wall box dimmers • External driver is only available on 5" and 7" models • For a list of compatible dimmers, see [JUNOSLIMFORM-DIM](#).

### Installation

#### Junction Box Mounting

Fixture provided with leads for direct wire connection in j-box • Installs directly to industry standard junction boxes • Compatible junction boxes include 4" metal standard and IC1JB junction box housing (3 1/2" junction box screw-hole spacing required for installation) • Minimum 1 3/4" depth and minimum 3 1/2" width of junction box required for installation for 5" and 7" fixtures • Quick mount bracket provides fast installation of fully assembled fixture to junction box • Suitable for ceiling mount • Suitable for use within closet storage spaces when installed per NEC requirements. Junction box sizes vary - Verify compatibility with fixture prior to installation

### Life

Rated for 50,000 hours at >70% lumen maintenance.

### Labels

ENERGY STAR® certified • Certified to the high efficacy requirements of California T24 JA8-2019 • CSA listed for US and Canada • Suitable for wet locations (covered ceilings).

### Testing

All reports are based on published industry procedures; field performance may differ from laboratory performance.

### Warranty

5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: [www.acuitybrands.com/support/warranty/terms-and-conditions](http://www.acuitybrands.com/support/warranty/terms-and-conditions)

**Note:** Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications subject to change without notice.



# Juno SlimForm™ LED with Selectable CCT


5" and 7" Round Downlight for JBox Installation



JSF


## PHOTOMETRICS

JSF 5IN 07LM SWW5 - 27K Input Watts: 9.2, Delivered Lumens: 791, LPW: 86.0, S/MH: 1.25, Test No: ISF 231051P1




CP Summary				Zonal Lumen Summary				Coefficients of Utilization										Cone of Light			Luminance (cd/sq.m)	
0°	Zone	Lumens	% Fixture	pf pc	80%		20%		50%		Mounting Height	Initial FC Center Beam	Beam Diameter	Average Luminance								
				pw	50%	30%	10%	50%	30%	10%	50%	30%	10%									
0°	282	0° - 30°	220	28%	0	119	119	119	116	116	116	111	111	111	6.0	7.8	17.9	0°	31,550			
5°	282	0° - 40°	358	45%	1	104	100	96	102	98	94	98	94	91	8.0	4.4	23.8	45°	29,745			
15°	274	0° - 60°	625	79%	2	91	84	78	89	82	77	85	80	75	10.0	2.8	29.8	55°	28,478			
25°	253	0° - 90°	791	100%	3	80	71	65	78	70	64	75	69	63	12.0	2.0	35.8	65°	26,737			
35°	224	90° - 180°	0	0%	4	71	62	55	69	61	55	67	60	54	14.0	1.4	41.7	75°	24,207			
45°	188	0° - 180°	791	100%	5	63	54	47	62	54	47	60	52	47	Beam Angle: 112.3°			85°	21,822			
55°	146															Field Angle: 163.9°						
65°	101																					
75°	56																					
85°	17																					
90°	0																					

JSF 5IN 07LM SWW5 - 30K Input Watts: 9.1, Delivered Lumens: 814, LPW: 89.5, S/MH: 1.25, Test No: ISF 231051P2



CP Summary				Zonal Lumen Summary				Coefficients of Utilization										Cone of Light			Luminance (cd/sq.m)	
0°	Zone	Lumens	% Fixture	pf pc	80%		20%		50%		Mounting Height	Initial FC Center Beam	Beam Diameter	Average Luminance								
				pw	50%	30%	10%	50%	30%	10%	50%	30%	10%									
0°	290	0° - 30°	227	28%	0	119	119	119	116	116	116	111	111	111	6.0	8.1	17.9	0°	32,496			
5°	290	0° - 40°	369	45%	1	104	100	96	102	98	94	98	94	91	8.0	4.5	23.8	45°	30,638			
15°	282	0° - 60°	643	79%	2	91	84	78	89	82	77	85	80	75	10.0	2.9	29.8	55°	29,332			
25°	261	0° - 90°	814	100%	3	80	71	65	78	70	64	75	69	63	12.0	2.0	35.8	65°	27,539			
35°	231	90° - 180°	0	0%	4	71	62	55	69	61	55	67	60	54	14.0	1.5	41.7	75°	24,933			
45°	194	0° - 180°	814	100%	5	63	54	47	62	54	47	60	52	47	Beam Angle: 112.3°			85°	22,477			
55°	150															Field Angle: 163.9°						
65°	104																					
75°	58																					
85°	18																					
90°	0																					

JSF 5IN 07LM SWW5 - 35K Input Watts: 8.9, Delivered Lumens: 846, LPW: 95.1, S/MH: 1.25, Test No: ISF 231051P3



CP Summary				Zonal Lumen Summary				Coefficients of Utilization										Cone of Light			Luminance (cd/sq.m)	
0°	Zone	Lumens	% Fixture	pf pc	80%		20%		50%		Mounting Height	Initial FC Center Beam	Beam Diameter	Average Luminance								
				pw	50%	30%	10%	50%	30%	10%	50%	30%	10%									
0°	302	0° - 30°	236	28%	0	119	119	119	116	116	116	111	111	111	6.0	8.4	17.9	0°	33,758			
5°	302	0° - 40°	383	45%	1	104	100	96	102	98	94	98	94	91	8.0	4.7	23.8	45°	31,827			
15°	293	0° - 60°	668	79%	2	91	84	78	89	82	77	85	80	75	10.0	3.0	29.8	55°	30,471			
25°	271	0° - 90°	846	100%	3	80	71	65	78	70	64	75	69	63	12.0	2.1	35.8	65°	28,609			
35°	240	90° - 180°	0	0%	4	71	62	55	69	61	55	67	60	54	14.0	1.5	41.7	75°	25,901			
45°	201	0° - 180°	846	100%	5	63	54	47	62	54	47	60	52	47	Beam Angle: 112.3°			85°	23,350			
55°	156															Field Angle: 163.9°						
65°	108																					
75°	60																					
85°	18																					
90°	0																					



# Juno SlimForm™ LED with Selectable CCT


5" and 7" Round Downlight for JBox Installation



JSF

## PHOTOMETRICS


JSF 5IN 07LM SWW5 - 40K Input Watts: 9.1, Delivered Lumens: 854, LPW: 93.8, S/MH: 1.25, Test No: ISF 231051P4



CP Summary		Zonal Lumen Summary				Coefficients of Utilization										Cone of Light			Luminance (cd/sq.m)	
0°	Zone	Lumens	% Fixture	pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	Mounting Height	Initial FC Center Beam	Beam Diameter	Average Luminance			
0°	0° - 30°	238	28%	0	119	119	119	116	116	116	111	111	111	6.0	8.5	17.9	0°	34,074		
5°	0° - 40°	386	45%	1	104	100	96	102	98	94	98	94	91	8.0	4.8	23.8	45°	32,125		
15°	0° - 60°	675	79%	2	91	84	78	89	82	77	85	80	75	10.0	3.0	29.8	55°	30,756		
25°	0° - 90°	854	100%	3	80	71	65	78	70	64	75	69	63	12.0	2.1	35.8	65°	28,876		
35°	90° - 180°	0	0%	4	71	62	55	69	61	55	67	60	54	14.0	1.6	41.7	75°	26,143		
45°	0° - 180°	854	100%	5	63	54	47	62	54	47	60	52	47				85°	23,568		
55°		158		6	57	48	41	56	47	41	54	47	41							
65°		109		7	52	43	37	51	42	36	49	42	36							
75°		60		8	47	39	33	46	38	33	45	38	32							
85°		18		9	43	35	29	43	35	29	42	34	29							
90°		0		10	40	32	27	39	32	27	38	31	27							

Beam Angle: 112.3°  
Field Angle: 163.9°


JSF 5IN 07LM SWW5 - 50K Input Watts: 9.2, Delivered Lumens: 854, LPW: 92.8, S/MH: 1.25, Test No: ISF 231051P5



CP Summary		Zonal Lumen Summary				Coefficients of Utilization										Cone of Light			Luminance (cd/sq.m)	
0°	Zone	Lumens	% Fixture	pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	Mounting Height	Initial FC Center Beam	Beam Diameter	Average Luminance			
0°	0° - 30°	238	28%	0	119	119	119	116	116	116	111	111	111	6.0	8.5	17.9	0°	34,074		
5°	0° - 40°	386	45%	1	104	100	96	102	98	94	98	94	91	8.0	4.8	23.8	45°	32,125		
15°	0° - 60°	675	79%	2	91	84	78	89	82	77	85	80	75	10.0	3.0	29.8	55°	30,756		
25°	0° - 90°	854	100%	3	80	71	65	78	70	64	75	69	63	12.0	2.1	35.8	65°	28,876		
35°	90° - 180°	0	0%	4	71	62	55	69	61	55	67	60	54	14.0	1.6	41.7	75°	26,143		
45°	0° - 180°	854	100%	5	63	54	47	62	54	47	60	52	47				85°	23,568		
55°		158		6	57	48	41	56	47	41	54	47	41							
65°		109		7	52	43	37	51	42	36	49	42	36							
75°		60		8	47	39	33	46	38	33	45	38	32							
85°		18		9	43	35	29	43	35	29	42	34	29							
90°		0		10	40	32	27	39	32	27	38	31	27							

Beam Angle: 112.3°  
Field Angle: 163.9°

JSF 7IN 10LM SWW5 - 27K Input Watts: 12.0, Delivered Lumens: 1182, LPW: 98.5, S/MH: 1.24, Test No: ISF 23588P1



CP Summary		Zonal Lumen Summary				Coefficients of Utilization										Cone of Light			Luminance (cd/sq.m)	
0°	Zone	Lumens	% Fixture	pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	Mounting Height	Initial FC Center Beam	Beam Diameter	Average Luminance			
0°	0° - 30°	331	28%	0	119	119	119	116	116	116	111	111	111	6.0	11.8	16.9	0°	18,617		
5°	0° - 40°	538	45%	1	104	100	96	102	98	94	97	94	91	8.0	6.7	22.5	45°	16,934		
15°	0° - 60°	937	79%	2	91	84	78	89	83	77	85	80	75	10.0	4.3	28.2	55°	16,153		
25°	0° - 90°	1,182	100%	3	80	72	65	78	71	64	75	69	63	12.0	3.0	33.8	65°	14,891		
35°	90° - 180°	0	0%	4	71	62	55	69	61	55	67	60	54	14.0	2.2	39.5	75°	12,833		
45°	0° - 180°	1,182	100%	5	63	54	48	62	54	47	60	52	47				85°	10,029		
55°		212		6	57	48	42	56	47	41	54	47	41							
65°		144		7	52	43	37	51	42	37	49	42	36							
75°		76		8	47	39	33	46	38	33	45	38	32							
85°		20		9	43	35	29	43	35	29	42	34	29							
90°		0		10	40	32	27	39	32	27	38	31	27							

Beam Angle: 109.3°  
Field Angle: 161.5°



# Juno SlimForm™ LED with Selectable CCT


5" and 7" Round Downlight for JBox Installation



JSF


## PHOTOMETRICS

JSF 7IN 10LM SWW5 - 30K Input Watts: 12.3, Delivered Lumens: 1218, LPW: 99.0, S/MH: 1.24, Test No: ISF 23588P2




CP Summary				Zonal Lumen Summary				Coefficients of Utilization										Cone of Light			Luminance (cd/sq.m)	
0°	Zone	Lumens	% Fixture	pf pc	80%		20%		50%		Mounting Height	Initial FC Center Beam	Beam Diameter	Average Luminance								
				pw	50%	30%	10%	50%	30%	10%				0°	85°							
0°	439	0° - 30°	341	28%	0	119	119	119	116	116	116	111	111	111	6.0	12.2	16.9	0°	19,176			
5°	438	0° - 40°	554	45%	1	104	100	96	102	98	94	97	94	91	8.0	6.9	22.5	45°	17,442			
15°	422	0° - 60°	966	79%	2	91	84	78	89	83	77	85	80	75	10.0	4.4	28.2	55°	16,637			
25°	388	0° - 90°	1,218	100%	3	80	72	65	78	71	64	75	69	63	12.0	3.0	33.8	65°	15,338			
35°	342	90° - 180°	0	0%	4	71	62	55	69	61	55	67	60	54	14.0	2.2	39.5	75°	13,218			
45°	282	0° - 180°	1,218	100%	5	63	54	48	62	54	47	60	52	47	Beam Angle: 109.3°			85°	10,329			
55°	218				6	57	48	42	56	47	41	54	47	41	Field Angle: 161.5°							
65°	148				7	52	43	37	51	42	37	49	42	36								
75°	78				8	47	39	33	46	38	33	45	38	32								
85°	21				9	43	35	29	43	35	29	42	34	29								
90°	0				10	40	32	27	39	32	27	38	31	27								

JSF 7IN 10LM SWW5 - 35K Input Watts: 12.1, Delivered Lumens: 1265, LPW: 104.5, S/MH: 1.24, Test No: ISF 23588P3



CP Summary				Zonal Lumen Summary				Coefficients of Utilization										Cone of Light			Luminance (cd/sq.m)	
0°	Zone	Lumens	% Fixture	pf pc	80%		20%		50%		Mounting Height	Initial FC Center Beam	Beam Diameter	Average Luminance								
				pw	50%	30%	10%	50%	30%	10%				0°	85°							
0°	456	0° - 30°	354	28%	0	119	119	119	116	116	116	111	111	111	6.0	12.7	16.9	0°	19,920			
5°	455	0° - 40°	575	45%	1	104	100	96	102	98	94	97	94	91	8.0	7.1	22.5	45°	18,120			
15°	439	0° - 60°	1,003	79%	2	91	84	78	89	83	77	85	80	75	10.0	4.6	28.2	55°	17,284			
25°	403	0° - 90°	1,265	100%	3	80	72	65	78	71	64	75	69	63	12.0	3.2	33.8	65°	15,933			
35°	355	90° - 180°	0	0%	4	71	62	55	69	61	55	67	60	54	14.0	2.3	39.5	75°	13,731			
45°	293	0° - 180°	1,265	100%	5	63	54	48	62	54	47	60	52	47	Beam Angle: 109.3°			85°	10,731			
55°	227				6	57	48	42	56	47	41	54	47	41	Field Angle: 161.5°							
65°	154				7	52	43	37	51	42	37	49	42	36								
75°	81				8	47	39	33	46	38	33	45	38	32								
85°	21				9	43	35	29	43	35	29	42	34	29								
90°	0				10	40	32	27	39	32	27	38	31	27								

JSF 7IN 10LM SWW5 - 40K Input Watts: 12.2, Delivered Lumens: 1301, LPW: 106.6, S/MH: 1.24, Test No: ISF 23588P4



CP Summary				Zonal Lumen Summary				Coefficients of Utilization										Cone of Light			Luminance (cd/sq.m)	
0°	Zone	Lumens	% Fixture	pf pc	80%		20%		50%		Mounting Height	Initial FC Center Beam	Beam Diameter	Average Luminance								
				pw	50%	30%	10%	50%	30%	10%				0°	85°							
0°	469	0° - 30°	364	28%	0	119	119	119	116	116	116	111	111	111	6.0	13.0	16.9	0°	20,479			
5°	468	0° - 40°	592	45%	1	104	100	96	102	98	94	97	94	91	8.0	7.3	22.5	45°	18,628			
15°	451	0° - 60°	1,031	79%	2	91	84	78	89	83	77	85	80	75	10.0	4.7	28.2	55°	17,768			
25°	415	0° - 90°	1,300	100%	3	80	72	65	78	71	64	75	69	63	12.0	3.3	33.8	65°	16,380			
35°	365	90° - 180°	0	0%	4	71	62	55	69	61	55	67	60	54	14.0	2.4	39.5	75°	14,116			
45°	301	0° - 180°	1,301	100%	5	63	54	48	62	54	47	60	52	47	Beam Angle: 109.3°			85°	11,031			
55°	233				6	57	48	42	56	47	41	54	47	41	Field Angle: 161.5°							
65°	158				7	52	43	37	51	42	37	49	42	36								
75°	84				8	47	39	33	46	38	33	45	38	32								
85°	22				9	43	35	29	43	35	29	42	34	29								
90°	0				10	40	32	27	39	32	27	38	31	27								



# Juno SlimForm™ LED with Selectable CCT


5" and 7" Round Downlight for JBox Installation



JSF

## PHOTOMETRICS

JSF 7IN 10LM SWW5 - 50K Input Watts: 12.3, Delivered Lumens: 1324, LPW: 107.6, S/MH: 1.24, Test No: ISF 23588P5



CP Summary	Zonal Lumen Summary				Coefficients of Utilization									Cone of Light			Luminance (cd/sq.m)		
	0°	Zone	Lumens	% Fixture	pw	80%			20%			50%			Mounting Height	Initial FC Center Beam	Beam Diameter	Average Luminance	
						50%	30%	10%	50%	30%	10%	50%	30%	10%					
0°	477	0° - 30°	370	28%	0	119	119	119	116	116	116	111	111	111	6.0	13.3	16.9	0°	20,851
5°	476	0° - 40°	602	45%	1	104	100	96	102	98	94	97	94	91	8.0	7.5	22.5	45°	18,967
15°	459	0° - 60°	1,050	79%	2	91	84	78	89	83	77	85	80	75	10.0	4.8	28.2	55°	18,091
25°	422	0° - 90°	1,324	100%	3	80	72	65	78	71	64	75	69	63	12.0	3.3	33.8	65°	16,678
35°	372	90° - 180°	0	0%	4	71	62	55	69	61	55	67	60	54	14.0	2.4	39.5	75°	14,373
45°	307	0° - 180°	1,324	100%	5	63	54	48	62	54	47	60	52	47				85°	11,232
55°	237				6	57	48	42	56	47	41	54	47	41					
65°	161				7	52	43	37	51	42	37	49	42	36					
75°	85				8	47	39	33	46	38	33	45	38	32					
85°	22				9	43	35	29	43	35	29	42	34	29					
90°	0				10	40	32	27	39	32	27	38	31	27					

Beam Angle: 109.3°  
Field Angle: 161.5°