



JOB NAME:	
DATE:	
TYPE:	

DESCRIPTION

Versatile HPS Floodlight with hinged lens frame and hydroformed reflector. Field adjustable vertical and horizontal lamp positions. Lamp supplied.

SPECIFICATIONS

Finish:

Chip and fade resistant polyester powder coat finish

Ground Mounting:

Use the new MPM19 PVC Mighty Post with aluminum cap for sturdy installation

Housing:

Precision die cast aluminum. 1/2" NPS threaded arm with locking swivel

Lens Frame:

Precision die cast aluminum. Hinged for easy access

Lens Gasket:

High temperature tubular silicone set in die cast retaining groove remains in place during relamping.

Reflector:

Hydroformed aluminum. Field adjustable vertical or horizontal

Socket:

Porcelain 4kv Pulse Rated socket with nickel plated screw shell

UL Listing:

Suitable for wet locations. Suitable for mounting within 4' of the ground

EPA: 0.6

Patents:


RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

Quad Tap:

Fixture works with 120, 208, 240 and 277 Volts


Color: White Weight: 13.5

DIMENSIONS



PHOTOMETRIC

150w HPS @ 10' Mounting Height Aimed 30° below horizontal



ORDERING INFORMATION

High Pressure Sodium Lamp supplied with fixture					Starting Amps/ Operating Amps 120V 208V 240V 277V			Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours	
	150	ED17	Medium	HX-HPF QT	2.0/1.7	1.2/1.0	1/1.9	.9/.8	188	S55	16000	24000

Factory Installed Options Add suffix to Catalog Number Swivel Photocontrol wired for 120V (/PCS) Dual Tap works with 120 / 277 volts (/DT) Quad Tap works with 120, 208, 240 and 277 volts (/the control wired for 120V (/PC) (/PC) and 277 volts (/the control wired for 120V (/PC) (/the control wired for 120V (/the control wired for 12

Note: Specifications may change without notice

RAB Lighting, Inc. • 170 Ludlow Ave• Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com