



# FXL250SFQTW/PC



JOB NAME: \_\_\_\_\_

DATE: \_\_\_\_\_

TYPE: \_\_\_\_\_

## DESCRIPTION

HPS or MH specification grade flood with Integra Hood glare shield and slip fitter mount for 2 3/8" diameter tenons. Lamp supplied.

## SPECIFICATIONS

### Finish:

Chip and fade resistant polyester powder coating.

### Housing:

Precision die cast aluminum with Wall Bracket, Trunnion or Slipfitter.

### Lens Frame & Glare Shield:

Precision die cast aluminum. Hinged for easy access. Phillips head screws for added security.

### Lens Gasket:

High temperature one piece molded silicone set in die cast retaining groove. Remains in place during relamping

### Lens:

Thermal tempered shock resistant glass, 3/16" thick.

### Reflector:

Anodized aluminum. Field adjustable beam spread.

### Socket:

HID: Porcelain 4kv Pulse Rated socket with nickel plated screw shell CFL: Plug in type, GX24q-4 base

### UL Listing:

Suitable for wet locations. Suitable for mounting within 4' of the ground

### EPA:

Maximum EPA: 2.0

### Patents:

Pat. D552,283

### Photocontrol:

Button Photocontrol installed and wired for 120V

### Color:

White

### Weight:

33.8

## ORDERING INFORMATION

**High Pressure Sodium**  
Lamp supplied with fixture

Total Watts	Lamp Type	Lamp Base	Ballast
250	ED18	Mogul	CWA-HPF QT

Starting Amps/ Operating Amps			
120V	208V	240V	277V
1.7/2.5	1.1/1.5	0.8/1.3	0.7/1.1

Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
295	S50	28500	24000

**Factory Installed Options**  
Add suffix to Catalog Number

Swivel Photocontrol wired for 120V (/PCS)  
Single fusing for 120 and 277 volt (/F)

Double fusing for 208 and 240 volt (/FF)  
Button Photocontrol wired for 120V (/PC)

Note: Specifications may change without notice

**RAB Lighting, Inc.** • 170 Ludlow Ave • Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • [www.rabweb.com](http://www.rabweb.com)  
© 2009