



FXL250TQTW/PC



JOB NAME: _____

DATE: _____

TYPE: _____

DESCRIPTION

HPS or MH specification grade flood with Integra Hood glare shield and trunnion mounting bracket. Lamp supplied.

SPECIFICATIONS

Finish:

Chip and fade resistant polyester powder coating.

Housing:

Precision die cast aluminum with Wall Bracket, Trunnion or Slipfitter.

Lens Frame & Glare Shield:

Precision die cast aluminum. Hinged for easy access. Phillips head screws for added security.

Lens Gasket:

High temperature one piece molded silicone set in die cast retaining groove. Remains in place during relamping

Lens:

Thermal tempered shock resistant glass, 3/16" thick.

Reflector:

Anodized aluminum. Field adjustable beam spread.

Socket:

HID: Porcelain 4kv Pulse Rated socket with nickel plated screw shell CFL: Plug in type, GX24q-4 base

UL Listing:

Suitable for wet locations. Suitable for mounting within 4' of the ground

EPA:

Maximum EPA: 2.0

Patents:

Pat. D550,387

Photocontrol:

Button Photocontrol installed and wired for 120V

Color:

White

Weight:

33.3

ORDERING INFORMATION

High Pressure Sodium
Lamp supplied with fixture

Total Watts	Lamp Type	Lamp Base	Ballast
250	ED18	Mogul	CWA-HPF QT

Starting Amps/ Operating Amps			
120V	208V	240V	277V
1.7/2.5	1.1/1.5	0.8/1.3	0.7/1.1

Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
295	S50	28500	24000

Factory Installed Options
Add suffix to Catalog Number

Swivel Photocontrol wired for 120V (/PCS)
Single fusing for 120 and 277 volt (/F)

Double fusing for 208 and 240 volt (/FF)
Button Photocontrol wired for 120V (/PC)

Note: Specifications may change without notice

RAB Lighting, Inc. • 170 Ludlow Ave • Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com
© 2009