



# FXL400XQTW/PC



JOB NAME: \_\_\_\_\_  
 DATE: \_\_\_\_\_  
 TYPE: \_\_\_\_\_

## DESCRIPTION

HPS or MH specification grade flood with Integra Hood glare shield and fixed wall mounting bracket. Bracket provides 2 different Full Cutoff Mounting angles. Can be mounted as uplight. Lamp supplied.

## SPECIFICATIONS

### Finish:

Chip and fade resistant polyester powder coating.

### Housing:

Precision die cast aluminum with Wall Bracket, Trunnion or Slipfitter.

### Lens Frame & Glare Shield:

Precision die cast aluminum. Hinged for easy access. Phillips head screws for added security.

### Lens Gasket:

High temperature one piece molded silicone set in die cast retaining groove. Remains in place during relamping

### Lens:

Thermal tempered shock resistant glass, 3/16" thick.

### Reflector:

Anodized aluminum. Field adjustable beam spread.

### Socket:

HID: Porcelain 4kv Pulse Rated socket with nickel plated screw shell CFL: Plug in type, GX24q-4 base

### UL Listing:

Suitable for wet locations. Suitable for mounting within 4' of the ground

### Patents:

Pat. D552,282

### Color:

White

### Weight:

36.8

## ORDERING INFORMATION

| High Pressure Sodium<br>Lamp supplied with fixture | Total<br>Watts | Lamp<br>Type | Lamp<br>Base | Ballast    | Starting Amps/ Operating Amps |         |         |         | Input<br>Watts | LAMP<br>ANSI | Initial<br>Lumens | Lamp<br>Hours |
|--|----------------|--------------|--------------|------------|-------------------------------|---------|---------|---------|----------------|--------------|-------------------|---------------|
|  |                |              |              |            | 120V                          | 208V    | 240V    | 277V    |                |              |                   |               |
|  | 400            | ED18         | Mogul        | CWA-HPF QT | 3.3/3.8                       | 1.8/2.2 | 1.5/1.9 | 1.4/1.7 | 464            | S51          | 50000             | 24000         |

**Factory Installed Options**  
 Add suffix to Catalog Number

Swivel Photocontrol wired for 120V (/PCS)  
 Single fusing for 120 and 277 volt (/F)

Double fusing for 208 and 240 volt (/FF)  
 Button Photocontrol wired for 120V (/PC)

Note: Specifications may change without notice