



JOB NAME: _____
 DATE: _____
 TYPE: _____

FXLH200TPSQ/PC

DESCRIPTION

HPS or MH specification grade flood with Integra Hood glare shield and trunnion mounting bracket. Lamp supplied.

SPECIFICATIONS

Finish:

Chip and fade resistant polyester powder coating.

Housing:

Precision die cast aluminum with Wall Bracket, Trunnion or Slipfitter.

Lens Frame & Glare Shield:

Precision die cast aluminum. Hinged for easy access. Phillips head screws for added security.

Lens Gasket:

High temperature one piece molded silicone set in die cast retaining groove. Remains in place during relamping

Lens:

Thermal tempered shock resistant glass, 3/16" thick.

Reflector:

Anodized aluminum. Field adjustable beam spread.

Socket:

HID: Porcelain 4kv Pulse Rated socket with nickel plated screw shell CFL: Plug in type, GX24q-4 base

UL Listing:

Suitable for wet locations. Suitable for mounting within 4' of the ground

EPA:

Maximum EPA: 2.0

Patents:

Pat. D550,387

Photocontrol:

Button Photocontrol installed and wired for 208, 208, 277 Volts

Pulse Start:

Pulse Start metal halide for increased lamp life, lumen maintenance, color uniformity and efficiency

Color:

Bronze

Weight:

30.3

ORDERING INFORMATION

Metal Halide Lamp supplied with fixture	Total Watts	Lamp Type	Lamp Base	Ballast	Starting Amps/ Operating Amps				Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
					120V	208V	240V	277V				
	200	T15	Mogul	CWA-HPF QT	1.4/2.0	0.8/1.2	0.7/1.0	0.6/0.9	232	M136	19000	15000

Factory Installed Options
 Add suffix to Catalog Number

Swivel Photocontrol wired for 120V (/PCS)
 Single fusing for 120 and 277 volt (/F)

Double fusing for 208 and 240 volt (/FF)
 Button Photocontrol wired for 120V (/PC)

Note: Specifications may change without notice