JOB NAME: _____

DATE: _____

TYPE: _____

FXLH200XPSQW/

DESCRIPTION

HPS or MH specification grade flood with Integra Hood glare shield and fixed wall mounting bracket. Bracket provides 2 different Full Cutoff Mounting angles. Can be mounted as uplight. Lamp supplied.

SPECIFICATIONS

Finish:
Chip and fade resistant polyester powder coating.

Housing:
Precision die cast aluminum with Wall Bracket, Trunnion or Slipfitter.

Lens Frame & Glare Shield:
Precision die cast aluminum. Hinged for easy access. Phillips head screws for added security.

Lens Gasket:
High temperature one piece molded silicone set in die cast retaining groove. Remains in place during relamping

Lens:
Thermal tempered shock resistant glass, 3/16" thick.

Reflector:
Anodized aluminum. Field adjustable beam spread.

Socket:
HID: Porcelain 4kv Pulse Rated socket with nickel plated screw shell CFL: Plug in type, GX24q-4 base

UL Listing:
Suitable for wet locations. Suitable for mounting within 4' of the ground

Patents:
Pat. D552,282

Color:
White

Weight:
30.8

ORDERING INFORMATION

Metal Halide
Lamp supplied with fixture

Total Watts	Lamp Type	Lamp Base	Ballast	Starting Amps/ Operating Amps 120V	208V	240V	277V	Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
200	T15	Mogul	CWA-HPF QT	1.4/2.0	0.8/1.2	0.7/1.0	0.6/0.9	232	M136	19000	15000

Factory Installed Options
Add suffix to Catalog Number

Swivel Photocontrol wired for 120V (/PCS)
Single fusing for 120 and 277 volt (/F)
Double fusing for 208 and 240 volt (/FF)
Button Photocontrol wired for 120V (/PC)

Note: Specifications may change without notice

RAB Lighting, Inc. • 170 Ludlow Ave• Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com
© 2009