



FXLH350SFPSQW



JOB NAME: _____
 DATE: _____
 TYPE: _____

DESCRIPTION

HPS or MH specification grade flood with Integra Hood glare shield and slip fitter mount for 2 3/8" diameter tenons. Lamp supplied.

SPECIFICATIONS

Finish:

Chip and fade resistant polyester powder coating.

Housing:

Precision die cast aluminum with Wall Bracket, Trunnion or Slipfitter.

Lens Frame & Glare Shield:

Precision die cast aluminum. Hinged for easy access. Phillips head screws for added security.

Lens Gasket:

High temperature one piece molded silicone set in die cast retaining groove. Remains in place during relamping

Lens:

Thermal tempered shock resistant glass, 3/16" thick.

Reflector:

Anodized aluminum. Field adjustable beam spread.

UL Listing:

Suitable for wet locations. Suitable for mounting within 4' of the ground

Socket:

HID: Porcelain 4kv Pulse Rated socket with nickel plated screw shell CFL: Plug in type, GX24q-4 base

EISA 2007 Compliant

This product complies with the new law for metal halide ballast efficiency. This law goes into effect January 1st, 2008

EPA:

Maximum EPA: 2.0

Patents:

Pat. D552,283

Photocontrol:

Button Photocontrol installed and wired for 208, 208, 277 Volts

Pulse Start:

Pulse Start metal halide for increased lamp life, lumen maintenance, color uniformity and efficiency

Color:

White

Weight:

33.5

ORDERING INFORMATION

Metal Halide Lamp supplied with fixture	Total Watts	Lamp Type	Lamp Base	Ballast	Starting Amps/ Operating Amps				Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
					120V	208V	240V	277V				
	350	ED28	Mogul	CWA-HPF QT	3.3/3.6	1.9/2.1	1.7/1.8	1.4/1.6	400	M131	33000	20000
Factory Installed Options Add suffix to Catalog Number				Swivel Photocontrol wired for 120V (/PCS) Single fusing for 120 and 277 volt (/F)					Double fusing for 208 and 240 volt (/FF) Button Photocontrol wired for 120V (/PC)			

Note: Specifications may change without notice