



JOB NAME: \_\_\_\_\_  
DATE: \_\_\_\_\_  
TYPE: \_\_\_\_\_

# FXLH400XPSQ/PC

## DESCRIPTION

HPS or MH specification grade flood with Integra Hood glare shield and fixed wall mounting bracket. Bracket provides 2 different Full Cutoff Mounting angles. Can be mounted as uplight. Lamp supplied.

## SPECIFICATIONS

**Finish:**

Chip and fade resistant polyester powder coating.

**Housing:**

Precision die cast aluminum with Wall Bracket, Trunnion or Slipfitter.

**Lens Frame & Glare Shield:**

Precision die cast aluminum. Hinged for easy access. Phillips head screws for added security.

**Lens Gasket:**

High temperature one piece molded silicone set in die cast retaining groove. Remains in place during relamping

**Lens:**

Thermal tempered shock resistant glass, 3/16" thick.

**Patents:**

Pat. D552,282

**Reflector:**

Anodized aluminum. Field adjustable beam spread.

**Socket:**

HID: Porcelain 4kv Pulse Rated socket with nickel plated screw shell CFL: Plug in type, GX24q-4 base

**UL Listing:**

Suitable for wet locations. Suitable for mounting within 4' of the ground

**EISA 2007 Compliant**

This product complies with the new law for metal halide ballast efficiency. This law goes into effect January 1st, 2008

**Color:**

Bronze

**Weight:**

33.5

## ORDERING INFORMATION

Metal Halide Lamp supplied with fixture	Total Watts	Lamp Type	Lamp Base	Ballast	Starting Amps/ Operating Amps				Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
					120V	208V	240V	277V				
	400	ED28	Mogul	CWA-HPF QT	3.5/4.0	2.0/2.3	1.8/2.0	1.5/1.8	450	M135/M46600	46600	20000

**Factory Installed Options**  
Add suffix to Catalog Number

Swivel Photocontrol wired for 120V (/PCS)  
Single fusing for 120 and 277 volt (/F)

Double fusing for 208 and 240 volt (/FF)  
Button Photocontrol wired for 120V (/PC)

Note: Specifications may change without notice