

	1
8.	/

JOB NAME:	
DATE:	
TYPE:	

DESCRIPTION

Floodinator with steel trunnion mount allows easy surface mounting for aiming flexibility. Factory wired with QT CWA-HPF ballast and 3-foot flexible cord. Adjustable aiming over 180° arc. Mounting can be locked securely in place. Lamp supplied.

SPECIFICATIONS

Effective Projected Area:

EPA = 4.2

Finish:

Chip and fade resistant polyester powder coating.

Housina:

One-piece die cast aluminum with die cast door frame held captive when opened

Lens Gasket:

High temperature extruded silicone set in die mounting within 4' of the ground cast retaining groove. Remains in place during relamping

Lens:

Thermal, tempered shock resistant glass, 5/32" thick

Reflector:

High quality anodized aluminum eliminates redirected energy to prolong lamp life. Contoured for maximum horizontal and vertical beam dispersion

Socket:

Porcelain socket pulse rate 4 KV, 1500 watts and 600 volts, reinforced with cat's eyes for added durability. Silicone and fiberglass #14 gauge socket leads rated for 200°C. Plated screw shell designed to resist corrosion with spring loaded center contact.

UL Listing:

Suitable for wet locations. Suitable for

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws

Color: Bronze Weight: 73.75

DIMENSIONS



ORDERING INFORMATION

High Pressure Sodium Lamp supplied with fixture			Ballast	Starting Amps/ Operating Amps 120V 208V 240V 277V			Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours		
	1000	BT37	Mogul	CWA-HPF QT	6.4/9.5	3.8/5.5	3.2/4.8	2.8/4.2	1100	S52	125000	24000

Factory Installed Options Add suffix to Catalog Number Swivel Photocontrol wired for 480 Volt (/PCS4) Single fusing for 120 and 277 volt (/F) Swivel Photocontrol wired for 208 - 240 Volt (/PC S2)uble fusing for 208 and 240 volt. (/FF) Swivel Photocontrol wired for 120V (/PCS) Button Photocontrol wired for 120V (/PC)

480 Volt (/480)

Note: Specifications may change without notice

RAB Lighting, Inc. • 170 Ludlow Ave• Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com © 2009