

BTH250GPSQ

Metal Halide HID with temporary guard.

Color: N/A

Weight: 21.1 lbs



Lamp Info

Type: BT28
 Watts: 250W
 Shape/Size: N/A
 Base: N/A
 ANSI: N/A
 Hours: 15,000
 Lamp Lumens: 23800
 Efficacy: 86 LPW

Ballast Info

Type: CWA HPF QT
 120V: 1.4/2.5A
 208V: .8/1.5A
 240V: .7/1.3A
 277V: .6/1.1A
 Input Watts: 278W
 Efficiency: 90%

Technical Specifications

UL Listing:

Suitable for damp locations.

Housing:

Die cast aluminum housing and wiring box with 1/2" NPS knockouts and easy leveling adjustment. Comes with 3' cord, hook/loop and safety chain.

Ballast:

Quad-Tap CWA Ballast (120/208/240/277 Volt).

Watts:

250 Watt.

Mounting Box:

Die-cast aluminum mounting box tapped for 3/4" conduit.

Lamp:

Mogul Base Up BT28 Metal Halide lamp supplied.

2005 NEC Compliance:

Open rated lamp and socket comply with 2005 NEC code .

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.