


# CLED2X13YBBW/PCS

26 Watts of energy efficient ceiling mounted LED lighting. 100,000-hour LED lifespan. 5 year warranty. Flush mount fixture bracket. LED Light Engine included.

Color: White

Weight: 6.6 lbs



## LED Info

Watts: 26W  
 Color Temp: 3000K (Warm)  
 Color Accuracy: 86  
 L70 Lifespan: 100000  
 LM79 Lumens: 1281  
 Efficacy: 42 LPW

## Driver Info

Type: Constant Current  
 120V: 0.6A  
 208V: N/A  
 240V: N/A  
 277V: N/A  
 Input Watts: 31W  
 Efficiency: 85%

## Technical Specifications

### CLED2X13 with Back Box:

Surface mounting box for CLED2X13.

### CLED2X13 with Photocell:

120V Swivel Photocell Included. Photocell is only compatible with 120V.

### UL Listing:

Suitable for wet locations.

### Lifespan:

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

### Driver:

Multi-chip 13W high output long life LED Driver  
 Constant Current, Class 2 100V - 277V, 50/60 Hz.

### THD:

12.16% at 120V

### Thermal Management:

Cast aluminum Thermal Management system for optimal heat sinking. Designed for cool operation, most efficient output and maximum LED life by minimizing LED junction temperature.

### Lumen Maintenance:

The LED will deliver 70% of its initial lumens at 100,000 hours of operation.

### Housing:

Precision die cast aluminum housing and lens framing.

### Finish:

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contains no VOC or toxic heavy metals.

## Green Technology:

RAB LEDs are Mercury and UV free.

## Patents:

The design of the CLED is protected by U.S. Pat. D608,040, D615,689, Canada Patent 821412 and patents pending in China, Taiwan and Mexico.

## Mounting Accessory:

Surface mounting box

## Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish.

## Color Consistency:

3-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color.

## Color Stability:

LED color temperature is warrantied to shift no more than 200K in CCT over a 5 year period.

## Color Uniformity:

RAB's range of CCT (Correlated color temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2008.

## Cold Weather Starting:

The minimum starting temperature is -40°F/-40°C.

## Ambient Temperature:

Suitable for use in 40°C (104°F) ambient temperatures.



CLED2X13YBBW/PCS - continued

**Surge Protection:**

4KV

**Fixture Efficacy:**

42 Lumens per Watt

**Color Temperature (Nominal CCT):**

3000K

**Color Accuracy:**

86 CRI

**California Title 24:**

CLED2X13BB/PCS complies with 2013 California Title 24 building and electrical codes as a commercial outdoor non-pole-mounted fixture < 30 Watts.

**IESNA LM-79 & IESNA LM-80 Testing:**

RAB LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 and 80, and have received the Department of Energy "Lighting Facts" label.

**Equivalency:**

The CLED2X13 is Equivalent in delivered lumens to a 42W CFL or 70W Metal Halide Ceiling Fixture.

**HID Replacement Range:**

The CLED2X13 can be used to replace 70-100W Metal Halide Ceiling Lights based on delivered lumens.

:  
.

**Country of Origin:**

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

**Buy American Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

**Recovery Act (ARRA) Compliant:**

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

**Trade Agreements Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

**GSA Schedule:**

Suitable in accordance with FAR Subpart 25.4.

