

PANEL2X4-44YN

2' x 4' LED panel lights provide smooth and uniform light edge-to-edge for a clean, modern look. For use in drop ceilings or drywall using the optional recessed mounting kit.

Color: White


Weight: 34.0 lbs

LED Info

Watts: 44W
 Color Temp: 3500K
 Color Accuracy: 84
 L70 Lifespan: 100000
 LM79 Lumens: 4608
 Efficacy: 102 LPW

Driver Info

Type: Constant Current
 120V: 0.37A
 208V: 0.25A
 240V: 0.22A
 277V: 0.19A
 Input Watts: 45W
 Efficiency: 97%



Technical Specifications

UL Listing:

Suitable for damp locations. Recommended for indoor use only.

IC Rating:

Suitable for insulated ceilings.

LEDs:

Long-life, High efficiency, micro-power, surface mount LEDs; binned and mixed for uniform light output and color.

Lifespan:

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

Drivers:

Two (2) Constant Current, Class 2, 100-277V, 50/60Hz, 4kV Surge Protection, 450mA, 100-277V: 0.4A, Power Factor 99.3%

THD:

7.8% at 120V, 12% at 277V

Lens:

High-transmission acrylic lens with excellent distribution and uniformity.

Color Consistency:

3-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color.

Housing:

Lightweight housing is constructed of extruded aluminum.

Installation:

Modular splice box/driver compartment for quick installation. Integral Tee-grid ceiling clips make installation easy and secure.

DLC Listed:

This product is on Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities.

Finish:

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contains no VOC or toxic heavy metals.

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80, and have received the Department of Energy "Lighting Facts" label.

California Title 24:

See PANEL2x4-44/D10 for a 2013 California Title 24 compliant product. Any additional component requirements will be listed in the Title 24 section under technical specifications on the product page.

Green Technology:

Mercury and UV free, and RoHS compliant. Polyester powder coat finish formulated without the use of VOC or toxic heavy metals.

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish.

